

HALE

TRAILER

BRAKE & WHEEL



A024533
VIN: 941002

SALES | RENTALS | PARTS | SERVICE

| | | | |
|--------------------------|---------------------|-------------------------|---------------------|
| Allentown, PA: | 800-383-8894 | Little Rock, AR: | 833-424-8944 |
| Baltimore, MD: | 888-601-7500 | Portland, ME: | 800-325-4253 |
| Concord, NC: | 800-438-2250 | Raleigh, NC: | 833-418-9777 |
| Delmar, DE: | 866-486-1400 | Scranton, PA: | 800-569-1400 |
| Des Moines, IA: | 888-673-5011 | Springfield, MA: | 800-854-5306 |
| Elkton, MD: | 800-544-7127 | Voorhees, NJ: | 866-315-0235 |
| Jacksonville, FL: | 800-828-3055 | Walpole, MA: | 800-854-5310 |

haletrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

ART-60-323

Description

EA New Ace Rolloff Trailer ART-60-323 Tri-axle Spring
VIN# 1B9RA3239SC941002

Overall Length: 33' 6"
Container Frame Length: 32'
Kingpin to Last Axle: 26' 7"
Rated 60,000 lbs. Lift Capacity
Container Size Range- 10'-32' Outside Rail Containers

MAIN FRAME:

12"X 4"X 1/4" Rectangular Tubing
12"X 4" Cross Members for Main Frame
Top Wrap: 1/2" X 4" Flat Bar Wear Pad
Bottom Wrap: 3/4" x 4" Flat Bar
1/4" Hollow Truss Mounted Below Main Frame with
1/2" X4" Bottom Wrap
(2) 1 1/4" Fixed Stops at Front of Trailer
(12) 3 1/2" Rollers Welded to Outside Frame
3/4" King Pin Plate with 3/4" Plate Supports & 2" Round Bar
Stiffener

STABILIZER FRAME:

4"X4"X 1/4" Tube with 4"x4"x3/8" Angle Wrap
Hinges: 2" Round Bar
28"x16"x5/8" Draft Arm Support Plates

HYDRAULICS:

(2) 8.5" - 4 Stage Telescopic Main Lift Cylinder 133,000
lbs. @ 2,400 PSI
(2) Ace Independent Reeves: 3 1/2 Rod 7" Bore Reeving
Cylinder 88,000 lbs. ea.
Directional Valve with Pressure Gauges and Adjustable
PSI - Set to 2,450 PSI
Hoses: 3/4" 3000 PSI Hoses with Nylon Covering
Hydraulic Pipes: 3/4" Steel Pipe
Standard JIC Fitting on All Hydraulics
NO HYDRAULICS IN REAR OF TRAILER
CABLE AND AFFILIATED COMPONENTS:
Cable-7/8" IWRC Cable, (4) Cable Clamps, Cable Button
with Cast Ring
Pulleys: 10" Sheave with 2.5" Pin (Qty 3)
Pulley Block - Independent (2)
Independent Pulley Track

RUNNING GEAR:

H900 Single Point 50,000 lbs. Suspension

Suspension Hanger: 21" Fabricated I-Beam
(2) 25,000 lbs. 5" Round Axles
LIFT AXLE: 20K 21ST RIDEWELL LIFT AXLE
Brake Control: Spring Loaded 16" x7.5"
ABS: 2S1M
10 Hole Uni-Mount Hubs & Drums
10 Hole Uni-Mount Rims w/11R22.5 Tires
Fenders- Rubber 2-Ply
Ace Logo Rubber Mud Flap with Hook
2-Speed Landing Gear 120K lbs.

LIGHTING & SAFETY

All L.E.D Lights
All Lights Meet DOT #108
Lights & Harness- Truck Lite
Body Hoist Up Alarm- LED Strobe
ICC REGULATED BUMPER- AIR ACTUATED
Meets FMCSA 49 CFR § 393.86
(4) Nylon Tie Down Strap - More can be added*

PAINT

Cleaned, Primed, Painted Industrial Epoxy (Black)
WARRANTY- In Years
(5) On Main Frame - Excluded Rollers and Greaseable
Items

(1) All Hydraulic Components
(1) on All Items Manufactured by Ace
Axles & Suspension are subject to manufacturer
discretion

EA Removable Stop Set Drive&Pass
For proper weight distribution on containers shorter
than trailers overall length

EA RR Roll-Off Complete 32' Hyd
Roll Rite Tarping System (Hydraulic) - Hydraulic Ace
Tower

EA Front Work Lights - Installed
(2) LED RECTANGLE LIGHTS

EA Automatic Tire Inflation Kit

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.