



A024555 VIN: 24563 SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894 Little Rock, AR: 833-424-8944 Baltimore, MD: 888-601-7500 Portland, ME: 800-325-4253 Concord, NC: 800-438-2250 Raleigh, NC 833-418-9777

Delmar, DE: 866-486-1400 Scranton, PA: 800-569-1400 Des Moines, IA: 888-673-5011 Springfield, MA: 800-854-5306

Elkton, MD: 800-544-7127 Voorhees, NJ: 866-315-0235 Jacksonville, FL: 800-828-3055 Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer f

800-232-6535 *FINANCING AVAILABLE

OVERALL LENGTH OVERALL WIDTH 102"

CAPACITY 130,000 LB DISTRIBUTED; 110,000 LB IN 10' CLOSED

WEIGHT +/- 3%

GOOSENECK

LENGTH 12' 5" NARROW NECK

KINGPIN SETTING 16" SWING CLEARANCE 105"

5TH WHEEL HEIGHT 52" W/7 VARIABLE RIDE HEIGHT POSITIONS

HYDRAULICS RUNS OFF WET KIT FLIP NECK PREP FOR 96" FLIP NECK 96" FLIP NECK EXTENSION

95,000 LBS MAX KING PIN FORCE LIFTING CAPACITY WITH 96" FLIP NECK ATTACHED TO 12'-5" GOOSENECK

MAIN DECK

LENGTH 30' 1" / OPENING TO 52' 11" 30" MINI DECK

LOADED DECK HEIGHT 24" W/ 6" GROUND CLEARANCE

DECKING 1 1/8" APITONG DECKING, FLUSH, CENTER COVERED CROSSMEMBER 6" JR. I-BEAM AND KNEE BRACES ON 12" CENTERS

BEAMS (4) FAB I-BEAMS

D-RINGS (10) BENT D-RINGS PER SIDE

REMOVABLE SWINGOUT OUTRIGGERS ON 24" CENTERS, AND DOUBLE FRONT OUTRIGGERS OUTRIGGER CHAIN DROPS

(10) CHAIN DROPS PER SIDE - OUTSIDE BEAMS - STAGGER BETWEEN D-RINGS

REAR DECK

LENGTH 14' 6" LOADED DECK HEIGHT 41"

AXLES (3) 25,000 LBS. NOMINAL (5/8" WALL) SUSPENSION HENDRICKSON / 25,000 CAPACITY / AIR RIDE

AXLE SPACING

ABS N/A SPRING BRAKES ON 1 AXLES TIRES 275 / 70R / 22.5 (J) MICHELIN

WHEELS 8.25 X 22.5 10-HOLE PILOT MOUNT, POLISHED ALUMINUM OUTSIDE, STEEL INSIDE, DISC

BRAKES 16 1/2" X 7" DRUMS OUTBOARD

ELECTRICAL 12V SEALED GROTE SYSTEM WITH (3) TAIL LIGHT ALUMINUM PACKAGE

4" AMBER STROBE WITH SWITCH TO MAKE 3RD TAIL LIGHT

DECKING 1 1/8" APITONG DECKING FLUSH, COVERED WHEELS WITH OPEN BOOM TROUGH

D-RINGS (1) PAN STYLE D-RING IN EACH CORNER D-RINGS (2) BENT D-RINGS IN TAIL CHANNEL

BLACK **PAINT**

(2) PAIR OF FLAG HOLDERS **ADDITIONAL**

RAISE AND LOWER VALVE

PREP FOR A TWO AXLE POWER BOOSTER (3+2)

MANUAL RIDE HEIGHT CONTROL 31" FRONT LOADING RAMPS

(1) EXTRA CLEARANCE LIGHTS PER SIDE ON GOOSENECK (5) EXTRA CLEARANCE LIGHTS PER SIDE ON MAIN DECK (1) EXTRA CLEARANCE LIGHTS PER SIDE ON WHEEL AREA (2) EXTRA MID TURNS PER SIDE ON THE MAIN DECK

EXTENSION STOPS ON 24" CENTERS

LIQUID FILLED AIR GAUGE

ALUMINUM BOX BETWEEN AXLES ON ROADSIDE FOR AIR COMPONENTS

DETACHABLE WHEEL AREA WITH VERTICAL PINS

PSI TIRE INFLATION SYSTEM

DUST SHIELDS

REFERENCE VIN 23967

TO FIT TO: 22 FA INT 22 FA REAR 42 PMB SO