

SERVICE

833-424-8944

800-325-4253

833-418-9777

800-569-1400

800-854-5306

866-315-0235

800-854-5310

AVAILABLE

BASE MODEL: DC-53   Drop Deck Combo Flatbed	
components	description
CAPACITY	Standard Beam Pkg - 80,000 GVWR (60,000 in 10' Span)
OVERALL LENGTH	53' - Base Weight 12,225#
UPPER DECK LENGTH	10'6"
LOWER DECK LENGTH	42'6"
OVERALL WIDTH	8' 6"
KING PIN SETTING	24" - Tapered Front
UPPER COUPLER PLATE	1/4"
UPPER COUPLER HEIGHT	48"
FRONT SKIRT	Steel
REAR SKIRT	Aluminum
BULKHEAD	Removable Aluminum - 48" - 10" Side Return - DOT Appd
MAIN FRAME	26" FabPreCamb.I-Beams-(80K Pkg 3/8"x 5" Top & 1/2" x 5" Bottom & 3/16" Web)
SIDE RAILS	6"-Alum-Extruded W/Double L Track
FLOOR SILLS	4" I-Beam 12" O.C. HD Pkg
FLOOR DECKING	1-1/4" HD Aluminum W/4 Nailer Boards
WINCHES	12 DOUBLE L (+)#75
WINCH TRACK	Double L Aluminum - Extruded Siderail R/S Only
	·
STRAPS	None
LANDING GEAR	Two Speed
SUSPENSIONS	Air Ride Cush - (1) Fixed Front and (1) Slider Rear (+489#)(Requires Man. O. Ride)
SUSPENSION LOCATION	Cal. Legal (Center of KP to Center of Rear Axle 40')
LIFT AXLE	None
DUMP VALVE	None
SCALES	None
PARKING BRAKES	2 Axle
AXLES	(2) 23K Capacity - Type 30 Chambers - Auto Slacks - ABS - 22.5 Tires
ABS SYSTEM	ABS System 2S/1M
AXLE SPACING	49" & 10'2"
DUST SHEILDS	None
WHEELS	Disc - Hub Piloted - 22.5 (2-AX)- Steel (672#)
TIRES	255/70R 22.5 - 40" Loaded Deck Height - Double Coin
TIRE INFLATION SYSTEM	None
ANTI-SAIL MUD FLAPS	Behind 2 Axles
**Make Sure Winch and Full Spool Can Pass By Mud Flap Bracket.**	
STAKE POCKETS	24" O.C. Sides & 4 Across Front, 3 Across Rear
PIPE SPOOLS	Double
RUB BAND ALUM	3/8" x 3" - Aluminum - Recessed for DOT Tape
DOCK BUMPERS	Rubber Inboard
CARGO TIE DOWN	14 Pair of Recessed Chain Ties Evenly Spaced
CONTAINER TWIST LOCKS	None
TIRE CARRIERS	None
TOOLBOX MATERIAL	None
TOOLBOX TYPE	None
LIGHTS	Sealed Wiring Harness w/ LED Pkg
CUSTOM LIGHTS	None
PAINT	Black
CUSTOM 1.	None
CUSTOM 1.	None
CUSTOM 3.	None
COIL HAUL PACKAGE	None
COIL HAUL FACRAGE	INOTIC