

Model: Axle Attachment **Capacity in tons:** 55

1. DESIGN PARAMETERS

Type Flip-up & removable

Framework Fabricated

Suspension Ridewell air with strap style air lift - may not lift very high due to camber and

prepitch

Axle attachment connections Attachment to be equipped with top and bottom connecting ears, pin tubes with

bolts and nuts, shims, chrome tapered connecting pins, air and electrical

connections

Axle capacity 25,000# - GAWR 24,700# Brakes 16-1/2" x 7" air actuated

Wheels Ten (10) stud; 285.75mm B.C. aluminum disc hub piloted system with oil seals,

inner aluminum wheels polished with outer aluminum wheels Dura-Bright

Anti-lock brake system None

Tires Four (4) 275/70R22.5 (H) 16PR Cooper radials

Bridge width 8'-6"

Axle frame height 41" frame; 37" bolster
Half bolster With flag holder slots
Lash rings 2 at rear bent style

Lights and wiring 12 volt system with the following:

All lights to be LED excluding license plate light

Strobe lights with switch at rear

Wire for battery back-up

Paint Valspar standard Talbert black, R-Cure 800 series paint with zinc rich primer

Mudflaps Talbert anti-sail

Additional design specifications 1) 2 rubber bumpers on top

54" axle spacingOver ride chains

4) Estimated empty weight: 3,060#

Compatibility With existing Talbert Trailer, 55SA or 55CC (SN44245)