

# HALE

## TRAILER

### BRAKE & WHEEL



**A025277**  
**VIN: 44334**

**SALES | RENTALS | PARTS | SERVICE**

<b>Allentown, PA:</b> 800-383-8894	<b>Little Rock, AR:</b> 833-424-8944
<b>Baltimore, MD:</b> 888-601-7500	<b>Portland, ME:</b> 800-325-4253
<b>Concord, NC:</b> 800-438-2250	<b>Raleigh, NC:</b> 833-418-9777
<b>Delmar, DE:</b> 866-486-1400	<b>Scranton, PA:</b> 800-569-1400
<b>Des Moines, IA:</b> 888-673-5011	<b>Springfield, MA:</b> 800-854-5306
<b>Elkton, MD:</b> 800-544-7127	<b>Voorhees, NJ:</b> 866-315-0235
<b>Jacksonville, FL:</b> 800-828-3055	<b>Walpole, MA:</b> 800-854-5310

haletrailer.com | @haletrailer     

**800-232-6535** \*FINANCING AVAILABLE

**Model:** 5th Axle Attachment  
**Capacity in tons:** 65

### 1. DESIGN PARAMETERS

Type	Flip-up & removable
Framework	Fabricated
Suspension	30,000# Ridewell air ride
Axle attachment connections	Attachment to be equipped with top and bottom connecting ears, pin tubes with bolts and nuts, shims, chrome tapered connecting pins, air and electrical connections
Axle capacity	25,000# - GAWR 24,700#
Brakes	16-1/2" x 7" air actuated
Wheels	Ten (10) stud; 285.75mm B.C. aluminum/steel disc hub piloted system with oil seals, inner wheels steel with outer aluminum wheels polished
Anti-lock brake system	None
Tires	Four (4) 275/70R22.5 (H) 16PR radials
Bridge width	8'-6"
Axle frame height	41" main beams; 37" bolsters
Half bolster	With flag holder slots
Lash rings	2 at rear (bent style)
Lights and wiring	12 volt system with the following: All lights to be LED excluding license plate light All marker/I.D. lights to be 3/4" bullet style 4 combination (2 PER SIDE) stop/turn/tail and back-up lights, back-up lights wired to switch on marker light circuit Strobe lights with switch at rear Wire for battery back-up
Paint	Standard Talbert black, R Cure 800 series paint with ZINC RICH
Mudflaps	Talbert anti-sail
Additional design specifications	<ol style="list-style-type: none"> <li>1) Reinforced for use as a 5th axle attachment in a 3+2 spread</li> <li>2) 2 rubber bumpers on top</li> <li>3) 60" axle spacing</li> <li>4) Over ride chains</li> <li>5) Liquid filled air gauge in curb side air bag with decal</li> <li>6) Estimated weight = 2,950#</li> </ol>
Compatibility	<p>With 65SA/70CC trailer (ref. SN44332)            With 4th intermediate axle attachment (ref. SN44333)            With E2 Nitro (ref. AN6145)</p>

#### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.