

HALE

TRAILER

BRAKE & WHEEL

A025313

VIN: 231879



SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894

Little Rock, AR: 833-424-8944

Baltimore, MD: 888-601-7500

Portland, ME: 800-325-4253

Concord, NC: 800-438-2250

Raleigh, NC: 833-418-9777

Delmar, DE: 866-486-1400

Scranton, PA: 800-569-1400

Des Moines, IA: 888-673-5011

Springfield, MA: 800-854-5306

Elkton, MD: 800-544-7127

Voorhees, NJ: 866-315-0235

Jacksonville, FL: 800-828-3055

Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

ITEM	DESCRIPTION
TYPE	MANAC, FLIP UP FOR LOWBED.
DIMENSIONS	
LENGTH	5'-11 5/8" (center of bushings to rear).
WIDTH	102".
COUPLING	
COUPLER PLATE	4 anchor plates with bushings and 4 zinc plated connecting pins 2 1/2" diameter.
STRUCTURE	
FLANGES	3/8" x 4", 100 000 psi steel., 1" taper, 17 3/4" high at front.
WEB	3/16" 100 000 psi steel.
ENDS	
BUMPER	8"x 4"x 3/16" tubing, including supports with flags, wide load sign support, 2 small rubber docks bumper on top and one "D" rings welded in center, (Buyer B-50).
ELECTRICAL	
FRONT CONNECTOR	One cord with 7 ways male connector.
ELECTRICAL SYSTEM	Shock proof lights, polycarbonate lenses, in compliance with CMVSS 108.
MAIN SYSTEM	Grote Ultra blue LED, sealed beams, in a closed back rubber grommet. (tail lights with male pins #54332, markers #47122 (2 1/2" dia.), licence light #60280-M).
BOGIE	
BOGIE	Fixed.
SUSPENSION	Hendrickson HT-300US (9), single, **to fit with unit #225792, 54" spread**
U-BOLTS	With nuts at bottom.
SPRINGS	Air.
AXLE(S)	Ingersoll, F22T, 25 000 lbs. capacity.
SPIDERS	Welded.
CAM SHAFTS	28 splines with enclosures, for Ingersoll axles.
TRACK	75 1/2".
DUST SHIELDS	Steel, bolted.
BRAKES	16 1/2" standard, long life IMT25XL Ingersoll lining.
BEARINGS	HM 218248 and HM 212049.
SLACK ADJUSTERS	Meritor, automatic, 28 splines, (6").
SEALS	Stemco, "Guardian" type, with "Gearlube" mineral oil, SAE 80W90.
BRAKE CHAMBERS	T.S.E. brake, "Omnibrake" (30-30), long stroke. (4 years warranty by T.S.E. for parts only).
HUBS AND DRUMS	WEBB, 10 studs disc hubs, balanced drums 117 lbs, outboard mount, 285.75mm B.C., single flange nuts. For dual aluminum wheels. (Heavy duty 25000 lbs cap.)
RIMS	Alcoa, aluminum, "ULTRA ONE vHub", 22.5 x 8.25, disc (10 holes), 285.75mm B.C., single flange nuts.



ITEM	DESCRIPTION
SPACERS	Wheel guard 10 holes. Located between the inside wheel and the drum.
TIRES	Continental, 305/70 R 22.5 HSR1 18 ply (40")
AIR SYSTEM GLAD HANDS AIR VALVES STROBE LIGHTS	Flexible. Sealco, synflex 3/8" diameter. Sealed beams (Grote LED #77353 strobe) amber. Qty: (1) each side. toggle switch installed at rear.
ACCESSORIES REGISTRATION HOLDER MUD FLAPS	One aluminum cylindre. One set, rubber with Manac logo and vertical grooves to reduce spray.
FINISHING PAINT PAINT AXLE(S) PAINTED HUBS WHEELS OR RIMS RETROREFLECTIVE TAPES	Shot blasted, one coat of zinc primer and two polyurethane acrylic top coats Color: black, code: PPG AU37-FP908. **Zinc** primer instead of epoxy primer. One polyurethane acrylic top coat. Color: black, code: PPG AU37-FP908. Black. Natural. Conspicuity striping in compliance with CMVSS 108. Gray and red, each side, fully covers rear bumper.
ADDITIONAL OPTIONS AJUSTEMENT UNIT COUPLED TO	Done on new unit. #225792
ANNEX(ES) ATTACHED	SER#2M571018XS1231879
CONFORMITY	This semi-trailer does not comply with GHG regulations. Should GHG regulations come into force prior to the production of the trailer(s), Manac will have the obligation to ensure the trailer(s) produced meet minimum GHG guidelines. Any modifications required to meet the GHG regulations will be added to the initial purchase price and charged back to the customer.

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
 Equipment availability, prices and specifications are subject to change without notice.