

HALE

TRAILER

BRAKE & WHEEL



Resale Inventory
A025407
VIN: 33284

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894	Little Rock, AR: 833-424-8944
Baltimore, MD: 888-601-7500	Portland, ME: 800-325-4253
Concord, NC: 800-438-2250	Raleigh, NC: 833-418-9777
Delmar, DE: 866-486-1400	Scranton, PA: 800-569-1400
Des Moines, IA: 888-673-5011	Springfield, MA: 800-854-5306
Elkton, MD: 800-544-7127	Voorhees, NJ: 866-315-0235
Jacksonville, FL: 800-828-3055	Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

Model:T(4)-55SA-HRG-(EC3/1)-T1
Capacity in tons: 55

Gooseneck design	RATCHET TYPE
Loaded 5th wheel height	52"
Swing radius	108"
Alternate kingpin	Removable kingpin stations for 108" and 96" swing radius
Support cylinder	Hydraulically operated
Power source	Hydraulic couplings: 3/4" fixed at front of gooseneck
Additional gooseneck specifications	Gooseneck light bar with 4 L.E.D. stop/tail/turn lights and 2 clear lights with switch, back of light bar protected.
Gooseneck locks	RATCHET TYPE gooseneck
Electrical receptacle	Seven pin connector
Additional gooseneck specifications	None
Deck section design	Four beam
Deck section length	25'-0" (24'-6" clear)
Deck section width	8'-6"
Loaded road clearance	6"
Loaded deck height	20"
Flooring	1-1/2" apitong secured with deck screws; no lumber between mainbeams
Mainbeams	14" T-1A
Gooseneck/deck connection	Pin and plate with remote lock
Deck/rear bridge connection	Fixed/welded
Outriggers	12" swinging/removable with double hook-on at front of deck
Heavy duty front folding ramps	32" with smoothplate and traction bars
Additional deck specifications	Recess last 4 deck crossmembers in deck between mainbeams and cover with 1/4" plate
Slope front of deck top down	Yes with plate and traction bars
Slope front of deck bottom up	None
Expanded metal	Between mainbeams 1st deck section at front and 1st deck section ahead of deck boom well
Rear bridge section width	8'-6"
Loaded rear bridge height	41"
Number of axles	3
Axle capacity	25,000# GAWR = 24,700#
Axle spacing	54"
Brakes	16-1/2" X 7" air actuated with spring brakes on one axle
Anti-lock brake system	None required - GVWR is greater than 120,000#
Wheels	Ten (10) stud; 285.75mm B.C. aluminum/steel disc hub piloted system with oil seals, inner wheels steel with outer aluminum wheels polished
Tires	Twelve (12) 275/70R22.5 (H) 16 PR radials
Suspension	Ridewell air
Suspension options	1) - Override chains on all axles 2) - Talbert manual raising and lowering (+3", -3") 3) - Air lift on axle 3

Recessed crossmembers	4) - Manual exhaust valve
Wide center bolster	Yes - 1st member recessed additionally
Rear half bolster	Yes with chain slots and flagholder slots
Front bridge ramp	Rear of axle 3 with flagholder slots
Rear bridge fenders	Sloped to deck outboard of mainbeams with plate and traction bars
Additional rear bridge specifications	3/8" floorplate over tires only 1) - Omit 1st crossmember in rear bridge section (shock mount cross member) for open boom well 2) - Connections for future 4th axle and spreader bar
Axle extension	None
Lights and wiring	12 volt system with the following: All lights to be L.E.D. including mid-turn, excluding license plate light 3 markers each side of deck including mid-turn Strobe lights with switch at rear of axle 3 Battery back-up system with switch to flash all marker/tail lights and strobes
Paint	Standard Talbert red
Lash rings	34 Total 10 each side of deck (bent style), 20 total 2 each side between deck mainbeams in the first two deck sections (bent style), 4 total 2 each side mounted on side of deck boom well plate inline with the last two crossmembers of deck (straight style), 4 total 1 each bolster and half bolster end (straight style), 6 total
Design notes	Frame is reinforced for a future axle extension
Additional general specifications	None

DISCLAIMER

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.