

HALE

TRAILER





BRAKE & WHEEL



A025408
VIN: P3268

SALES | RENTALS | PARTS | SERVICE

| | |
|---------------------------------------|--------------------------------------|
| Allentown, PA: 800-383-8894 | Little Rock, AR: 833-424-8944 |
| Baltimore, MD: 888-601-7500 | Portland, ME: 800-325-4253 |
| Concord, NC: 800-438-2250 | Raleigh, NC: 833-418-9777 |
| Delmar, DE: 866-486-1400 | Scranton, PA: 800-569-1400 |
| Des Moines, IA: 888-673-5011 | Springfield, MA: 800-854-5306 |
| Elkton, MD: 800-544-7127 | Voorhees, NJ: 866-315-0235 |
| Jacksonville, FL: 800-828-3055 | Walpole, MA: 800-854-5310 |

haletrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

| Flip Axle (Model: REN FA54) | |
|--|-------------------------|
| AXR40**54RS | Est. Wt.: 2,790# +/- 3% |
| Compatibility: Renegade 18, N18, 20, N20, X20, XN20 | |
| Length: 4 feet 6 inches | |
| Width: 8 feet 6 inches | |
| Flooring: 1 1/8 inch nominal wood (full width) | |
| Number of Axles: 1 | |
| Axle Capacity: 25,000 lb. nominal capacity per axle NOTE: GAWR determined by suspension type, brakes, tires and other components. | |
| Axle Spread: 54.5 inches (between axles) | |
| Brakes: 16.5 inches x 7 inches with 5.5 inches autoslacks - heavy duty brake drums - outboard mount | |
| Dust Shields: None | |
| Suspension: Air ride with automatic controls | |
| Accent Package: Stainless steel bumper insert | |
| Tires: 255/70R 22.5 H ply OEM Standard | |
| Wheels: 8.25 x 22.5 Outer LVL One buffed/steel disc inside - hub-piloted | |
| Hubodometer: None Standard | |
| Tire Inflation: None Standard | |
| Electrical System: DOT sealed beam and harness with LED lights - | |
| Paint: Fontaine black polyurethane enamel | |
| Lash Rings: 2 pair - 4 total | |
| Flag Holders: 1 pair flag holders | |
| VIN Plate: Bilingual VIN plate | |

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.