

HALE

TRAILER

BRAKE & WHEEL



A025590
VIN: 024560

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer

800-232-6535 *FINANCING AVAILABLE

XL SPECIALIZED TRAILERS

XL 130 Hydraulic Detachable Extendable

OVERALL LENGTH	57'
OVERALL WIDTH	102"
CAPACITY	130,000 LB DISTRIBUTED; 110,000 LB IN 10' CLOSED
WEIGHT +/- 3%	0,000 LB

GOOSENECK

LENGTH	12' 5" NARROW NECK
KINGPIN SETTING	16"
SWING CLEARANCE	105"
5TH WHEEL HEIGHT	52" W/7 VARIABLE RIDE HEIGHT POSITIONS
HYDRAULICS	RUNS OFF WET KIT
FLIP NECK	PREP FOR 96" FLIP NECK 96" FLIP NECK EXTENSION 95,000 LBS MAX KING PIN FORCE LIFTING CAPACITY WITH 96" FLIP NECK ATTACHED TO 12'-5" GOOSENECK

MAIN DECK

LENGTH	30' 1" / OPENING TO 52' 11" 30" MINI DECK
LOADED DECK HEIGHT	24" W/ 6" GROUND CLEARANCE
DECKING	1 1/8" APITONG DECKING, FLUSH, CENTER COVERED
CROSSMEMBER	6" JR. I-BEAM AND KNEE BRACES ON 12" CENTERS
BEAMS	(4) FAB I-BEAMS
D-RINGS	(10) BENT D-RINGS PER SIDE
OUTRIGGER	REMOVABLE SWINGOUT OUTRIGGERS - 24" O/C WITH DOUBLE FRONT OUTRIGGER
CHAIN DROPS	(10) CHAIN DROPS PER SIDE - OUTSIDE BEAMS - STAGGER BETWEEN D-RINGS

REAR DECK

LENGTH	14' 6"
LOADED DECK HEIGHT	36"
AXLES	(3) 25,000 LBS. NOMINAL (5/8" WALL)
SUSPENSION	HENDRICKSON / 25,000 CAPACITY / AIR RIDE
AXLE SPACING	60"
ABS	N/A SPRING BRAKES ON 1 AXLES
TIRES	245 / 70R / 17.5 (J) MICHELIN
WHEELS	6.75 X 17.5 8-HOLE PILOT MOUNT, POLISHED ALUMINUM OUTSIDE, STEEL INSIDE, DISC
BRAKES	12 1/4" X 7 1/2"
DRUMS	HUB PILOT / OUTBOARD DRUMS
ELECTRICAL	12V SEALED GROTE SYSTEM WITH (3) TAIL LIGHT ALUMINUM PACKAGE 4" AMBER STROBE WITH SWITCH TO MAKE 3RD TAIL LIGHT
DECKING	1 1/8" APITONG DECKING FLUSH, COVERED WHEELS WITH OPEN BOOM TROUGH
D-RINGS	(1) PAN STYLE D-RING IN EACH CORNER
D-RINGS	(2) BENT D-RINGS IN TAIL CHANNEL

PAINT

BLACK

ADDITIONAL

(2) PAIR OF FLAG HOLDERS
RAISE AND LOWER VALVE
PREP FOR A TWO AXLE POWER BOOSTER (3+2)
MANUAL RIDE HEIGHT CONTROL
31" FRONT LOADING RAMPS
(1) EXTRA CLEARANCE LIGHTS PER SIDE ON GOOSENECK
(5) EXTRA CLEARANCE LIGHTS PER SIDE ON MAIN DECK
(1) EXTRA CLEARANCE LIGHTS PER SIDE ON WHEEL AREA
(2) EXTRA MID TURNS PER SIDE ON THE MAIN DECK
EXTENSION STOPS ON 24" CENTERS
LIQUID FILLED AIR GAUGE
ALUMINUM BOX BETWEEN AXLES ON ROADSIDE FOR AIR COMPONENTS
DETACHABLE WHEEL AREA WITH VERTICAL PINS
PSI TIRE INFLATION SYSTEM
DUST SHIELDS

REFERENCE VIN 23964
TO FIT TO:
22 FA INT 24561
22 FA REAR 24562
42 PMB SO 80129

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.