| | SALES | RENTALS | PARTS | SERVICE |
|-------------|-------------------|-------------------|------------------|--------------|
| | Allentown, PA: | 800-383-8894 | Little Rock, AR: | 833-424-8944 |
| | Baltimore, MD: | 888-601-7500 | Portland, ME: | 800-325-4253 |
| TRAILE | Concord, NC: | 800-438-2250 | Raleigh, NC | 833-418-9777 |
| BRAKE & WHI | EEL Delmar, DE: | 866-486-1400 | Scranton, PA: | 800-569-1400 |
| | Des Moines, IA: | 888-673-5011 | Springfield, MA: | 800-854-5306 |
| | Elkton, MD: | 800-544-7127 | Voorhees, NJ: | 866-315-0235 |
| A025926 | Jacksonville, FL: | 800-828-3055 | Walpole, MA: | 800-854-5310 |
| VIN: 86119 | haletrailer | .com @halet | railer f У | |
| | 800-232 | 2-65 <u>35</u> *F | FINANCING | AVAILABLE |

CHIPPER

LIGHT PANEL

Model # TNAR45FR920

| Weight | 13764 lbs. *** | Cubic Yards 100 |
|----------------|-----------------------------------|--|
| ODY | | |
| LOAD PROFILE | | MATERIAL, 80K GVWR |
| LENGTH | | 45 |
| WIDTH | | 102 |
| DRIVE UNIT | | KEITH, 25 SLAT 3-1/2 IN. CYLINDER (HEAVY DUTY) |
| | keith 26 slat drive 2293 horizona | il seal 3 1/2 cyl |
| FLOOR | | KEITH 2190 (1975), 7/32 IN. (102 W) |
| | ADD 24 INCH WEAR STRIPS TO |) END OF SLATS |
| HYDRAULIC PIP | Έ | STAINLESS STEEL HYDRAULIC PIPE |
| CROSSMEMBER | R TYPE | HEAVY FULL |
| CROSSMEMBER | R SPACING | 5-1/4 IN. I-BEAMS, 12 O.C. |
| RUBBER SEAL | | NONE |
| WALL HEIGHT | | 92 |
| FRONT WALL T | HICKNESS | .062 |
| | ALL BLACK PREPAINTED PANE | ELS |
| MID WALL THIC | KNESS | .062 |
| REAR WALL TH | ICKNESS | .062 |
| | LAST SHEET AT REAR TO BE ." | 125" THICKNESS |
| FULL LID | | NONE |
| TOP RAIL OPTIC | NC | STD TOP RAIL |
| | STD TOP RAIL | |
| UPRIGHT SPAC | ING | 14 IN. |
| | 12" UPRIGHT SPACING | |
| ADDITIONAL UP | PRIGHTS AT FRONT | NO |
| BULKHEAD | | .165 |
| BULKHEAD STE | PS | LADDER ONLY |
| | 16" WIDE LADDER | |
| FRONT FENDER | RS WITH FLAPS | NONE |
| BOTTOM RAIL | | SQUARE NO CLEAN OUT |
| UPPER CROSS | TUBES / ARCH | 6 |
| | USE ONLY 3 CROSS TUBES (R | OLLED GALVANIZED CROSSTUBES) BETWEEN FRONT AND REAR CAPS |
| FRONT CAP | | YES |
| | W/ GRAB HANDLE | |
| REAR CAP | | YES |
| TIRE CARRIER | | NONE |
| | | |
| IGHTS | | |
| LIGHT TYPE | | TRUCKLITE L.E.D. W/ GROMMET |

4 LARGE-3 SMALL-4 LARGE (SPLIT LIGHT PANEL) OOOO 000 OOOO

| APRON | | NONE | |
|--------------|---|---|--|
| STD. MARKER | LIGHTS | (5) EACH SIDE | |
| | (7) PER SIDE TOP & BOTTOM PENNY L | IGHTS. | |
| MID-TURNS | | (1) PAIR L.E.D. (COMBO) | |
| BACK-UP LIGH | ITS | (1) PAIR L.E.D. BACK UP LIGHTS | |
| | ADD ONE PAIR OF WORKLIGHTS TO IN TARP SWITCH - ADD RED INDICATOR L | SIDE FRONT - TO BE DUAL STOP/WORK LIGHT COMBO 4" LIGHT . WIRE TO FRONT ON .IGHT WHEN WORKLIGHTS ARE ON | |
| AUXILIARY CA | BLE | 7 WAY (ISO) | |
| | B/U ON BLACK MAIN | | |
| REAR POCKET | LIGHTS | (1) PAIR | |

GATE

| GATE OPERATION | BI-FOLD | |
|--------------------------|-------------------------------|--|
| SWING DOORS - QUAD LOCKS | | |
| GATE OPTIONS | SOLID .080 | |
| BLACK DURAPLATE | | |
| HINGE TYPE | BARN DOORS SIDE SWING (ALUM.) | |
| S/S HINGES | | |
| SAFETY CHAIN | YES | |
| WINDERS / SAFETY LATCH | NONE | |
| GATE STEPS | NONE | |
| TARP HOOKS | NONE | |

| PRIMARY A | XLES | | |
|--------------|---------------------------|--|--|
| MODEL | | CLOSED TANDEM | |
| | ADDED CROSSMEMBER GUSSETS | OVER SUB FRAME AREA | |
| NO. OF PRIMA | RY AXLES | 1 | |
| SUSPENSION | | HEND. INTRAAX AA-250 TP - 25K (77.5) | |
| | GAWR 24K | | |
| AXLE SPACING | 3 | 60 | |
| | REAR AXLE SET AT 72" | | |
| SUB-FRAME | | TANDEM (ALUM T-BEAM) | |
| AXLES | | AXLE FOR INTRAAX ONLY | |
| BRAKES | | DISC BRAKES - HEND. MAXX22T W/ DUCTILE STEEL HUB (23,000 | |
| | | LB ONLY) | |
| CAM GUARDS | | NONE | |
| HUB AND DRU | M | NONE, DISC BRAKES | |
| TIRES | | GENERAL RA 11 R 22.5 16 PLY | |
| WHEELS | | ALUMINUM HP 22.5X8.25 - ALL POLISHED (XP) | |
| | | | |

| IFT AXLES NO. OF LIFT AXLES | 1 | |
|--------------------------------|--|--|
| LIFT AXLE SUSPENSION | HEND. INTRAAX AAL-25K (77.5) | |
| LIFT KIT | HEND. UBL-002 (INTRAAX AAL) | |
| LIFT AXLE DISTANCE | 60 | |
| LIFT AXLE | AXLE FOR INTRAAX ONLY | |
| LIFT AXLE BRAKES | DISC BRAKES - HEND. MAXX22T W/ DUCTILE STEEL HUB (23,000 LB ONLY) | |
| LIFT AXLE CAM GUARDS | NONE | |
| LIFT AXLE HUB AND DRUM | NONE, DISC BRAKES | |
| LIFT AXLE TIRES | GENERAL RA 11 R 22.5 16 PLY | |
| LIFT AXLE WHEELS | ALUMINUM HP 22.5X8.25 - ALL POLISHED (XP) | |
| LIFT AXLE CONTROLS | AIR IN CAB & BALL VALVE NO/ REG. | |
| W/ AUTO LIFT | | |
| FREE WHEEL VALVE | NONE | |

| STEERABLE LIFT AXLES | | |
|---------------------------|------|--|
| NO. OF STEERABLE AXLES | 0 | |
| STEERABLE AXLE SUSPENSION | NONE | |
| STEERABLE AXLE DISTANCE | N/A | |
| STEERABLE AXLES | NONE | |
| | | |

| STEERABLE AXLE BRAKES | NONE |
|------------------------------|------|
| STEERABLE AXLE HUB AND DRUMS | NONE |
| STEERABLE AXLE TIRES | NONE |
| STEERABLE AXLE WHEELS | NONE |
| STEERABLE AXLE CONTROLS | NONE |
| STEERABLE AXLE LIFT KIT | NONE |

| HASSIS | |
|--|--|
| PIN SETTING | 36 |
| 5TH WHEEL PLATE | 3/8 LOW PROFILE |
| 5TH WHEEL PLATE HEIGHT | 48 IN. HIGH |
| GALVANIZED SUSPENSION HANGERS | INCLUDED W/ SUSPENSION |
| SUSPENSION CONTROL | ELECTRIC THRU AUX. & BALL VALVE |
| QUICK RELEASE GLADHANDS | |
| ABS FOR TRAILER | (1) 2S1M MERITOR / WABCO |
| SLACKS | AUTOMATIC |
| TIRE INFLATION SYSTEM | NONE |
| AXLE LUBRICATION | 5 YR. SYNTHETIC GREASE |
| HUBODOMETER | NONE |
| DUST COVERS | NONE |
| DOLLIES - LANDING GEAR - LANDING LEGS | JOST A451 - (62,500 LB.) - 10 YEAR NO LUBE - STEEL - (REVERSE MOUNT) D.S. |
| ADD ONE PAIR OF WORKLIGHTS NE WORKLIGHTS ARE ON | EAR DOLLIES. WIRE TO FRONT ON TARP SWITCH - ADD RED INDICATOR LIGHT WHEN |
| REGISTRATION HOLDER | BETTS PS-1 W/ SIGHT GLASS (ROUND HOLDER) |
| AIR GAUGE / SYSTEM | YES, IN FRONT |
| ENCLOSURE FOR SWITCHES | NONE |
| AIR TANKS | 12 IN. ALUMINUM TANK |
| HYDRAULIC HOSE FITTING | 1 IN. X 108 IN. HOSE W/ WING FITTING |
| add 45 degree angle at bulkhead | |
| LAPS FRONT OF TIRES | NONE |
| FLAPS REAR OF TIRES | FLAP BEHIND REAR AXLE |
| BUMPER | D.O.T. BUMPER |
| | |

| NONE | |
|----------------------------|------|
| TRIC SIDE ROLL TARP SYSTEM | |
| NONE | |
| NONE | |
| NONE | |
| | NONE |

| PAINT | | |
|------------------|-----------------|--|
| SUSPENSION COLOR | BLACK SOFT COAT | |
| PIN STRIPING | BLACK (931716) | |

DISCLAIMER