



A025950
VIN: 24956

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer



800-232-6535 *FINANCING AVAILABLE

Model: T(4)-55CC-HRG-T1

Capacity in tons: 55

1. GOOSENECK

Gooseneck design
Loaded 5th wheel height
Swing radius
Alternate kingpin
Support cylinder
Power source
Gooseneck locks
Electrical receptacle
Coverplate
Additional gooseneck specifications

RATCHET

52"
108"
Removable kingpin stations for 108" and 90" swing radius
Hydraulically operated with 4" x 3" cylinder mount cross member
Hydraulic couplings: 3/4" fixed at front of gooseneck

RATCHET

Seven pin connector
Aluminum
1) Formed aluminum diamond plate light bar mounted in gooseneck base with 4 LED stop/tail/turn lights and 2 clear work lights wired to marker light circuit with on/off switch
2) Fully enclosed chain bar in gooseneck base with aluminum diamond plate and lockable hinged lid (paddle latches)
3) Full penetration weld on gooseneck gusset
4) Base pivot tube reinforcement

2. DECK

Deck section design
Deck section length
Deck section width
Loaded road clearance
Loaded deck height
Flooring
Mainbeams
Gooseneck/deck connection
Deck/rear bridge connection

Four beam
26'-0" (25'-6" clear)
8'-6"
6"
18"
2" apitong with secured with deck screws; no lumber between main beams
12" T-1A
Horizontal pin and plate with remote lock
Fixed/welded

Outriggers	12" swinging/removable with double hook-on at front of deck (painted Talbert standard black)
Reinforced top flange of sidemember	Full length with 2" chain slots
Additional deck specifications	Bucket well, recess last 4 deck cross members in deck between main beams and cover with 1/4" plate
Slope front of deck top down	With plate and traction bars
Heavy duty front folding ramps	32" with smooth plate and traction bars
Expanded metal	Between main beams, full length up to bucket well
3. REAR BRIDGE	
Rear bridge section width	8'-6"
Loaded rear bridge height	41"
Number of axles	3
Axle capacity	25,000# - GAWR = 24,700#
Axle spacing	54"
Brakes	16-1/2" X 7" air actuated with spring brakes on one axle
Anti-lock brake system	None required - GVWR is greater than 120,000#
1 Wheels	Ten (10) stud; 285.75mm B.C. aluminum/steel disc hub piloted system with oil seals, inner steel wheels black with outer aluminum wheels DURA-BLACK WITH DURA-BLACK CENTER CAPS AND VALVE STEMS
Tires	Twelve (12) 275/70R22.5 (H) 16PR radials
Suspension	Ridewell air
	Air Weigh scale with blue tooth
Suspension options	<ol style="list-style-type: none"> 1) Over ride chains on all axles 2) Talbert manual raising and lowering (+3", -3") 3) Air lift 3rd axle 4) Manual exhaust 5) Liquid filled air gauge in 2nd axle curb side air bag with decal
Rear Bridge Center Section	Boom well, cross members recessed - recess 1st member additionally
	Removable 3/8" floor plate full boom well length (rear of deck to rear of rear bridge), painted Talbert standard black
Wide center bolster	With chain slots & flag holder slots
Rear half bolster	Rear of axle 3 with flag holder slots
	Stainless steel light panel inserts out board main beams
	Stainless steel mud flap brackets
Front bridge ramp	Sloped to deck outside of main beams with plate and traction bars
Rear bridge fenders	3/8" floor plate over tires only
Additional rear bridge specifications	<ol style="list-style-type: none"> 1) Omit 1st cross member in rear bridge section (shock mount cross member) for open boom well 2) Connections for future 4th axle 3) Reflective Oversized Load sign with brackets (Removable/Hinged ref. SN43007)
4. GENERAL	
Lights and wiring	<p>12 volt system with the following:</p> <p>All lights to be LED including mid-turn, excluding license plate light</p> <p>All marker/I.D. lights to be 3/4" bullet style</p> <p>1 marker each side of gooseneck at front</p> <p>5 markers each side of deck including mid-turn</p> <p>4 combination (2 PER SIDE) stop/turn/tail and back-up lights, back-up lights wired to switch on marker light circuit</p> <p>Strobe lights with switch at rear of axle 3</p> <p>Battery back-up system with switch to flash all marker/tail lights and strobes</p>

Paint	Valspar standard Talbert red, R-Cure 800 series paint with ZINC RICH primer. Deck outriggers and removable boom well plate painted Talbert standard black. Use black Talbert logo decals
Lash rings	48 total - 12 each side of deck (bent style), 24 total 2 each side between deck main beams in the first two deck sections (bent style), 4 total 4 each side mounted on side of deck bucket well plate in-line with the last four cross members of deck (bent style), 8 total 1 each bolster and half bolster end (straight style), 6 total 1 each side between rear bridge main beams mounted on the sides of the recessed bolsters (straight style), 6 total
Estimated empty weight	25,210#
Design notes	Not reinforced for spread axle capabilities
Additional general specifications	None

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.