

HALE

TRAILER

BRAKE & WHEEL

A026065

VIN: 235039



SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer



800-232-6535 *FINANCING AVAILABLE

ITEM	DESCRIPTION
TYPE	SEMI-TRAILER, STEEL DROP PLATFORM LEGEND SD
DIMENSIONS	
LENGTH	53'-0"
WIDTH	102", 97" between side rails.
HEIGHT	Floor, approximately 59" high at front and 41" at the bumper.
DROP HEIGHT	20", located at 10'-6" from front.
COUPLING	
COUPLER PLATE	1/4", 80 000 psi steel, plug welded structure.
KING PIN LOCATION	18" from front.
COUPLER HEIGHT	48".
STRUCTURE	44" c/c frame with "CAMBER".
FLANGES	3/8" x 5", 100 000 psi steel, goose neck section.
WEB	1/2" x 5", high tensile, 24" high in center and 16 1/2" above suspension.
GOOSENECK	1/4" plate in king pin area and the remaining in 3/16",
CROSSMEMBERS	80 000 psi steel. 24" high, with holes, parachute shaped, to lighten trailer.
FLOOR	11 1/4" high, 48" straight behind king pin.
FLOOR FASTENING	I beams, 4" @ 3.2 lbs/ft, 80 000 psi steel, galvanised,
SIDE RAILS	16" c/c in gooseneck and the remaining 12" c/c.
SIDE BOXES	Apitong or equivalent, 1 1/8" thick shiplap finished, no preservative.
RUB RAILS	Screws.
CORNERS	10 gauge shaped 80 000 psi steel, 5" width x 5 11/16" height.
FENDERS	3/16" steel plate, 1 5/8" x 3 5/8" interior, 4" high, (USA Dimensions).
KNEE BRACES	Cargo pockets.
X BRACES	3/8" x 2 1/2" shaped steel.
ENDS	Bevelled.
FRONT RAIL	Reinforcement over tires at rear, steel tubing structure, galvanized (G164),
BUMPER	floor full length.
BUMPER	3/16" formed steel plates, galvanized (G164), bolted in web and a
REAR RAIL	crossmembers located each side.
	Between main beams, full length.
ELECTRICAL	
FRONT CONNECTOR	7 way (SAE J560).
ELECTRICAL SYSTEM	Shock proof lights, polycarbonate lenses, in compliance with CMVSS 108.
MAIN SYSTEM	Grote Ultra Blue LED, sealed beams, tail lights, markers lights "Dot",
FLASHERS	identification lights (2 1/2" dia.), licence light.
	Sealed beams LED, one lamp including side marker and flasher,



ITEM	DESCRIPTION
	each side at middle point, amber.
LANDING GEAR SAND SHOES CRANK	AXN, (LG50DUN) 10" x 10". Road side.
BOGIE BASIC MECHANICAL BOGIE	Fixed front suspension and slider bogie at rear Intraax AAZL 23K single, Z frame structure, 6.5" R.H., with "UHMV" slider plastic pads, 4 retainers and 4 pneumatic locking pins "Quik Draw", tandem 54", 65" and 122" spread.
MECHANICAL (GROUND AXLES) SUSPENSION	Hendrickson INTRAAX AANL-23K (6.5), tandem with AAZL-23K N.B.: Winged suspension bracket. For axles with bearings HM 218248 and HM 212049.
SPRINGS	Air.
AXLE(S)	LDA, 5 3/4" diameter, 23 000 lbs. capacity.
CAM SHAFTS	28 splines with enclosures, 10" long.
TRACK	77 1/2".
DUST SHIELDS	None (Intraax axles).
BRAKES	16 1/2" standard, long life H20-HXS Hendrickson lining.
BEARINGS	HM 218248 and HM 212049.
SLACK ADJUSTERS	Meritor, automatic, 28 splines.
SEALS	Stemco, "Guardian" type, with "Gearlube" mineral oil, SAE 80W90.
BRAKE CHAMBERS	T.S.E. brake, "Omnibrake" (30-30), (push rod 9 3/4"). (4 years warranty by T.S.E. for parts only).
HUBS AND DRUMS	10 stud disc hubs, balanced drums outboard mount, 285.75mm B.C., single flange nuts. For dual aluminum wheels.
RIMS	22.5 x 8.25, disc (10 holes), 285.75mm B.C., single flange nuts, 2 hand holes.
TIRES	Continental, 255/70 R 22.5 HSR2 SA 16 ply (36.6")
AIR SYSTEM GLAD HANDS AIR VALVES VALVE(S) VALVE(S)	Fixed. Rockwell Wabco, ABS, 2 sensors 1 modulator. Automatic blow down valve, WITHOUT control box, Fast-brake kit.
ACCESSORIES REGISTRATION HOLDER MUD FLAPS SLIDING TRACK WINCHES	One plastic, Betts-PS-1 or equivalent. One set, rubber black with moose and vertical grooves to reduce spray. Full length, "LL" extruded aluminum, road side. Qty: 12, ANCRA #49207-137-XZ, zinc plated slider (low profil 5 7/8").
FINISHING PAINT	Trailer not painted and no primer applied.



ITEM	DESCRIPTION
FINISHING	Trailer frame prepared and shipped to AZZ Galvanizer to be galvanized.
PAINT	Galvanized Siderails, front sill, and rear sill No paint or primer applied
BOGIE	One coat of epoxy primer and one acrylic urethane top coats, Color: black, code: PPG CCA947255-55. Axles (wheel end) included. (Tandem).
RETROREFLECTIVE TAPES	Conspicuity striping in compliance with CMVSS 108. Gray and red each side, fully covers rear sill and horizontal underride protection bar.
WHEELS OR RIMS	White (power top coat).

CONFORMITY	This semi-trailer does not comply with GHG regulations. Should GHG regulations come into force prior to the production of the trailer(s), Manac will have the obligation to ensure the trailer(s) produced meet minimum GHG guidelines. Any modifications required to meet the GHG regulations will be added to the initial purchase price and charged back to the customer.
------------	--

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.