

HALE

TRAILER

BRAKE & WHEEL



A026090
VIN: 000096

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894	Little Rock, AR: 833-424-8944
Baltimore, MD: 888-601-7500	Portland, ME: 800-325-4253
Concord, NC: 800-438-2250	Raleigh, NC: 833-418-9777
Delmar, DE: 866-486-1400	Scranton, PA: 800-569-1400
Des Moines, IA: 888-673-5011	Springfield, MA: 800-854-5306
Elkton, MD: 800-544-7127	Voorhees, NJ: 866-315-0235
Jacksonville, FL: 800-828-3055	Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

Base Weight: 11,820

30 NTT 30 Ton Tridem Non Tilt Tags

TRAILER	Overall Length	37 ft. 7 in.
	Overall Width	102 in.
	Weight lbs +/- 2%	13248, including options
	A-Frame	6 ft. 11 in. Hi-Tensile Cold Formed Wide Flange Beam
	Hitch	3 in. pintle eye, adjustable 7 position, 19 in. to 33 in.
DECK	Deck Length	24 ft.
	Loaded Deck Height	34 in.
	Main Frame	Hi-Tensile Wide Flange 14 in. @ 26
	Cross Members	Hi-Tensile 6 in. Channel @ 8.2
	Side Rail	Hi-Tensile 8 in. Channel @ 11.5 open on inside
	Floor	1 3/8 in. x 7 in. Keruing Shiplapped
	Landing Gear	Dual Holland Mark V 2 Speed
	Step	*NPO*: Bolt on, Located on Front Corner of deck, Driver side and 1 on Passenger side ahead of lead axle
SUSPENSION/AXLES	Axles	25,000 lbs Capacity 77.5 in. Track ,1 Lift Axle with Control Box
	Spread	49 in.
	Suspension	Heavy Duty spring ride., 1 Ridewell RAR 260 Underslung Air ride 25,000lbs. (includes air gauge)
	Alum Air Tank	*NPO*: Drain plug with cable
	Brakes	Quick Change 12 1/4 in. x 7 in.
	Brake Chamber	#3030, All Axles
	Air Brake System	2S/1M
	Air Tank(s)	Aluminum
	Bearings	Oil Bath
	Slack Adjusters	Automatic
	Hubs & Drums	8 Stud Unimount C / W Cast Drums
	Tires	235/75R17.5 16 ply
	Wheels	Alum. Wheel Pkg. 17.5 (12 polished)
BEAVERTAIL	Length	6 ft. Beavertail, Planked
RAMPS	Length	*NPO*: 38 in. x 96 in. Air Operated Planked
	Ramp Support	*NPO*: Ramp Support, weld on
	Brackets	*NPO*: To hold ramp brace when not in use, 1 per side
GENERAL SPECIFICATIONS	Electrical System	Modular, Vapor Proof GROTE Ultra Blue
	Lights	LED CMVSS 108 / FMVSS 108

GENERAL SPECIFICATIONS

Lights *NPO*: Amber Flashing Strobe Lights(Mounted in Ramps) mounted as close to outside of ramp as possible

Lights *NPO*: Switch for strobes mounted in toolbox

Front Connector SAE J560 7 Pin

Finishing Preparation by Steel Shot Blast, Commercial / Industrial Topcoat, Oven Baked

Lights *NPO*: 5, pr. Of LED Light Enhancement Package, evenly spaced

Color *NPO*: PPG Essentail Yellow # PMX1CF2855

Mudflaps 1 set of BWS at rear

Toolbox *NPO*: Full A Frame mounted with solid bottom and cover , move back to achieve the most room possible

Load Securement 11 pair of D-rings: 9 pr on main deck, evenly spaced, 1 pr on top of main beam at headboard

Fenders *NPO*: Heavy Duty Fenders (17.5) NO traction bars

plate between fenders *NPO*: 5/16 in plate between fenders front top of beavertail to first axle

GVWR Rating is based on standard configuration and a 15% Tongue weight distribution

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.