

HALE

TRAILER

BRAKE & WHEEL



A026157
VIN: AN6138

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

Model: 30'-0" Beam Deck

Capacity in tons: 60

Deck section design	Beam
Deck section length	30'-0" (29'-6" clear)
Deck section width	47" Out to out main beams
Loaded road clearance	6"
Loaded deck height	22"
Flooring	None
Mainbeams	16" T-1A
Gooseneck/deck connection	Pin and plate with remote lock
Deck/rear bridge connection	Vertical pin and plate
Outriggers	None
Reinforced top flange of sidemember	Full length with 2" chain slots
1 Additional deck specifications	1) - Last four (4) cross members recessed 8" below top of main beams 2) - Recess the 3rd, 4th & 5th cross members like bucket well cross members (see sketch)
Slope front of deck top down	Yes with plate and traction bars
Heavy duty front folding ramps	None
1 Expanded metal	Between mainbeams in the first 4 and last 4 deck sections (see sketch) 4.27# Expanded metal with 3/4 x 13 expanded metal on top
1 Lights and wiring	12 volt LED system including mid-turn lights (Ref. SN37025) 10 marker lights (MARKERS ARE BUTTON STYLE) each side of deck including two mid-turns 6 L.E.D. Strip lights each side mounted between the deck mainbeams in the first 3 and last 3 deck sections wired to switch in rear bridge (see sketch)
Paint	Valspar standard Talbert black, R-Cure 800 series paint with zinc rich primer and clear coat
1 Lash rings	36 total - (See sketch) 10 each side of deck (bent style), 20 total 1 each side between deck main beams in the first four and in the last four deck sections (bent style), 16 total
Compatibility	Compatible with customers existing SN37025. NOTE: Customer to return all components to TMI for fitting and installation.
Design notes	60 Ton capacity in a 14'-0" two point rigid load base with 4 axle close coupled or 3+1
Additional general specifications	None

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.