

HALE

TRAILER

BRAKE & WHEEL



A026268
VIN: 44385

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer



800-232-6535 *FINANCING AVAILABLE

Model: T4-60CC/55SA-LD-HRG-(EC3/1)-T1

Capacity in tons: 60

1. GOOSENECK

Gooseneck design
Loaded 5th wheel height
Swing radius
Gooseneck extension
Alternate kingpin
Support cylinder
Power source
Gooseneck locks
Electrical receptacle
Additional gooseneck specifications

Ratchet
52"
108"
Connections for future 24" flip-up gooseneck extension to achieve 132" radius
Removable kingpin stations for 108" and 90" swing radius
Hydraulically operated with 4" x 3" cylinder mount cross member
Hydraulic couplings: 3/4" fixed at front of gooseneck
Ratchet
Seven pin connector
1) Aluminum diamond cover plate
2) Formed aluminum diamond plate light bar mounted in gooseneck base with 4 LED stop/tail/turn lights and 2 clear work lights wired to marker light circuit with on/off switch
3) Fully enclosed chain bar with aluminum diamond plate and lockable hinged lid (paddle latches)
4) Full penetration weld on gooseneck gusset
5) Base pivot tube reinforcement
6) Ratchet pivot shaft collar

2. DECK

Deck section design
Deck section length
Deck section width
Loaded road clearance
Loaded deck height
Flooring
Mainbeams
Gooseneck/deck connection
Deck/rear bridge connection
Outriggers
Reinforced top flange of sidemember
Additional deck specifications

Four beam
26'-0" (25'-6" clear)
8'-6"
6"
18"
2" apitong secured with deck screws; no lumber between main beams
12" T-1A
Horizontal pin and plate with remote lock
Fixed/welded
12" swinging/removable with double hook-on at front of deck
None
1) - Bucket well, recess last 4 deck cross members in deck between main beams and cover with 1/4" plate
2) - 3/4" side rail flanges
With plate and traction bars
32" with smooth plate and traction bars
Between main beams 1st deck section at front and last deck section at rear, in front of bucket well

Slope front of deck top down
Heavy duty front folding ramps
Expanded metal

3. REAR BRIDGE

Rear bridge section width
Loaded rear bridge height
Number of axles

8'-6"
43"
4

Axle capacity	25,000# - GAWR 23,000# Disc brakes for 22.5 tire size
Axle spacing	54"
Brakes	Disc brakes for 22.5 tire size air actuated with spring brakes on one axle
Anti-lock brake system	None required - GVWR is greater than 120,000#
Wheels	Ten (10) stud; 285.75mm B.C. aluminum disc hub piloted system with oil seals, inner aluminum wheels polished, outer aluminum wheels DURA BRITE
Tires	Sixteen (16) 275/70R22.5 (H) 16PR radials
Suspension	25,000# Capacity Ridewell air for disc brakes with oversized air bag 4th Axle (SN44385) flip-up and removable, use chrome tapered connecting pins. Include shims, pin tubes, and nuts/bolts.
Suspension options	<ol style="list-style-type: none"> 1) Over ride chains on all axles 2) Talbert style manual raising and lowering (+3", -3") 3) Air lift 3rd axle 4) Manual exhaust valve 5) Liquid filled air gauge mounted in 2nd & 4th axle curb side air bag with decal
Rear Bridge Center Section	Boom well, cross members recessed - recess 1st member additionally
Wide center bolster	With chain slots & flag holder slots
Rear half bolster	Rear of axle 3 and 4 with flag holder slots
Front bridge ramp	Sloped to deck outside of main beams with plate and traction bars
Rear bridge fenders	3/8" floor plate over tires only - First 3 axle only, 4th axle not covered
Additional rear bridge specifications	<ol style="list-style-type: none"> 1) Omit 1st cross member in rear bridge section (shock mount cross member) for open boom well 2) Connections for 4th axle and future 3+1 E1 Nitro
4. GENERAL	
Lights and wiring	<p>12 volt system with the following:</p> <p>All lights to be LED including mid-turn, excluding license plate light</p> <p>3 markers each side of deck including mid-turn</p> <p>Strobe lights with switch at rear of axle 3 and 4</p> <p>Battery back-up system with switch to flash all marker/tail lights and strobes</p>
Paint	Valspar standard black, R-Cure 800 series paint with ZINC RICH primer
Lash rings	<p>36 total -</p> <p>10 each side of deck (bent style), 20 total</p> <p>1 each side between deck mainbeams in the first two deck sections (bent style), 4 total</p> <p>1 each side mounted on side of deck bucket well plate in-line with the last two crossmembers (bent style), 4 total</p> <p>1 each bolster and half bolster end of trailer (straight style), 6 total</p> <p>2 at rear of 4th axle (bent style), 2 total</p>
Estimated empty weight	28,500#
Compatibility	None
Design notes	<p>55 ton capacity in a 10'-0" two point rigid load base with a 108" swing radius and 4 axles close coupled</p> <p>55 ton capacity in a 13'-0" two point rigid load base with a 132" swing radius and 3+1 E1 nitro axles extension</p> <p>60 ton capacity in a 13'-0" two point rigid load base with a 108" swing radius and 4 axles close coupled</p>
Additional general specifications	None
5. ADDITIONAL COMPONENTS	
Axle extension	Reinforced for future East Coast E1 Nitro style axle extension.

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.