



A026550 VIN: 45710

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894 Little Rock, AR: 833-424-8944 Baltimore, MD: 888-601-7500 Portland, ME: 800-325-4253 Concord, NC: 800-438-2250 Raleigh, NC 833-418-9777 Delmar, DE: 866-486-1400 Scranton, PA: 800-569-1400 Des Moines, IA: 888-673-5011 Springfield, MA: 800-854-5306 Elkton, MD: 800-544-7127 Voorhees, NJ: 866-315-0235 Jacksonville, FL: 800-828-3055 Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer **f © in @ & 800-232-6535** *FINANCING AVAILABLE

BASE MODEL: DF-22.5	Drop Deck - Steel Giant
cc pohents	description
	Standard Beam Pkg - 80,000 GVWR (60,000 in 10' Span)
OVERALL LENGTH	36'
TOP DECK-LGTH/HGT	10' Length = 59" Height
LOWER DECK-LGTH/HGT	26' Length = 75 Height 26' Length = Front 41", Center 42" Rear 40" Heights
OVERALL WIDTH	8' 6"
KING PIN SETTING	18" - Squared Front
UPPER COUPLER PLATE	1/4"
UPPER COUPLER HEIGHT	48"
BULKHEAD	None
MAIN FRAME	
	26" PreCamb Beam-130K Tru-Strength Flanges - Limited Lifetime Warranty 6" - 6.5# Per Foot
SIDE RAILS	2. 2.14 2.1.
TOP DECK FLOOR SILLS	4" Steel I-Beam - 18" O.C.
	4" Steel I-Beam 12" O.C. HD Pkg
COIL HAUL PACKAGE	None
FLOOR DECKING	1-1/8" Apitong
WINCHES	12
STRAPS	None
WINCH TRACK	Steel Slide Entire Length of Drivers Side
LANDING GEAR	Two Speed
SUSPENSIONS	Air Ride - Hendrickson Intraax - 23K - 2 Axles
SUSPENSION LOCATION	Set at Rear most Position - 32.5" Center of Rear Axle to Rear of Trailer
AXLES	(2) 23K Capacity - Type 30 Chambers - Auto Slacks - ABS - 22.5 Tires (1463#)
AXLE SPACING	49" (+35#)
Closed Tandem.	
LIFT AXLE	None
DUMP VALVE	Auto Dump Glad Hand Activated All Axles
SCALES	None
PARKING BRAKES	All Axles
ABS SYSTEM	Wabco ABS System 2S/1M
DUST SHEILDS	None
WHEELS	Disc - Hub Piloted - 22.5 - Steel (672#)
TIRES	255/70R 22.5 - Firestone
TIRE INFLATION SYSTEM	None
ANTI-SAIL MUD FLAPS	Behind Rear Axle
STAKE POCKETS	24" O.C. Sides & 4 Across Front, 5 Across Rear
PIPE SPOOLS	Double
RUB BAND STEEL	3/8" X 2-1/2" Recessed for DOT Tape
DOCK BUMPERS	Rubber Inboard
CARGO TIE DOWN	
A STATE OF THE STA	None NONE
TIRE CARRIERS	Tire Carrier Positioned In Front of Main Beams Between Landing Gear
TOOLBOX TYPE	None
TOOLBOX LOCATION	None
LIGHTS	Grote Ultra Blue Sealed Wiring Harness- 2 Micros Per Side & Mid Turn-3/3/3 Rear
CUSTOM LIGHTS	None
PAINT	Black - Sherwin Williams Epoxy Primer and Acrylic Polyurethane - Shot Blasted
DECAL PACKAGE	Standard Dorsey Logo Kit
	Fold Up Ladder Mounted Lower Deck At Neck
CUSTOM 1.	
**48" Aluminum Fold Up Ladder.	
- VI	