



Resale Inventory

A026577

VIN: 121776



SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894

Little Rock, AR: 833-424-8944

Baltimore, MD: 888-601-7500

Portland, ME: 800-325-4253

Concord, NC: 800-438-2250

Raleigh, NC: 833-418-9777

Delmar, DE: 866-486-1400

Scranton, PA: 800-569-1400

Des Moines, IA: 888-673-5011

Springfield, MA: 800-854-5306

Elkton, MD: 800-544-7127

Voorhees, NJ: 866-315-0235

Jacksonville, FL: 800-828-3055

Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer



800-232-6535 *FINANCING AVAILABLE

ITEM	DESCRIPTION
TYPE	CHIPS TRAILER
DIMENSIONS	Long box.
DIMENSIONS	
LENGTH	50'-10".
WIDTH	102 3/8" (2600 mm)
HEIGHT	13'-6" coupler height: 49"
DROP HEIGHT	12"(300 mm) in 47 1/4"(1200 mm) located at third wall panel.
SUB-STRUCTURE	
KING PIN LOCATION	36" from front. (900 mm)
KING PIN	Bolted Holland KP 0881.
COUPLER PLATE	5/16" thick, 100 000 psi steel, 19 000 kg capacity. Supported on the main beam with slope at front.
CROSSMEMBERS	1 beams, 4" @ 3.64 lbs/ft, 80 000 psi steel, 15 3/4" (400 mm) c/c, special croosmembers between axles and, ahead and behind suspension.
FLOOR	FIR soft wood, 1 5/8" thick shiplap finished, covered with one coat of linseed oil.
REAR THRESHOLD	Floor even with sill.
FENDERS	Made of aluminum 3/16" thick.
FRAME	Fabricated "I" beam structure, 100 000 psi steel, full length.
BOGIE	Stucture only. Do not cut the floor.(further application 4 axles)
FRONT WALL	Type: "G" (5" radius corners).
PANELS	Prepainted white aluminum 0.049 thick.
POSTS	Qty: 6, 4 of 45 mm, aluminum, and 1 each end, integrated to aluminum front corners.
FASTENERS	3/16" aluminum rivets, 4" c/c and 2" c/c on joints.
INTERIOR LINER	See insulation section.
FRONT CORNERS	Double sheating, 20 gauge stainless steel mirror finished on the outside and unpolished aluminum extrusions.
NET RACK	None.
LADDERS	
CAT WALK	Aluminum, 18 3/4" wide on front wall, ladder, made of aluminum, center included.
SIDE WALLS	Aluminum.
PANELS	Prepainted white aluminum (.049 thick).
POSTS	Aluminum, 45 mm, 16" c/c, full length.
FASTENERS	3/16" aluminum rivets, 4" c/c and 2" c/c on joints.
INTERIOR LINER	See insulation section.
INTERIOR LINER	Horizontal.
SAMPLE DOOR(S)	One, aluminum, 10" x 14", installed road side.
TOP RAILS	5 1/2" high, open top aluminum extrusions, unpolished.
BOTTOM RAILS	8 7/8" high, aluminum extrusions, unpainted.
VENTS	6 openings on each side wall with perforated aluminium plate.
REAR END	
DOOR FRAME	Galvanized steel (G164).
DOOR(S)	Single, dump style, aluminum smoothside.



ITEM	DESCRIPTION
HEADER DOOR PANELS DOOR LOCK(S) DOOR LOCK(S) HINGES DOOR FRAME BUMPER BUMPER	Steel formed 4" x 4" x 3/16". Smoothside panels aluminum 1 1/2" thick. On door sill. Manually operated by a road side handle. Extra handle holder on door frame. Full length. 1 1/2" x 1 1/2" solid steel push bars. CMVSS 223-RIG approved (in accordance with Canada & USA regulation). Formed steel uprights, 4" x 4" cross bar roll formed tubing at a maximum height of 22" from under tubing to ground.
ROOF BOWS TARP SUPPORT NET	Open type. Qty: 3, steel, without offset and hignes. 1/4" aluminum plate at each end of the unit for roll tarp type. None, (NO HOOK FOR NET).
INSULATION FRONT WALL FRONT INTERIOR LINER SIDE WALLS INTERIOR LINER INTERIOR LINER CARGO CONTROL	1 1/2" thick Polyform. Front corners, 1" thick Polyform. 1/2" plywood, laid horizontally and fixed with 1/4" steel pop rivets. 1 1/2" thick Polyform. 3/8" plywood. Fastened with self-drilling serrated tap screws. Backing plate (3") behind walls plywood joints.
ELECTRICAL FRONT CONNECTOR FRONT ADD. CONNECTOR ELECTRICAL SYSTEM MAIN SYSTEM FLASHERS BACK UP LIGHTS	7 ways (SAE J560), Phillips brand, located center. 7 ways (ISO 3731), for auxiliary fonctions only. Shock proof lights, polycarbonate lenses, in compliance with CMVSS 108. Grote Ultra Blue LED, Grote sealed beams, (tail lights with male pins #53252, markers #47122,233 (2 1/2"), licence light #60280-M). Sealed beams LED, (Grote #53963), one lamp including side marker and flasher, each side at middle point, amber. Sealed beam spot light (Grote #40-4411-00 in a closed back rubber grommet), Qty: 2
LANDING GEAR SAND SHOES CRANK SPAN	Holland, Mark V (LGH-1F012), heavy duty, square, self leveling feet. Road side. Fix on the full frame.
BASIC MECHANICAL FRAME	Fixed, see frame section sub structure.
MECHANICAL SUSPENSION STROKE STOPPERS SPRINGS AXLES	Hendrickson INTRAAX AAT-30K, tridem, 72" spread. For axles with bearings HM 518445. None. Air. 30 000 lbs. capacity.



ITEM	DESCRIPTION
SPIDERS CAM SHAFTS TRACK DUST SHIELDS BRAKES BEARINGS SLACK ADJUSTERS SEALS BRAKE CHAMBERS HUBS AND DRUMS	Welded. 10" long, 28 splines with enclosures. 77". Steel, clamped. 16 1/2" standard, 931-162 Abex lining. HM 518445. Meritor, automatic, 28 splines. Stemco, "Guardian" type, with "Gearlube" mineral oil, SAE 80W90. T.S.E. brake, "Omni brake" (30-30), (push rod 9 3/4"). KIC, 10 stud disc hubs, drums 114 lbs, outboard mount, 285.75mm B.C., single flange nuts. For dual steel wheels or single steel or aluminium wheels. 24.5 x 8.25, disc (10 holes), 285.75mm B.C., single flange nuts, 2 hand holes. Wheel guard 10 holes. Located between two wheels.
RIMS SPACERS TIRES TIRES	Goodyear, 11 R 24.5 G-287 16 ply (43.7")
AIR SYSTEM GLAD HANDS AIR VALVES VALVE DIAGNOSTIC CABLE PRESSURE GAUGE	Fixed. Rockwell Wabco, ABS, 2 sensors 1 modulator. Manual blow down valve in a control box, WITHOUT auto-reset feature, including Glycerin filled pressure gauge, in P.S.I., to indicate load with a conversion table. Not included with ABS valve. Air gage, SILICONE filled, in P.S.I., to indicate load with a conversion table. (for pneumatic suspensions only). (-40 @ 65 degree celcius) (Liquid filled gage 4" diameter). P605-4BF-SF45 Located: roadside rear, 3 ft up from bottom rail.
ACCESSORIES TIRE CARRIER REGISTRATION HOLDER MUD FLAPS EXTRA MUD FLAPS	Qty: 1, heavy duty tubing, located behind landing gear, mouth road side. One plastic, Betts-PS-1 or equivalent. One set, rubber with Manac logo and vertical grooves to reduce spray. Qty: 2 set(s), rubber with Manac logo and vertical grooves to reduce spray. Located at rear of each axles.
FINISHING PAINT UNDERCARRIAGE HUBS WHEELS OR RIMS RETROREFLECTIVE TAPES	Roof bows cleaned with abrasive and covered with two coats of epoxy primer and two top coats of polyurethane paint, color: gray, Code: Sico T 11445. One coat black latex primer. Black. White. Conspicuity striping in compliance with CMVSS 108. Gray and red, 2' segments at bottom of each side wall. Fully covers bottom of rear doors and horizontal underride protection bar. 2 segments of gray tape at each upper corner.



ITEM	DESCRIPTION
ADDITIONAL OPTIONS	
MISCELLANEOUS	Pre delivery inspection.
SUB-CONTRACT BY AN OUTSID	Price ajustement

ANNEX(ES) ATTACHED	
R	ref: 118305.

DISCLAIMER
Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.