

HALE

TRAILER

BRAKE & WHEEL



A026619-A5878
A026620-A5879

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

Workhorse 55LCC Air Tridem (Flat Level Deck) (Model: WORKHORSE 55LCC)

WKH55LCC*F*826543

Est. Wt.: 23,415# +/- 3%

TRAILER - GENERAL

Capacity: 55 tons in 13-foot length with 4 axles close coupled; - GAWR and GVWR determine legal payloads
Load Base: 13-foot rigid 2-point load centered in deck area with 4 axles close coupled
Length (Trailer Only): 52 feet 10 inches (with standard deck length and axle spread)
Compatibility: Designed to accept 55/60 rear axle below
Accent Package: None

GOOSENECK

Design: Narrow hydraulic removable non-ground bearing - swing radius of 108 inches (12ft 7in overall gooseneck length) set up for wetline operation
Loaded Fifth Wheel Height: Dual Cam Pawl Arm Assembly with 7 ride height positions (50 inches nominal)
Kingpin: Removable kingpin at 89 and 108 inch radius
Power Source: Set up for wet line operation
Tool Box: None
VIN Plate: Bilingual VIN plate
Registration/Document Holder: Registration/document holder installed
Hydraulic Fittings: OEM Standard 1/2 inch

DECK

Framework: All main longitudinal members fabricated with 100,000# minimum yield steel flanges with 50,000# webs
Deck Length: Flat Level Deck (FLD) design - standard 26 feet clear deck length- OAL 52 feet 10 inches
Deck Width: 8 feet 6 inches overall (unless optional deck width is selected)
Loaded Deck Height: 18 inches with 6 inches ground clearance
Crossmembers: On 24 inch centers (nominal)
Chain Slots: Chain Slots located on siderail
Flooring: 2 inch nominal wood - side rails only
Front Ramps: Fixed Toe Ramp instead of standard flip ramp PN 80600902
Extension Brackets: 13 pair - 26 total removable swing type, 2 pair - 4 total heavy duty removable hook-on type (26 swing type, 4 hook-on type on 27 foot deck)
Tool Box: 2 Fully covered trays in front of deck between mainbeams with lockable covers
Hammer Plate: Hammer Plate installed over recessed crossmembers. Preforated plate under hammer plate forming two storage areas. 2 pair lashing ring located in last two deck sections.

REAR BRIDGE

Front Bogie Ramp: Included as standard
Boom Trough: Low Boom Well V crossmembers with bolt-in V pan
Deck to Bogie Connection: Fixed
Bolsters: Recessed
Covered Rear Bogie: Bolt-on load bearing wheel covers (Individual pieces per axle- 6 pieces)
Rear Bogie Height: 40 7/8 inches to top flange - 36 5/8 inches to top of bolsters

Connections for Future Axle Attachment: Air and electrical connections to go along with connecting ears	
Bumper: Heavy duty V-style rear bumper	
AXLES	
Number of Axles: 3 axles	
Axle Capacity: 25,000 lb. nominal capacity per axle NOTE: GAWR determined by suspension type, brakes, tires and other components.	
Axle Spread: 54.5 inches (between axles)	
Brakes: 16.5 inches x 7 inches with 5.5 inches autoslacks - heavy duty brake drums - outboard mount	
Spring Brakes: None	
Dust Shields: None	
SUSPENSION	
Suspension: Air ride	
ABS: None required	
First Axle Chain Lift: Chain lift axle	
Third Axle Lift: Air lift	
Mechanical Ride Height Control: 7-position mechanical ride height control system	
Manual Dump Valve: Manual Dump Valve (Push Pull)	
Liquid Filled Gauge: None	
Load Scale: None Standard	
WHEELS AND TIRES	
Wheels: 8.25 x 22.5 LVL One buffed outside/steel inside - hub-piloted	
Tires: 275/70R 22.5 OEM standard	
Hubodometer: None Standard	
Tire Inflation: None Standard	
LIGHTING	
Electrical System: DOT sealed beam and harness with LED lights and 4 inch flush mounted battery powered amber strobes	
Tail Lights: 3 tail light package	
Electrical Receptacle: J560 7-pin connector	
Marker Lights: 3 marker lights per side including mid turn	
Additional Marker Lights: Additional Marker Lights Installed	
PAINT	
Paint: Premium polyurethane enamel matched to Fontaine paint brand Viper Red PN 51130170/KPR0120	
MISCELLANEOUS	
Lashing Rings: 19 pair - 38 total (with standard deck option)	
Flag Holders: Flag holders - 1 pair located at front of deck and on rear bumper	
AVAILABLE COMPONENTS	
Compatibility: Designed to accept 55/60 rear axle below	
Flip Axle: None standard	
Hydraulic Flip Axle Option: None Standard	
Dust Shields on Flip Axle: None standard	
MISCELLANEOUS	
(1) additional pair lash rings located in 4th deck section from the front	
(2) additional punch plate bottoms located in the 3rd and 4th deck sections from the front	
Zinc rich primer	

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.