

SERIAL NO. \_\_\_\_\_ MODEL NO. \_\_\_\_\_ WEIGHT

5MAMN4524AC017204 TNAR45MF104-2010 18027 lb. +/- 3%, 119 yds.

## **MOVING FLOOR TRAILER SS**

BODY		
LOAD PROFILE	DEMOLITION, 80 GVWR	
LENGTH	45 ft.	
WIDTH	102 in.	
WALL HEIGHT	104 in.	
PANEL TYPE	(52) 2-1/4 X 10 VERTICAL PANELS - (BUFFED)	
TAPERED SIDE	NONE	
TOP RAIL OPTION	2-1/4" VERTICAL PANEL TOP RAIL	
FLOOR	2297 (1841) , IMPACT	Reinforced plates where floor bolts to drive unit
DRIVE UNIT	KEITH, 3-1/2 in. CYLINDER (HEAVY DUTY)	
BOTTOM RAIL	2-1/4" x 10" BOTTOM RAIL (NO CLEANOUT)	
CROSSMEMBER SPACING	5-1/4 in. I-BEAMS, 12 O.C.	
I-BEAM WIDTH	Z-BEAM, 48in. WIDTH	
REAR POCKET HEIGHT	115 1/8 in.	
TARP BAR	NONE	
LOWER BULKHEAD WRAP	YES	
BULKHEAD TYPE & OPTIONS	1/4"	
BULKHEAD HEIGHT	109 3/4 in.	
BULKHEAD STEPS / CATWALK	CATWALK & LADDER W/STEPS INSIDE	
GATE STEPS	(STD.) UP CENTER OF GATE OUTSIDE ONLY	
TARP HOOKS	BULKHEAD AND GATE	
TARP BASKET	NO	
FENDERS/FRONT FLAPS	NONE	
FLAPS, REAR AXLE	FULL ACROSS	
FLAPS, FRONT AXLE(S)	NONE	
COMPACTOR COMPATIBLE	NO	
	NONE	
UPPER CROSS TUBES / CAPS	(1) SPRING-MID & (1) TUBE-REAR	
IGHTS	000 000 000	
LIGHT TYPE	GROTE L.E.D. W/ GROMMET	Grote LED sealed harness system
	3 LARGE-3 SMALL-3 LARGE (IN TAILGATE)	
	NONE	
MARKER LIGHTS	3 EACH SIDE	
MIDTURNS	1 PAIR (NON-COMBO)	
BACK-UP LIGHTS	NONE	
REAR FACING LIGHTS	NONE	
SWITCH ENCLOSURE	NONE	
	NONE	
AUXILARY CABLE (4 OR 7 WAY)	NONE	
TARP MANUFACTURER	SEE NOTES	Prep for dealer arranged Aero Lid system, hinged on curbside wal
TARP MANUFACTURER	SEE NOTES SEE NOTES	Hydraulic operation off the truck
	NONE	
BOW HOLDERS	NONE	
BOWS	NONE	
PAINT		
CHASSIS COLOR	BLACK	
PIN STRIPING	BLACK	
"MAC" LOGOS	MAC BLACK	
OPTIONAL SIGNS	NONE	
ATE		
GATE HEIGHT	105 1/2 in.	
GATE WIDTH	99 1/2 in.	
GATE PANEL TYPE	STANDARD SMOOTH	Smooth panel design
	SEE NOTES	Single Barn Door tailgate hinged roadside
GATE OPERATION	MECHANICAL SIDE LATCH	
SAFETY CHAIN	YES	
PUSHER BLOCK	NONE	

WINDERS / SAFETY LATCH	(STD.) (1) WINDER ON SIDE ONLY	
ASSIS		
MODEL	TANDEM	
SUB FRAME RAILS	TANDEM, 10in. X 22# I-BEAM	
SUB FRAME WIDTH	47 1/4 in.	
PIN SETTING	36 in.	3/8" steel king pin plate
5th WHEEL PLATE	I-BEAM STYLE (LOW PROFILE) @ 49 in. HIGH	
PIN TO AXLE SETTING	465, 32 REAR SETTING	Set suspension forward 12 inches (44 in. setting)
SUSPENSION	HEND. INTRAAX AA-300 TP WHLS	······································
SPRINGS	AIR	
AXLE SPACING	52 in.	
SUSPENSION CONTROL	BALL VALVE (STD.)	
AXLES	( 2) AXLE FOR INTRAAX ONLY	
ABS	(1) 4S2M MERITOR / WABCO	
BRAKE SHOES	7" XL, W/30-30 CHAMBERS	
SLACKS	HALDEX	
CAM GUARDS (ALL AXLES)	STANDARD	
TIRES	(8) GENERAL S360 11R 24.5 16 PLY	
TIRE INFLATION SYSTEM	NONE	
RIM TYPE (PER AXLE)	STEEL HP 24.5X8.25 10 HOLE WHITE	
HUB AND DRUM	(4) CAST W/STEEL HUB HP 10 STUD TP, SS, 7"	
SYNTHETIC GREASE ILO OIL	NO	
HUBODOMETER	NONE	
DUST COVERS	NO	
TIRE CARRIER	(1) IN MIDDLE ONLY	
DOLLIES	(STD.) JOST - 5 YEAR NO LUBE - D.S. (REVERSE MOUNT)	
AIR GAUGE/SYSTEM	NONE	
TOW HOOKS	(2) TWO IN POCKET	
HYD. HOSE FITTING	1" X 108" HOSE W/WING FITTING	
BUMPER	D.O.T. BUMPER	
TAXLE		
ТҮРЕ	NONE	
NO. OF LIFT AXLES	0	
LIFT KIT	(0) NONE	
AXLE	(0) NONE	
TIRES	( 0) NONE	
RIM TYPE (PER AXLE)	( 0) NONE	
HUB AND DRUM	(0) NONE	
BRAKE SHOES	NONE	
CONTROLS	NONE	
DISTANCE	NONE	

DISCLAIMER Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.