



A026727 VIN: A5466

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: Little Rock, AR: 833-424-8944 800-383-8894 Baltimore, MD: 888-601-7500 Portland, ME: 800-325-4253 Concord, NC: 800-438-2250 833-418-9777 Raleigh, NC Delmar, DE: 866-486-1400 Scranton, PA: 800-569-1400 Springfield, MA: Des Moines, IA: 888-673-5011 800-854-5306 Elkton, MD: 800-544-7127 Voorhees, NJ: 866-315-0235 Jacksonville, FL: 800-828-3055 Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer f 👽 庙 🎯 🛗

800-232-6535 *FINANCING AVAILABLE

| Intermediate Axle 60-90 (Model: MAG IA 6090 60) | |
|---|-------------------------|
| | |
| | Est. Wt.: 3,780# +/- 3% |
| TRAILER - GENERAL | |
| Compatibility: Magnitude 60HD, 65, 75 and 80 ton | |
| Length: 5 feet 1 inches | |
| Width: 8 feet 6 inches | |
| AXLES | |
| Number of Axles: 1 axle | |
| Axle Capacity: 25,000 lb. nominal capacity per axle NOTE: GAWR determined by suspension type, brakes, tires and other components. | |
| Axle Spread: 60 inches (between axles) | |
| Brakes: 16.5 inches x 7 inches with 5.5 inches autoslacks - heavy duty brake drums - outboard mount | |
| Dust Shields on Flip Axle: None | |
| SUSPENSION | |
| Suspension: Air ride | |
| WHEELS AND TIRES | |
| Wheels: 8.25 x 22.5 Outer LvL One buffed/steel disc inside - hub-piloted | |
| Tires: 275/70R 22.5 OEM Standard | |
| Hubodometer: None Standard | |
| Tire Inflation: None Standard | |
| REAR BRIDGE | |
| Boom Trough: V-style boom trough with bolt-in V pan | |
| Manual Dump Valve: Manual Dump Valve (Push Pull) | |
| Bumper: Heavy duty V-style rear bumper | |
| LIGHTING | |
| Electrical System: DOT sealed beam and harness with LED lights and 4 inch flush mounted amber strobes | |
| PAINT | |
| Paint: Fontaine black polyurethane enamel PN 51172000/G02BC0001 | |
| MISCELLANEOUS | |
| Lash Rings: 1 pair - 2 total | |
| Flag Holders: Flag holders - 1 pair located on rear bumper | |
| VIN Plate: Bilingual VIN plate | |
| | |