


HALE

TRAILER

BRAKE & WHEEL



A026920
TEMP VIN: S025886

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer

800-232-6535 *FINANCING AVAILABLE

BOTTOM DUMP - SHORT FORM

STANDARD SPECIFICATIONS: TRAVIS ALUMINUM BOTTOM DUMP

ALL ALUMINUM CONSTRUCTION

Extruded tubular longitudinal lower rails
Extruded top rail
Extruded horizontal rail
Extruded I-beam sub-frame
Extruded aluminum drop legs (mounted on gates)
.160" thick aluminum hopper sides and inner slope plates
.250" thick aluminum chute ends and sides
.250" thick aluminum gate inner sheet
.125" thick aluminum outer shed plates

Smooth aluminum front & rear fenders

12 degree side wall slope
99" outside body width / 91" inside at top rail

GATE

.250" thick 5454 H34 aluminum chute
106" X 50" opening, 14" ground clearance
Infinitely adjustable electronic control valve with dryer & oiler (jogging valve)
(2) 8" diameter, 26" stroke, composite lightweight air cylinders with positive stops

Aluminum air reservoirs

CHASSIS / UNDERBODY RELATED

Rocking upper coupler, 2" diameter Steel pin, 8 degree oscillation
5/16" T-1 steel coupler plate
Hutchens CH9700 single leaf, 4-spring suspension, bolt-on
5" round axles (2), 5/8" wall, common inner/outer bearings
Automatic slack adjusters
16-1/2" X 7" air actuated brakes

Wabco ABS - 4S/2M

Cast steel hubs - hub piloted
Outboard drums
Radial tires (choice of size)
Steel disc wheels, white, hub-piloted

OTHER STANDARD FEATURES

Ladder on front shedder plate with safety rail and steps
HMW plastic, 1/2" thick, windrow deflector
D.O.T. conspicuity tape (3M)
Silver enamel paint on steel parts
Anti-spray, anti-sail rear mud flaps
Truck Lite sealed light system
Removable drop legs

All Travis trailers conform to Federal Motor Vehicle safety standards in effect at time of production. Because of continuous improvements, the above specifications are subject to change without notice.

MODEL	LENGTH	KP to REAR AXLE	BASE WEIGHT	CUBIC YARDS CAPACITY	
39/23 AERO ALBD				23.00	
CHANGES FROM STANDARD: For TYPE of change: D = Delete Standard Specification, A = Alter Standard Specification, O = Add Optional Equipment					
No.	TYPE	DESCRIPTION	WEIGHT +/-	YDS +/-	
		HT-300 Air Ride Suspension in lieu of Spring			
		SHURCO Elec Flip Tarp, Mesh Material			
		Centrifuge Drums and Duralite Hubs			
		Full Flaps across the rear			
		Push Bumper			
		Safety Pin Bars in lieu of Chains			
		(8) 22.5 x 8.25 Aluminum wheels, all polished			
		(8) 11R22.5, 14ply Falken Radial Tires			
		Electric Control Box to mount inside the cab of the truck to operate the gates and the suspension, with the same controls on the D/S of the trailer ahead of the Left Front Axle.			

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.