

VIN: 90614

RENTALS PARTS SERVICE SALES Allentown, PA: 800-383-8894 Little Rock, AR: 833-424-8944 Baltimore, MD: 888-601-7500 Portland, ME: 800-325-4253 Concord, NC: 833-418-9777 800-438-2250 Raleigh, NC Delmar, DE: 866-486-1400 Scranton, PA: 800-569-1400

Elkton, MD: 800-544-7127 Voorhees, NJ: Jacksonville, FL: 800-828-3055

888-673-5011

866-315-0235 Walpole, MA: 800-854-5310

Springfield, MA:

800-854-5306

haletrailer.com | @haletrailer **f** (in) 800-232-6535 \*FINANCING AVAILABLE

BODY: "GENESIS"		TAILGATE:		CHASSIS:	
WIDTH (INCHES)	102	HEIGHT	FULL	MODEL	TRIAXLE-1&3LIFT(10)
LENGTH (FEET)	48	TYPE	SINGLE	TYPE	ALUM SUB FRAME
HEIGHT (INCHES)	104	STYLE	GENESIS	AXLE TO AXLE	60" - 60"
SIDE MAT'L (OUTBOARD)	) "GENESIS"	MAT'L THICKNESS	0.150	REAR AXLE SETTING	54"
FRONT 0.150		S / S HINGE ON	PASS. SIDE 4-3-4	5TH WHEEL HT	50"
MIDDLE 0.150		GATESEAL	YES	PIN SETTING	36" W/ 3/8" KP PLATE
RE	AR 0.150	GATE LADDER	CENTER-LADDER	SUSPENSION	AAT30K (4)(8)
POLISHED SIDES	YES+TG+REAR PKT	TARP HOOKS	NONE	SPRINGS	AIR (11)(12)(13)
ROOF	NONE	WINDERS	ONE-D/S	AXLES	TP - HXL-5
ROOF MAT'L	NONE	GATE GUIDE	YES	BRAKES	HEND MAXX 22T
BULKHEAD	3/16" BUFFED(1)(3)	GATE CONTROL	MECH - BOLT CLAW	DUSTSHIELDS	YES
TARP HOOKS	NONE	POCKETS	EXTRUDED	BRAKE CHAMBERS	TOP OF AXLE
TARP BASKET	NONE	CROSSPIPE (S)	TWO - (7)	ABS	2S / 1M
TARP	NONE		MIDDLE-SPRING	HUBS	10LW STEEL/GREASE
CATWALK	YES-74" INTRMDTE		REAR-TUBE	DRUMS	N/A
B.H. LADDER	DER D/S-LADDER COMPACTO		ACTOR:	WHEELS	8.25" X 24.5"
CROSSMEMBER	"I"BEAM- 12" C/L	SIDE LATCH	N/A		6 STEEL/ 6 HP (15)
FLOOR MAKE	KEITH-3.5" DRIVE	CENTER LATCH		TIRES	11R 24.5 R268
FLOOR MAT'L	2299 (17)	PIN DIA.			ECOPIA 16PLY(16)
WEARPADS	CWS			DOLLIES	HX 151
TAPE COLOR	BLACK IN TOP RAIL	HYDRAULICS:		LOCATION	D/S CRANK (2)
LIGHT PANEL	NOTE (20)	HOSES	TWO-4000 PSI	BUMPER	EAST UNDERRIDE
MARKER LIGHTS	LED (6)	LENGTH	144"	TOW HOOK(S)	TWO
MIDMOUNT SIGNALS	MODEL 60	FITTINGS	WINGNUT	PUSH BLOCKS	YES
MUDFLAPS	STD	HP	1" FEMALE	PAINT	EAST BLACK
HOSE HANGER	YES-0N BULKHEAD	LP	1" MALE (5)(9)(14)		
TIRE CARRIER	NONE	HOSE LOCATION	P/S-REF 72189		REMARKS
		AIR & ELECTRICAL	CENTER-REF 72189		.(18)(19)(20)(21)(22)

Des Moines, IA:

## **REMARKS:**

- 1.NO INSIDE BULKHEAD STEPS.
- 2.ADD TRUCKLITE REGISTRATION HOLDER TO D/S LANDING GEAR BRACKET
- 3. MANDOOR IN CENTER OF BULKHEAD -USE CAST STEP BELOW MANDOOR
- 4. T-BLOCKS @ REAR. DRIVE UNIT FLOOR OPENING MOVED FORWARD FOR TRIDEM. MAKE SURE DRIVE UNIT OPENING MISSES ALL AXLES NOTE 54" REAR AXLE SETTING
- 5. JUNCTION BOX WIRED TO AUXILIARY PLUG FOR ALL FUNCTIONS LOCATED @ INSIDE FRAME RAIL D/S OPPOSITE THE CONTROL BOX

## 6. 5 PR BOTTOM - NO PROTECTORS -

- 7. REAR CROSSPIPE MOVE FORWARD 1' FROM STANDARD PLACEMENT.
- 8. AAT30K FOR AXLE 2 w/ AAL30K/R1 LIFT AXLES FOR AXLES 1&3(INDEPENDENTLY)(LIFT AXLES TO HAVE SWITCH IN BOX AND ELEC CC OPERATIONS)
- 9. ALL CONTROLS TO BE IN BOX (AMP1086LF)IN FRONT OF FIRST AXLE, AND WIRED FOR CAB CONTROL THRU AUX 7-WAY ISO PLUG -OLD STYLE
- 10. GALVANIZED SUSPENSION HANGERS.
- 11. RIGHT WEIGH OIL FILLED GAUGE IN LBS. FLUSH MOUNTED IN BULKHEAD ON D/S RADIUS FOR DRIVER VISIBILITY-REF 72189
- 12. ALL 3 AXLES TO EQUALIZE FROM REAR TO FRONT AAL30K/E-3-1AAT30K/E-2
- 13. LIFT AXLES TO BE FRAME SWITCH & ELEC CC AND BRAKE RELEASE WIRED TO AUXILIARY PLUG.
- 14. CONTROL BOX TO BE LIKE ATTACHED PIC.- REF BELOW.
- 15. STEEL INSIDE / ALUM OUTSIDE. USE WHEEL GUARD INSULATOR BETWEEN STEEL AND ALUMINUM WHEELS.
- 16. HENDRICKSON TIRE MAXX PRO ALL AXLES.
- 17. KEITH SPLASH GUARD HOLD DOWN BEARINGS
- 18. BACK UP WORK LIGHTS (BOXED IN)(WIRED TO AUXILIARY PLUG) -REARWARD OF LANDING GEAR & SWITCH IN BOX-REF PIC BELOW REF 81019
- 19. AUXILIARY ISO 7 WAY PLUG
- 20. ADD LED BACK UP LIGHTS OOX 000 XOO-WIRED TO SAME AUX WIRE THAT THE BOXED IN BACK UP LIGHTS ARE WIRED TO. X=B/U LIGHTS
- 21. CENTER MUDFLAP AHEAD OF AXLE #1 4" FORWARD OF NORMAL PLACEMENT
- 22. AERO SMOOTH ALUM TOOLBOX 24" X 24" X 36" 1/8" CAM LOCK STYLE ON D/S
- 23. INSTALL PHILLIPS TRACKER SPRING KIT (PART # 17-1488) TO HYDRAULIC HOSES AND CATWALK-REF PIC

**CHANGE 1** 

CUBIC YARDS

125

**OVERALL HEIGHT (FT)** 

13.25

EMPTY WEIGHT (#) 20,751 (EMPTY WEIGHT VARIANCE +/- 3%)



