

HALE

TRAILER

BRAKE & WHEEL



A027082
VIN: 46129

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer

800-232-6535 *FINANCING AVAILABLE

Base Model #: DDF50 x 102 Air Fixed 22.5 Side Ramp

Serial #: 46129

components description

CAPACITY Standard Beam Pkg - 80,000 GVWR (60,000 in 10' Span)

OVERALL LENGTH 50'

UPPER DECK LENGTH 12'

LOWER DECK LENGTH 5'6" Clear Double Drop Section & 32' Standard Lower Deck

OVERALL WIDTH 8' 6"

KING PIN SETTING 42" - Squared Front

UPPER COUPLER PLATE 1/4"

UPPER COUPLER HEIGHT 48"

BULKHEAD Removable Steel - 72" - No Side Return - 4 Posts DOT

MAIN FRAME 26" Fab.-PreCamb.I-Beams-(80K Pkg)

SIDE RAILS 6" - 6.5# Per Foot

TOP DECK FLOOR SILLS 4" Steel I-Beam - 18" O.C.

LOWER DECK FLOOR SILLS 4" Steel I-Beam 12" O.C. HD Pkg

COIL HAUL PACKAGE None

FLOOR DECKING 1-1/8" Apitong

WINCHES 12 Ratcheting Winches

Ancra 49207-127-RW.

STRAPS None

WINCH TRACK Steel Slide Entire Length of Drivers Side

LANDING GEAR Two Speed

SUSPENSIONS Air Ride - Hendrickson 23K - 2 Axle

SUSPENSION LOCATION Set at Rear most Position

AXLES (2) 23K Capacity - Type 30 Chambers - Auto Slacks - ABS - 22.5 Tires AXLE

SPACING 49" (+35#)

LIFT AXLE None

DUMP VALVE None

SCALES None

PARKING BRAKES All Axles

ABS SYSTEM ABS System 2S/1M

DUST SHEILDS None

WHEELS Disc - Hub Piloted - 22.5 - Steel (672#)

TIRES 255/70R 22.5 - Firestone

TIRE INFLATION SYSTEM Hendrickson Pro

ANTI-SAIL MUD FLAPS Behind Rear Axle

STAKE POCKETS 24" O.C. Sides & 4 Across Front, 5 Across Rear

PIPE SPOOLS Double

RUB BAND STEEL 3/8" X 2-1/2" Recessed for DOT Tape

CARGO TIE DOWN None

CONTAINER TWIST LOCKS NONE

TIRE CARRIERS None

TOOLBOX MATERIAL Steel- Smooth Box & Smooth Door(s)

TOOLBOX TYPE 18x18x36 Alum Box Barn Style

TOOLBOX LOCATION Passenger Side- In Front Of First Axle

LIGHTS Sealed Wiring Harness w/ LED Pkg

CUSTOM LIGHTS None

PAINT Red

CUSTOM 1. Special Ramp (See Note)

See Pictures and Reference Serial Number.

**Steel Grading Flooring Smooth Surface/Mill Finish (22w4) 2-1/2" x 1/4" **

(2) 24" Runs of Grating On Ramp, Set For Customer Forklift Wheel Base.

Mechanically lock in place in vertical position.

Ramp angle not to exceed 13 degrees in lowered position.

Ramp installed on curbside.

Removable For Stacking Units.

CUSTOM 2. Electric Winch

Electric 2 Ton Winch With Battery Backup.

Single Pole Plug At Front To Recharge Battery.

CUSTOM 3. None

Reference # 33733

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.

Equipment availability, prices and specifications are subject to change without notice.