

HALE

TRAILER

BRAKE & WHEEL



A027255
VIN: 941014

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

Description

NEW ACE ROLL OFF TRAILER - ART-60-40

Overall Length: 40' 11"
Container Frame Length: 40'
Kingpin to Last Axle: 34'
Rated 60,000 lbs. Lift Capacity
Container Size Range- 10'-40' Outside Rail Containers

MAIN FRAME:

12"X 4"X 1/4" Rectangular Tubing
12"X 4" Cross Members for Main Frame
Top Wrap: 1/2" X 4" Flat Bar Wear Pad
Bottom Wrap: 3/4" x 4" Flat Bar
1/4" Hollow Truss Mounted Below Main Frame with 1/2"
X4" Bottom Wrap
(2) 1 1/4" Fixed Stops at Front of Trailer
(14) 3 1/2" Rollers Welded to Outside Frame
3/4" King Pin Plate with 3/4" Plate Supports & 2" Round Bar
Stiffener

STABILIZER FRAME:

4"X4"X 1/4" Tube with 4"X4"X3/8" Angle Wrap
Hinges: 2" Round Bar
28"X16"X5/8" Draft Arm Support Plates

HYDRAULICS:

(2) 8.5"- 4 Stage Telescopic Main Lift Cylinder 133,000
lbs. @ 2,400 PSI
(2) Ace Independent Reeves: 3 1/2 Rod 7" Bore Reeving
Cylinder 88,000 lbs. ea.
Directional Valve with Pressure Gauges and Adjustable
PSI - Set to 2,450 PSI
Hoses: 3/4" 3000 PSI Hoses with Nylon Covering
Hydraulic Pipes: 3/4" Steel Pipe
Standard JIC Fitting on All Hydraulics
NO HYDRAULICS IN REAR OF TRAILER

CABLE AND AFFILIATED COMPONENTS:

Cable-7/8" IWRC Cable, (4) Cable Clamps, Cable Button
with Cast Ring
Pulleys: 10" Sheave with 2.5" Pin (Qty 3)
Pulley Block - Independent (2)
Independent Pulley Track

Description

RUNNING GEAR:

H900 50,000 lbs. Spring Single Point Suspension
(Tandem)
Suspension Hanger: 21" Fabricated I-Beam
(2) 25,000 lbs. 5" Round Axles
Brake Control: Spring Loaded 16" x7.5"
ABS: 2S1M
10 Hole Uni-Mount Hubs & Drums
10 Hole Uni-Mount Rims w/11R22.5 Tires
Fenders- Rubber 2-Ply
Ace Logo Rubber Mud Flap with Hook
2-Speed Landing Gear 120K lbs.

LIGHTING & SAFETY

All L.E.D Lights
All Lights Meet DOT #108
Lights & Harness- Truck Lite
Body Hoist Up Alarm- LED Strobe
ICC REGULATED BUMPER- AIR ACTUATED
Meets FMCSA 49 CFR § 393.86
(4) Nylon Tie Down Strap – More can be added*

PAINT

Cleaned, Primed, Painted Industrial Epoxy (Black)
WARRANTY- In Years
(5) On Main Frame – Excluded Rollers and Greaseable
Items
(1) All Hydraulic Components
(1) on All Items Manufactured by Ace
Axles & Suspension are subject to manufacturer
discretion
Main Frame Assy, Standard Tandem
Finishing Stages, 40FT Tandem
Removable Stop Set Driver & Passenger
Winch, Standard, Weld-on
Tarp System, Roll-Off Complete 40' Hyd
Front Work Lights - Installed
Automatic Tire Inflation Kit

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.