

# HALE

## TRAILER

### BRAKE & WHEEL



A027309  
VIN: A6089

#### SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer



**800-232-6535** \*FINANCING AVAILABLE

Rear Axle 60-90 Only available in 60" spread (Model: MAG FA 6090 60)	
AXM609060RS	Est. Wt.: 3,270# +/- 3%
TRAILER - GENERAL	
<b>Compatibility:</b> Magnitude 60HD, 65, 75 and 80 ton	
<b>Width:</b> 8 feet 6 inches	
AXLES	
<b>Number of Axles:</b> 1 axle	
<b>Axle Capacity:</b> 25,000 lb. nominal capacity per axle NOTE: GAWR determined by suspension type, brakes, tires and other components.	
<b>Axle Spread:</b> 60 inches (between axles)	
<b>Brakes:</b> 16.5 inches x 7 inches with 5.5 inches autoslacks - heavy duty brake drums - outboard mount	
<b>Dust Shields on Flip Axle:</b> None	
SUSPENSION	
<b>Suspension:</b> Air ride	
WHEELS AND TIRES	
<b>Wheels:</b> 8.25 x 22.5 Outer Lvl One buffed/steel disc inside - hub-piloted	
<b>Tires:</b> 275/70R 22.5 OEM Standard	
REAR BRIDGE	
<b>Boom Trough:</b> V-style boom trough with bolt-in V pan	
<b>Manual Dump Valve:</b> Manual Dump Valve (Push Pull)	
<b>Bumper:</b> Heavy duty V-style rear bumper	
<b>Accent Package:</b> None	
LIGHTING	
<b>Electrical System:</b> DOT sealed beam and harness with LED lights and 4 inch flush mounted amber strobes	
PAINT	
<b>Paint:</b> Fontaine black polyurethane enamel PN 51172000/G02BC0001	
MISCELLANEOUS	
<b>Lash Rings:</b> 1 pair - 2 total	
<b>Flag Holders:</b> Flag holders - 1 pair located on rear bumper	

#### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.