

HALE

TRAILER

BRAKE & WHEEL



A027369 & A027370
VIN: A6012 & A6013

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer

800-232-6535 *FINANCING AVAILABLE

Magnitude 55H MBMD - Modular Tridem (Beam Deck) (Model: MAGNITUDE 55H MBMD)	
MAG55H***MB*29603/AXM516060RS	Est. Wt.: 25,282# +/- 3%
TRAILER - GENERAL	
Capacity: 55 tons in 12-foot length with 4 axle close coupled or single axle stinger - GAWR and GVWR determine legal payloads	
Load Base: 12-foot rigid 2-point load centered in deck area with 4 axles close coupled	
Length (Trailer Only): 52 feet 0 inches (with standard deck length and axle spread)	
Compatibility: Designed to accept optional 51/60 rear axle, spreader, and/or 35 inch flip box	
Accent Package: None	
GOOSENECK	
Gooseneck Design: Narrow hydraulic removable non-ground bearing - swing radius of 102 inches (11ft 11in overall gooseneck length) set up for wetline operation	
Loaded Fifth Wheel Height: Dual Cam Pawl Arm Assembly with 7 ride height positions (50 inches nominal)	
Swing Radius: 102 inches (11 feet 11 inches overall gooseneck length) - NGB	
Alternate Kingpin: Dual kingpin at 81 inch and 102 inch radius	
Power Source: 13 HP (min.) Gasoline powered auxiliary power unit	
VIN Plate: Bilingual VIN plate	
Registration/Document Holder: Registration/document holder installed	
Hydraulic Fittings: OEM Standard 1/2 inch	
DECK	
Framework: All main longitudinal members fabricated with 100,000# minimum yield steel flanges with 50,000# webs	
Deck Design: Beam Deck (MBMD) deck design	
Deck Length: Beam Deck (MBMD) design - 29 feet clear deck length **Note: OAL with this option is 55 feet with standard axle spread	
Loaded Deck Height: 22 inches with 6 inches ground clearance	
Crossmembers: On 24 inch centers (nominal)	
Tool Box: 2 Fully covered trays in front of deck between mainbeams with lockable covers	
Hammer Plate: None	
REAR BRIDGE	
Front Bogie Ramp: Included	
Boom Trough: Low Boom Well V crossmembers with bolt-in V pan	
Deck to Bogie Connection: Modular	
Bolsters: Recessed	
Covered Rear Bogie: None	
Rear Bogie Height: 40 7/8 inches	
Connections for Future Axle Attachment: Air and electrical connections to go along with connecting ears	
Liquid Filled Gauge: None	
AXLES	
Number of Axles: 3	
Axle Capacity: 25,000 lb. nominal capacity per axle NOTE: GAWR determined by suspension type, brakes, tires and other components.	

Axle Spread: 60 inches (between axles) **Note: Adds 11 inches to overall length**	
Dust Shields: None	
Brakes: 16.5 inches x 7 inches with 5.5 inches autoslacks - heavy duty brake drums - outboard mount	
Spring Brakes: Spring brakes on 2 axles	
SUSPENSION	
Framework: All main longitudinal members fabricated with 100,000# minimum yield steel flanges with 50,000# webs	
Suspension: Air ride	
ABS: None required	
First Axle Lift: Chain lift first axle	
Third Axle Lift: Air lift	
Mechanical Ride Height Control: 7-position mechanical ride height control system	
Manual Dump Valve: Manual Dump Valve (Push Pull)	
Load Scale: None Standard	
WHEELS AND TIRES	
Wheels: 8.25 x 22.5 LVL One buffed wheels	
Tires: 275/70R 22.5 OEM Standard	
Hubodometer: None Standard	
Tire Inflation: None Standard	
LIGHTING	
Electrical System: DOT sealed beam and harness with LED lights and 4 inch flush mounted battery powered amber strobes	
Tail Lights: 3 tail light package	
Electrical Receptacle: J560 7-pin connector	
Marker Lights: 3 marker lights per side including mid turn	
Additional Marker Lights: None Standard	
PAINT	
Paint: Fontaine black polyurethane enamel PN 51172000/G02BC0001	
MISCELLANEOUS	
Lash Rings: 11 pair - 22 total	
Flag Holders: 2 pair flag holders	
AVAILABLE COMPONENTS	
Flipbox: None included	
Flip Axle: 51/60 rear flip axle -LVL One buffed wheels -275/ 70R 22.5 Tires OEM Standard Serial Number A6013	
Hydraulic Flip Axle Option: None Standard	
Dust Shields on Flip Axle: None	
Spreader: None	
TERMS	
Additional Options:	
Punch Plate toolbox bottoms full length of deck between mainbeams	
Override Chains on all axles	
Additional 6 pair of lashing rings customer and engineering to approve location A4643 for reference	

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.