

HALE

TRAILER

BRAKE & WHEEL



A027371
VIN: A6011

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer



800-232-6535 *FINANCING AVAILABLE

Renegade 20 Air Tandem, 20 inch Loaded Deck Height, Mechanical Gooseneck (Model: RENEGADE 20)

REN LX40**F*831542

Est. Wt.: 16,380# +/- 3%

TRAILER - GENERAL

Capacity: 40 tons in 16-foot length - GAWR and GVWR determine legal loads

Width: 8 feet 6 inches

Compatibility: Designed to accept optional flip box (gooseneck extension) and third flip axle

GOOSENECK

Length / Width: 47 feet 11 inches - 102 inches wide

Gooseneck Design: Mechanical removable with removable guide rollers - Combination figure-8 plate which provides 50 inches and 52 inches loaded - Swing radius of 81 inches

Gooseneck Platform: Full-width gooseneck platform with 1 1/8 inch wood floor

Gooseneck Fenders: Aluminum fenders at rear of gooseneck

DECK

Deck Design: Flat level deck design

Deck Length: 31 feet 0 inches clear deck length--OAL with this option is 49 feet 11 inches

Loaded Deck Height: 20 inches with 6 inches ground clearance

Crossmembers: On 12 inch centers

Flooring: 1 3/8 inch nominal wood (full width)

Recessed Floor Mounted D-Ring Package: None

Front Ramps: None, front of deck sloped top down to assist in loading with traction cleats

Extension Brackets: Outriggers - 14 pair - 28 total removable swing type, 1 pair - 2 total removable hook-on type

Front Bogie Ramp: Sloped steel bogie ramp (full width)

Deck to Bogie Connection: Fixed

AXLES

Number of Axles: 2

Axle Capacity: 25,000 lb. nominal capacity per axle NOTE: GAWR determined by suspension type, brakes, tires and other components.

Axle Spread: 54.5 inches (between axles)

Brakes: 16.5 inches x 7 inches with 5.5 inches autoslacks - heavy duty brake drums - outboard mount

Spring Brakes: Spring brakes (2 axles)

Dust Shields: None

SUSPENSION

Framework: All main longitudinal members fabricated with 100,000# minimum yield steel flanges with 50,000# webs

Suspension: Air ride with automatic controls

ABS: 4S/2M system without diagnostic tool and cable

Load Scale: None Standard

WHEELS AND TIRES

Wheels: 8.25 x 22.5 steel disc - hub-piloted

Tires: 255/70R 22.5 H ply OEM Standard

Hubodometer: None Standard

Tire Inflation: None Standard	
REAR BRIDGE	
Covered Rear Bogie: Rear bogie platform with 1 1/8 inch wood floor	
Rear Bogie Height: 40 inches	
Bumper: 3 tail light package	
Connections for Future Axle Attachment: Air and electrical connections to go along with connecting ears	
Mini Boom Trough & Traction Cleats: None	
Accent Package: Stainless steel bumper insert	
Liquid Filled Gauge: Included	
LIGHTING	
Electrical System: DOT sealed beam and harness with LED lights and 4 inch flush mounted battery powered amber strobes	
Marker Lights: 7 marker lights per side including mid-turn	
Electrical Receptacle: J560 7-pin connector	
Additional Marker Lights: None Standard	
PAINT	
Paint: Fontaine black polyurethane enamel PN 51172000/G02BC0001	
MISCELLANEOUS	
Lash Rings: 9 pair - 18 total	
Flag Holders: 2 pair flag holders	
VIN Plate: Bilingual VIN plate	
Registration/Document Holder: Registration/document holder installed	

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.