

**TK80MG-HG detachable gooseneck, 70,000 Lbs in 16 feet 14009-80MG-HG_New

14009-Base

Item #	Category	Description	Weight (lbs)	Qty
14009	Open Deck	**TK80MG-HG detachable gooseneck, 70,000 Lbs in 16 feet		

14009-General

			Weight	
Item #	Category	Description	(lbs)	Qty
15710	Overall Length	Max 48' Length Trailer		
		24' lower deck length		
14074	Overall Width	102" Wide		
17866	Paint	Zinc-rich Primer		
08024	Paint	S7203 Black with white decals		
18508	Paint	Red & white conspicuity markings		
14764	Flagholders	Flag holder tubes - 1 pair on front of GN (or front of bed if narrow GN), 1 pair at rear of trailer		

14009-Gooseneck

			Weight	
Item #	Category	Description	(lbs)	Qty
17864	Gooseneck	Hyd 10'-2" (14" KP fixed / 78" SC) full width; (reduces deck length)		
14051	Gooseneck	Steel gooseneck		
14053	Gooseneck	No lift arm on mech GN (Lift arm std on all hyd GN's)		
14056	Gooseneck	Hyd PTO (only available on hyd GN)		
14059	Gooseneck	No Gooseneck Flip		
14066	Gooseneck	Quick coupler connection between gooseneck and main deck		
14068	Gooseneck	Manually operated gooseneck lock pin release		
14071	Gooseneck	Chain rack for hydraulic neck (only available with PTO hyd)		

14050	Fifth Wheel / King Pin	Hyd 5-position w/ 50" 5th wheel height, single stirrups (only available on hyd GN)
14141	Decking, Gooseneck	1-1/8" Apitong decking GN outer bays (flush)
14144	Decking, Gooseneck	1-1/8" Apitong decking GN inner bay (Flush)
14738	Tie Downs	2-Pr Straight recessed D-Rings on gooseneck corners (full width gooseneck only)

14009-Deck

			Weight	
Item #	Category	Description	(lbs)	Qty
10028	Main Deck	Full-width deck - 4 beam main frame construction		
		Overall length determined by 24' deck length		
14076	Main Deck	18" Deck height - 6" ground clearance		
14102	Main Deck	Steel cross members 12" OC in main frame; 8" full width I-beams alternating with 4" stub I-beams; keyhole slots 24" OC (cannot be used with pullouts)		
14106	Main Deck	Brackets for Swing-out and storage area with loose decking over top of storage area in center bay (cannot be used with box beam cross members)		
14729	Main Deck	Tapered front approach (down to 4" at front)		
14730	Main Deck	3/4" Traction aids on front approach		
14731	Main Deck	Triangle cut-outs on beams		
17808	Main Deck	No outrigger planks		
14147	Decking, Main Deck	1-3/8" Apitong decking main deck outer bays (raised)		
14150	Decking, Main Deck	1-3/8" Apitong decking main deck inner bay (raised)		
14740	Tie Downs	8-Pr Bent D-Rings minimum on main frame. (Approx 48" O.C and between all pullouts with pullout option)		

14009-Wheel Area

			Weight	
Item #	Category	Description	(lbs)	Qty
14118	Wheel Area	Reinforced for flip axle - includes brackets, air and electrical; with deck access cover (only available on 2 axle WA) (includes lid over glad hands)		
14124	Wheel Area	Steel wheel area, includes steel outer rails, cross members and tail channel		
14735	Wheel Area	3/4" Traction aids on wheel area transition		
14736	Wheel Area	Mini boom trough		
14737	Wheel Area	Dock bumpers at rear of wheel area		
14153	Decking, Wheel Area	1-1/8" Apitong decking wheel area outer bays (Flush)		

14155	Decking, Wheel Area	1-1/8" Apitong decking Wheel Area inner bay (Flush)
14130	Axle Spacing	54.5" Axle spacing
14765	Miscellaneous	Wide load sign brackets
14741	Tie Downs	1-Pr Straight D-Rings on wheel area transition
14742	Tie Downs	1-Pr Straight pan style D-Rings on front wheel area corners, 1-Pr recessed D-rings on rear wheel area corners
14759	Flaps, Mud Guards & Fenders	Mudflaps

14009-Suspension

			Weight		
Item #	Category	Description	(lbs)	Qty	
14133	Suspensions / Axles	25,000-lb. (5/8" wall) axles (per complete axle)		2	
14743	Suspensions / Axles	Air ride suspension with cable adjustable ride height control			
14744	Suspensions / Axles	Air suspension control panel (includes liquid filled air gauge) located on side of wheel area ahead of rear axle			
14749	Suspensions / Axles	2 Axle			
14757	Suspensions / Axles	Wheel end lube type - Oil			
14140	Brakes	Air Disc Brakes (must select 5/8" wall, 102" wide, and 22.5" wheels) (per complete axle)		2	
14758	Brakes	4S2M anti-lock brakes with spring brakes			
14138	Hub / Drum	Steel hub piloted, Cast drum, Tapered (D) spindle (per complete axle)		2	
12849	Wheels (inside)	8.25 x 22.5 10-hole steel disc wheel		4	
15052	Wheels (outside)	8.25 x 22.5 10-hole polished (XP) aluminum wheel (per wheel) Accuride ILO Std 8.25 x 22.5 10-hole steel disc wheel	(120)	4	
10058	Spare Wheel	No Spare Wheel			
16219	Tires	Continental 255/70R22.5 HSR2 SA - 16 ply (tire only) (per tire)		8	
10059	Spare Tires	No Spare Tire			

14009-Electrical

Item #	Category	Description	Weight (lbs)	Qty
18228	Lights / Electrical	No remote flasher w/ battery backup		
14648	Lights / Electrical	Grote LED Lights		
17489	Lights / Electrical	One (1) license light		
18726	Lights / Electrical	Grote sealed electrical harness system		

14760	Lights / Electrical	1 pair of oval penny lights on side of gooseneck
14761	Lights / Electrical	1 pair of oval penny lights on front of gooseneck (must be full width gooseneck)
14762	Lights / Electrical	3 pair of oval penny lights on main deck with (2) pair of mid-turn lights, OXOXO
14763	Lights / Electrical	1 pair of oval penny lights on side wheel area and (3) oval penny ID lights at rear of wheel area
14166	Lights / Electrical	One pair of 4" round quad flash amber strobes at rear w/ switch mounted by suspension controls ILO 3rd tail light package
18230	Lights / Electrical	Center cluster lights illuminated with marker lights
14649	Lights / Electrical	7-pole electrical connector
99999- 16	Lights / Electrical	Custom Option 200571 - TK90HG: 2 LED work lights facing toward the load deck, located at rear of full width GN.

14009-Additional Options

		·		
			Weight	
Item #	Category	Description	(lbs)	Qty
O9999- 01	Custom Options	Custom Option 1204771 - MG/HG: Last 2 Bays In Center of Main Deck, In Front of Mini Boom Trough to be for Storage. (Install Bottom & Wood Over w/ Finger Hole).		
204405	Custom Options	Custom Option 204405 - TK75MG: Air Lift Rear Axle for 2-Axle Wheel Area		
		NOTE, DUE TO THE NATURE OF THE DESIGN THE LIFT AXLE MAY CAUSE "FLAT SPOTTING" OF THE LIFTED TIRE. TRAILKING IS NOT RESPONSIBLE FOR THIS RESULT		
O9999- 03	Custom Options	Custom Option 200287 80MG - 24' Main Deck Length ILO STD 29' (will be used with tandem trailer and flip axle).		