

# HALE

## TRAILER

BRAKE & WHEEL



A027512  
VIN: 941035

### SALES | RENTALS | PARTS | SERVICE

<b>Allentown, PA:</b> 800-383-8894	<b>Little Rock, AR:</b> 833-424-8944
<b>Baltimore, MD:</b> 888-601-7500	<b>Portland, ME:</b> 800-325-4253
<b>Concord, NC:</b> 800-438-2250	<b>Raleigh, NC:</b> 833-418-9777
<b>Delmar, DE:</b> 866-486-1400	<b>Scranton, PA:</b> 800-569-1400
<b>Des Moines, IA:</b> 888-673-5011	<b>Springfield, MA:</b> 800-854-5306
<b>Elkton, MD:</b> 800-544-7127	<b>Voorhees, NJ:</b> 866-315-0235
<b>Jacksonville, FL:</b> 800-828-3055	<b>Walpole, MA:</b> 800-854-5310

haletrailer.com | @haletrailer     

**800-232-6535** \*FINANCING AVAILABLE

#### Description

ART-60-252 EA Roll Off , 60,000 lbs Cap., 25FT, Tandem  
Serial # 2239

Overall Length: 26' 7"  
Container Frame Length: 25'  
Kingpin to Last Axle: 20' 1"  
Rated 60,000 lbs. Lift Capacity  
Container Size Range- 10'-25' Outside Rail Containers

**MAIN FRAME:**  
12"X 4"X 1/4" Rectangular Tubing  
12"X 4" Cross Members for Main Frame  
Top Wrap: 1/2" X 4" Flat Bar Wear Pad  
Bottom Wrap: 3/4" x 4" Flat Bar  
(2) 1 1/4" Fixed Stops at Front of Trailer  
(12) 3 1/2" Rollers Welded to Outside Frame  
3/4" King Pin Plate with 3/4" Plate Supports & 2" Round Bar Stiffener

**STABILIZER FRAME:**  
4"X4"X 1/4" Tube with 4"x4"x3/8" Angle Wrap  
Hinges: 2" Round Bar  
28"x16"x5/8" Draft Arm Support Plates

**HYDRAULICS:**  
(2) 8.5"- 4 Stage Telescopic Main Lift Cylinder 133,000 lbs. @ 2,400 PSI  
(2) Ace Independent Reeves: 3 1/2 Rod 7" Bore Reeving Cylinder 88,000 lbs. ea.  
Directional Valve with Pressure Gauges and Adjustable PSI – Set to 2,450 PSI  
Hoses: 3/4" 3000 PSI Hoses with Nylon Covering  
Hydraulic Pipes: 3/4" Steel Pipe  
Standard JIC Fitting on All Hydraulics  
NO HYDRAULICS IN REAR OF TRAILER

**CABLE AND AFFILIATED COMPONENTS:**  
Cable-7/8" IWRC Cable, (4) Cable Clamps, Cable Button with Cast Ring  
Pulleys: 10" Sheave with 2.5" Pin (Qty 3)  
Pulley Block - Independent (2)  
Independent Pulley Track

**RUNNING GEAR:**  
H900 50,000 lbs. Spring Single Point Suspension (Tandem)  
Suspension Hanger: 21" Fabricated I-Beam

Ordered	Shipped	Description
		<p>(2) 25,000 lbs. 5" Round Axles  71.5" Track, 38" Spring Center  Brake Control: Spring Loaded 16" x7.5"- Drum  ABS: 2S1M  10 Hole Uni-Mount Hubs &amp; Drums  10 Hole Uni-Mount Rims w/11R22.5 Tires  Fenders- Rubber 2-Ply  Ace Logo Rubber Mud Flap with Hook  2-Speed Landing Gear 120K lbs.- Jost</p> <p>LIGHTING &amp; SAFETY  All L.E.D Lights  All Lights Meet DOT #108  Lights &amp; Harness- Truck Lite  Body Hoist Up Alarm- LED Strobe  ICC REGULATED BUMPER- AIR ACTUATED  Meets FMCSA 49 CFR § 393.86  (4) Nylon Tie Down Strap – More can be added*  (1) Winch Bar with Holder</p> <p>Warranty- In Years  (5) On Main Frame- Excluded Rollers and Greaseable Items  (1) All Hydraulic Components  (1) on All Items Manufactured by Ace  Axles &amp; Suspension are subject to manufacturer discretion</p>
		115-1003-I EA Front Work Lights Installed
		221-1007 EA Automatic Tire Inflation Kit, Pre-assembled
	1.00	STEEL SURCHARGE Due to increased prices of steel, a steel surcharge may apply.
		252-3001-25H EA Tarp System, Roll-Off Complete 25' Hyd Roll Rite (Hydraulic) - Hydraulic Ace Tower

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.