

HALE

TRAILER

BRAKE & WHEEL



A027513
VIN: 941038

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894	Little Rock, AR: 833-424-8944
Baltimore, MD: 888-601-7500	Portland, ME: 800-325-4253
Concord, NC: 800-438-2250	Raleigh, NC: 833-418-9777
Delmar, DE: 866-486-1400	Scranton, PA: 800-569-1400
Des Moines, IA: 888-673-5011	Springfield, MA: 800-854-5306
Elkton, MD: 800-544-7127	Voorhees, NJ: 866-315-0235
Jacksonville, FL: 800-828-3055	Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer



800-232-6535 *FINANCING AVAILABLE

Quantity	Product ID	Description
1.00	ART-60-323	EA New ART-60-323 Ace Rolloff Trailer TriAxle

1.00 ART-60-323

EA New ART-60-323 Ace Rolloff Trailer TriAxle

New Ace Rolloff Trailer ART-60-323 Tri-axle Spring
Overall Length: 33' 6"
Container Frame Length: 31' 4"
Kingpin to Last Axle: 27' 2"
Rated 60,000 lbs. Lift Capacity
Container Size Range- 10'-32' Outside Rail Containers

MAIN FRAME:

12"X 4"X 1/4" Rectangular Tubing
12"X 4" Cross Members for Main Frame
Top Wrap: 1/2" X 4" Flat Bar Wear Pad
Bottom Wrap: 3/4" x 4" Flat Bar
1/4" Hollow Truss Mounted Below Main Frame with 1/2" X4"
Bottom Wrap
(2) 1 1/4" Fixed Stops at Front of Trailer
(12) 3 1/2" Rollers Welded to Outside Frame
3/4" King Pin Plate with 3/4" Plate Supports & 2" Round Bar
Stiffener

STABILIZER FRAME:

4"X4"X 1/4" Tube with 4"x4"x3/8" Angle Wrap
Hinges: 2" Round Bar
28"x16"x5/8" Draft Arm Support Plates

HYDRAULICS:

(2) 8.5"- 4 Stage Telescopic Main Lift Cylinder 133,000 lbs. @
2,400 PSI
(2) Ace Independent Reeves: 3 1/2" Rod 7" Bore Reeving Cylinder
88,000 lbs. ea.
Directional Valve with Pressure Gauges and Adjustable PSI –
Set to 2,450 PSI
Hoses: 3/4" 3000 PSI Hoses with Nylon Covering
Hydraulic Pipes: 3/4" Steel Pipe
Standard JIC Fitting on All Hydraulics
NO HYDRAULICS IN REAR OF TRAILER
CABLE AND AFFILIATED COMPONENTS:
Cable-7/8" IWRC Cable, (4) Cable Clamps, Cable Button with
Cast Ring
Pulleys: 10" Sheave with 2.5" Pin (Qty 3)
Pulley Block - Independent (2)
Independent Pulley Track

RUNNING GEAR:

Quantity	Product ID	Description	New ART-60-323 Ace Rolloff Trailer TriAxle New Ac
		H900 Single Point 50,000 lbs. Suspension Suspension Hanger: 21" Fabricated I-Beam (2) 25,000 lbs. 5" Round Axles LIFT AXLE: 20K 215T RIDEWELL LIFT AXLE Brake Control: Spring Loaded 16" x7.5" ABS: 2S1M 10 Hole Uni-Mount Hubs & Drums 10 Hole Uni-Mount Rims w/11R22.5 Tires Fenders- Rubber 2-Ply Ace Logo Rubber Mud Flap with Hook 2-Speed Landing Gear 120K lbs. LIGHTING & SAFETY All L.E.D Lights All Lights Meet DOT #108 Lights & Harness- Truck Lite Body Hoist Up Alarm- LED Strobe ICC REGULATED BUMPER- AIR ACTUATED Meets FMCSA 49 CFR § 393.86 (4) Nylon Tie Down Strap – More can be added*	
1.00	80-3004	PAINT Cleaned, Primed, Painted Industrial Epoxy (Black) WARRANTY- In Years (5) On Main Frame – Excluded Rollers and Greaseable Items (1) All Hydraulic Components (1) on All Items Manufactured by Ace Axles & Suspension are subject to manufacturer discretion EA Removable Stop Set Driver & Passenger	
2.00	46-1003	EA Winch, Standard, Weld-on	
1.00	252-3001-32H	EA Tarp System, Roll-Off Complete 32' Hyd Roll Rite (Hydraulic) - Hydraulic Ace Tower Ace Gantry Tower Assembly Roll Rite Hydraulic Gantry Kit Roll Off Tarp Hose & Fitting Kit Pipe, Roll Off 32'-34' 1/2"x84" Tarp, Black Mesh	
1.00	115-1003-IOLD	EA Front Work Lights - Installed	
1.00	221-1007	EA Automatic Tire Inflation Kit	

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
 Equipment availability, prices and specifications are subject to change without notice.