

HALE

TRAILER

BRAKE & WHEEL



A027650
VIN: 44570

SALES | RENTALS | PARTS | SERVICE

| | | | |
|-------------------|--------------|------------------|--------------|
| Allentown, PA: | 800-383-8894 | Little Rock, AR: | 833-424-8944 |
| Baltimore, MD: | 888-601-7500 | Portland, ME: | 800-325-4253 |
| Concord, NC: | 800-438-2250 | Raleigh, NC: | 833-418-9777 |
| Delmar, DE: | 866-486-1400 | Scranton, PA: | 800-569-1400 |
| Des Moines, IA: | 888-673-5011 | Springfield, MA: | 800-854-5306 |
| Elkton, MD: | 800-544-7127 | Voorhees, NJ: | 866-315-0235 |
| Jacksonville, FL: | 800-828-3055 | Walpole, MA: | 800-854-5310 |

haletrailer.com | @haletrailer



800-232-6535 *FINANCING AVAILABLE

Model: AC-22.5-AR
Capacity: 20 Tons

1. TONGUE

Pintle eye
Tongue

Adjustable pintle eye (3" ID) with 48" chain and grab hooks
6'-6" with lockable tool box with aluminum diamond plate lid - move hinge 4" forward

Drop leg

2-speed, 50,000# crank down dual landing leg, mounted to main beams and headboard

Electrical receptacle
Headboard

Seven pin connector
8" high full width

2. DECK

Deck section design
Deck section length
Deck section width
Loaded deck height
Flooring
Lash rings

One piece tongue, main beam and beavertail (cold formed)
32'-0" (26'-0" flat with 6'-0" beavertail)
8'-6"
34"
1-1/2" apitong with individual wheel wells
18 total -
7 each side on flat deck, evenly spaced (straight style), 14 total
1 each side on beavertail 24" down from top of beavertail (straight style), 2 total
1 each side on beavertail as far rearward as possible (straight style), 2 total
14" x 26# deep hi-tensile
6" deep hi-tensile
8" deep hi-tensile
6'-0" Double break with wood flooring full width
38" wide x 6'-6" long air ramps with wood flooring, stored vertically with lock bar

Mainbeams
Crossmembers
Sidemembers
Beavertail
Ramps

3. RUNNING GEAR

Number of axles
Axle capacity

2
25,000#, full width track; GAWR =22,400#

Brakes

12-1/4" x 7-1/2" air with 2S/1M ABS, 6" auto slacks and type 30 brake chambers.
Spring brakes on both axles.
Aluminum air tanks

Wheels

Aluminum/steel disc with oil seals (6.75 x 17.5), inner wheels steel, outer aluminum wheels polished

Tires

Eight (8) 235/75R17.5 (H) 16PR radials
Use valve stem extensions on inside wheels

Suspension

44,800# Hutch spring

4. GENERAL

Lights and wiring

12 volt LED system (license plate regular), supplied with female 7-way plug on tongue, SUPPLY JUMPER CORD FOR TRUCK
strobe lights mounted in rear ramps with switch in tool box

Paint

Valspar standard Talbert black

Estimated empty weight

10,650#

Additional general specifications

Formed step in front of 1st axle both sides of trailer

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.