



A027651
TEMP VIN: S026599

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE



Product
Hauled: Water

Barrel Description

Model	SRJ9 6250-1, Stainless steel, Round, Jacketed, Non-code trailer
	Trailer to designed level with a 48" king pin setting.
Code	Non-code
Capacity	6250 gallons (shell full)
Compartments	One
Shape	Straight, Round
Shell Material	T304 Stainless steel, 12 gauge. Two piece barrel with one circumferential weld.
Head Material	T304 Stainless steel, 12 gauge (5 PSI max test pressure)
Operating Pressure	Atmospheric
Design Temperature	212 Degrees F. (TEMPERATURE RATING OF 212 DEGREE F. WITH STANDARD INSULATION. THE USE OF OTHER INSULATIONS MAY DECREASE THE MAXIMUM TEMPERATURE RATING FOR THIS TRAILER. SEE INSULATION FOR MAXIMUM TEMPERATURE RATING CHANGE.)
Overall Length	42' 6"
	Max overall height allowed is 11'
Product	Various; to be compatible with the materials of construction.

Other Barrel Information

* Baffles	4	10 gauge T304 stainless steel full circle, flanged
		Equally, spaced in the tank.
Heat		None

Plumbing		None
Intransit		None
Weld finish		W-0 inside
Construction		
Rings		Stainless steel channel
Longerons		12 gauge Stainless steel channel
Frame		Stainless steel frame
* Frame	2	Frame extension. Installed over 2 ring spaces, with 8" sump in the forward position, customer to install cabinet and pumping system.
Dam		Non-code, Stainless steel construction
* Dam Drains		2" Stainless steel drains under jacket, both roadside and curbside.
Overturn Protection		None
Cleanout overturns		None
Manhole		OEM 20" stainless steel cover assembly with stainless steel collar, six hold-down and manhole stop.
Gasket		White hypalon gasket in cover
Fill		None
Gasket		None
Splash deflector		None
Insulation		Fiberglass, 5" compressed to 4"
* Thermometer		No thermometer installed.
Jacketing		22 gauge stainless steel bright finish
* Jacket heads		18 gauge stainless steel bright finish jacket heads.
Underlayment		None
Capacity indicator		None
Static cable		No static cables installed.
Hose Carriers		
Hose Carrier		None
Carrier Location		None
Lights and Wiring		
Lights		12-volt, Truck-Lite grommet mount LED lamp system complying to FMVSS. Combination center marker / turn signals, one each side.

Wiring	Center marker/turn light installed low.
* Wiring	Plug-in style harness system.
* Wiring	Air and electrical lines mounted in bright stainless steel covering down the center of the trailer.
Rear Lights	Air and electrical lines mounted in bright stainless steel covering from landing gear to the front head.
* Extra Lights	Enclosed in stainless steel light boxes
Nose box	Ring of Fire 2, Red Maxxima LED Strip Lighting on rear head, Full Circle
Gladhands	Standard 7 way, J560 receptacle without circuit breakers.
	Gladhand, Phillips, Quick Release

Undercarriage

Upper 5th Wheel	5/16" Standard duty upper coupler with Heavy duty double hubbed kingpin.
Paint	Fifth wheel plate painted black.
Landing Gear	Jost A440, 2-speed, load bearing, telescopic, with swivel type sand shoe.
Frame	Stainless steel construction
Bracing	Stainless steel, with cross brace.
Crank location	Crank handle located on roadside
Tire carrier	None.
Suspension	Hendrickson INTRAAX AANT23K tandem axle with 5.75" diameter Hendrickson integrated axles. Axle spacing to be determined by scale. Trailer to designed level with a 48" king pin setting.
Dump valve	Hendrickson AK-54 automatic dump valve. System exhausts the air from the air bags when the glad-hands are disconnected or when the parking brake is activated and automatically refills when glad-hands are reconnected.
Lift Axle Control	None - no auto lift controls included
Hangers	Stainless Steel weld on hangers with soft coat applied to axle and trailing arm.
Subframe	3/16" Stainless steel subframe, 38" wide with stainless fender supports.
Bumper	Stainless steel non-code, straight bolt-on bumper/mudflap bracket.
Under-ride Protection	No Underride included
Beam	Straight axle beam
Track	Axle track, 71.5"

Hub & drums	Hendrickson 5 year warranty, Ready to roll with Duralite hubs, cast drums and semi-fluid grease. OEM slack adjusters, seals, brake chambers and brake lining.
Anti-lock / Roll stability	Wabco 4S/2M with "RSS-Plus" roll stability support system for tandem (2) axle airride suspension set.
Air system	One (1) aluminum tank system. 2850 cu. in. meeting FMVSS 121 D.O.T. specifications.
Emission Compliance	NA
* Wheels	ALCOA ULTRA ONE 24.5 X 8.25 HIGH POLISH. ALCOA #98U637
* Tires	Original Equipment Manufacturer, 11R-24.5, Load Range G 14 Ply.
Tire pressure system	No tire pressure system included.
* Front	Front stainless bright finish contour tandem axle
* Rear	Rear stainless steel bright finish contour tandem axle
Mud flaps	White, anti-sail and anti-spray with Polar logo, mounted front and rear.

Valving and Piping

Seal provisions	None
* Sump	8" stainless steel flanged bottom sump, with blind flange. Installed 114" from the back of the landing gear frame to the center line of the 8" sump.
Emergency Valve	None
Emergency Valve Operator	None
EVO Lines	None
EVO Location	None
* Pipe	None
Discharge location	Rear of trailer.
* Outlet valve	None. No outlet valve installed. TTMA flange installed on piping unless otherwise specified.
* Adaptor	None
* Cap	None.

Venting and cleanouts

* Venting	4" free breathing with elbow and splash deflector Installed in the dam area, max overall height allowed is 11', this vent will need to allow the customer to use a 1250 gal per minute pump.
-----------	---

* Vacuum	None
Pressure package	None
Cleanouts	None
Caps	None, No caps installed.
Pressurizing Line	
Pressure Line	None, no pressure line installed.
Walkway and Ladder	
Top center	None
* Ladder	None. No access to top of trailer provided.
* Ladder Location	No access provided to top of trailer.
Cabinet	
Cabinet	None. No Cabinet installed.
Overfill system	
Overfill system	None
Pump System	
Hydraulic Lines	None
Meter	None
Meter Installation	None
TANK Ai™	
IntelliSECURE	TANK Ai™ - None installed
Miscellaneous	
Decals	Standard warning and safety package. Decals in English.
* Conspicuity Tape	Continuous 3M tape
Customer Logo	None
Document holder	Truck Lite 97960 Certificate Holder. Install in standard location unless otherwise specified.
Calibration	Computer generated theoretical calibration chart, 1/4" increments. Based on innage.
Placards	None
Paint	None. No paint or primer installed on trailer.
Passivate	None
Warranty	Polar standard two year.
Tests	Standard testing.
Drawings	None.
* EST	Stainless steel angle brackets for continuous tape, installed low on the jacketing.

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.