

Model: AC-20-AR **Capacity in tons:** 20

1. TONGUE

Pintle eye Adjustable pintle eye (3" ID) with 48" chain and grab hooks

Tongue 5'-6" with lockable tool box with aluminum diamond plate lid - move hinge 4"

forward

Drop leg 2-speed, 50,000# crank down dual landing leg, mounted to main beams and

headboard

Electrical receptacle Seven pin connector Headboard 8" high full width

2. DECK

Deck section design One piece tongue, main beam and beavertail (cold formed)

Deck section length 30'-0" (24'-0" flat with 6'-0" beavertail)

Deck section width 8'-6" Loaded deck height 32-1/4"

1-1/2" apitong with individual wheel wells Flooring

Lash rings 14 total -

> 6 each side on flat deck (straight style), 12 total 1 each side on beavertail (straight style), 2 total

Crossmembers 6" deep hi-tensile Mainbeams 12" deep hi-tensile x 22# Sidemembers 8" deep hi-tensile

Beavertail

6'-0" Double break with wood flooring full width

38" wide x 6'-6" long air ramps with wood flooring, stored vertically with lock bar Ramps

3. RUNNING GEAR

2 Number of axles

Axle capacity 25,000#, full width track

**Brakes** 12-1/4" x 7-1/2" air with 2S/1M ABS. Spring brakes on both axles.

Wheels Steel disc with oil seals (6.75 x 17.5) Eight (8) 215/75R17.5 (H) 16PR radials Tires Use valve stem extensions on inside wheels

Suspension 44,800# Hutch spring

4. GENERAL

12 volt LED system (license plate regular), supplied with female 7-way plug on Lights and wiring

tongue, SUPPLY JUMPER CORD FOR TRUCK

Special color Blue Valspar urethane matched to a customer supplied paint chip Paint

(NON-METALLIC) with ZINC RICH primer

Additional general specifications Formed step in front of 1st axle both sides of trailer