

Model: Axle Attachment Capacity in tons: 60

## **1. DESIGN PARAMETERS**

Type Framework Suspension Axle attachment connections

Axle capacity Brakes Wheels

Anti-lock brake system Tires Bridge width Axle frame height Half bolster Lash rings Lights and wiring

Paint Mudflaps Additional design specifications

Compatibility

Flip-up & removable Fabricated 30,000# Capacity Ridewell air Attachment to be equipped with top and bottom connecting ears, pin tubes with bolts and nuts, shims, chrome tapered connecting pins, air and electrical connections 25.000# - GAWR 24.700# 16-1/2" x 7" air actuated Ten (10) stud; 285.75mm B.C. aluminum/steel disc hub piloted system with oil seals, inner wheels steel with outer aluminum wheels polished None Four (4) 275/70R22.5 (H) 16PR radials 8'-6" 41" frame: 37" bolster With flag holder slots 2 at rear bent style 12 volt system with the following: All lights to be LED excluding license plate light All marker/I.D. lights to be 3/4" bullet style 4 combination (2 PER SIDE) stop/turn/tail and back-up lights, back-up lights wired to switch on marker light circuit Strobe lights with switch at rear Wire for battery back-up Valspar standard Talbert black, R-Cure 800 series paint with ZINC RICH primer Talbert anti-sail 1) 2 rubber bumpers on top 2) 54" axle spacing 3) Over ride chains 4) Estimated empty weight: 2,850#

With existing Talbert Trailer, 60SA & 60CC

DISCLAIMER