



A028203 VIN: S027139

# SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894 Little Rock, AR: 833-424-8944 **Baltimore, MD:** 888-601-7500 Portland, ME: 800-325-4253 Concord, NC: 800-438-2250 Raleigh, NC 833-418-9777 Delmar, DE: 866-486-1400 Scranton, PA: 800-569-1400 Des Moines, IA: Springfield, MA: 888-673-5011 800-854-5306 Elkton, MD: 800-544-7127 Voorhees, NJ: 866-315-0235 Jacksonville, FL: 800-828-3055 Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer f 쭞 庙 🎯 🖀

800-232-6535

\*FINANCING AVAILABLE

#### Description

New ART-60-323 Ace Rolloff Trailer TriAxle New Ac

# **Quantity Product ID**

#### Description

1.00 ART-60-323

EA New ART-60-323 Ace Rolloff Trailer TriAxle

New Ace Rolloff Trailer ART-60-323 Tri-axle Spring

Overall Length: 33' 6"

Container Frame Length: 31'4" Kingpin to Last Axle: 27' 2"' Rated 60,000 lbs. Lift Capacity

Container Size Range- 10'-32' Outside Rail Containers

## MAIN FRAME:

12"X 4"X 1/4" Rectangular Tubing 12"X 4" Cross Members for Main Frame Top Wrap: ½" X 4" Flat Bar Wear Pad Bottom Wrap: 3/4" x 4" Flat Bar

1/4" Hollow Truss Mounted Below Main Frame with 1/2" X4"

**Bottom Wrap** 

(2) 1 ¼" Fixed Stops at Front of Trailer (12) 3 1/2" Rollers Welded to Outside Frame

34" King Pin Plate with 34" Plate Supports & 2" Round Bar

Stiffener

## STABILIZER FRAME:

4"X4"X 1/4" Tube with 4"x4"x3/8" Angle Wrap

Hinges: 2" Round Bar

28"x16"x5/8" Draft Arm Support Plates

## **HYDRAULICS:**

(2) 8.5"- 4 Stage Telescopic Main Lift Cylinder 133,000 lbs. @

2,400 PSI (2) Ace Independent Reeves: 3½ Rod 7" Bore Reeving Cylinder

88,000 lbs. ea.

Directional Valve with Pressure Gauges and Adjustable PSI –

Set to 2,450 PSI

Hoses: 3/4" 3000 PSI Hoses with Nylon Covering

Hydraulic Pipes: 3/4" Steel Pipe Standard JIC Fitting on All Hydraulics NO HYDRAULICS IN REAR OF TRAILER CABLE AND AFFILIATED COMPONENTS:

Cable-7/8" IWRC Cable, (4) Cable Clamps, Cable Button with

Cast Ring

Pulleys: 10" Sheave with 2.5" Pin (Qty 3)

Pulley Block - Independent (2) Independent Pulley Track

**RUNNING GEAR:** 

Quantity	Product ID	Description
		H900 Single Point 50,000 lbs. Suspension Suspension Hanger: 21" Fabricated I-Beam (2) 25,000 lbs. 5" Round Axles LIFT AXLE: 20K 215T RIDEWELL LIFT AXLE Brake Control: Spring Loaded 16" x7.5" ABS: 2S1M 10 Hole Uni-Mount Hubs & Drums 10 Hole Uni-Mount Rims w/11R22.5 Tires Fenders- Rubber 2-Ply Ace Logo Rubber Mud Flap with Hook 2-Speed Landing Gear 120K lbs. LIGHTING & SAFETY All L.E.D Lights All Lights Meet DOT #108 Lights & Harness- Truck Lite Body Hoist Up Alarm- LED Strobe ICC REGULATED BUMPER- AIR ACTUATED Meets FMCSA 49 CFR § 393.86 (4) Nylon Tie Down Strap – More can be added*
	80-3004 252-3001-32H	PAINT Cleaned, Primed, Painted Industrial Epoxy (Black) WARRANTY- In Years (5) On Main Frame – Excluded Rollers and Greaseable Items (1) All Hydraulic Components (1) on All Items Manufactured by Ace Axles & Suspension are subject to manufacturer discretion EA Removable Stop Set Driver & Passenger 3/4 Thk Stop For proper weight distribution on containers shorter than trailers overall length EA Tarn System, Roll-Off Complete 32! Hyd
		EA Tarp System, Roll-Off Complete 32' Hyd Roll Rite (Hydraulic) - Hydraulic Ace Tower
1.00	115-1003-I	EA Front Work Lights Installed
1.00	221-1007	EA Automatic Tire Inflation Kit, Pre-assembled