



A028246
VIN: 000063

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer



800-232-6535 *FINANCING AVAILABLE

Base Weight: 12,800

End Dump 2X

TRAILER

Overall Frame Length	*NPO*: 33 ft.
Overall Box Length	*NPO*: 33 ft.
Width	*NPO*: 96 in. width
Board Size	None Required
Wall Height	60 in.
Weight lbs +/- 3%	13462, including options
Cubic Yard Capacity	60

CHASSIS

Frame Construction	18 in. Extruded Aluminum Beam Construction, Milled Finish
King Pin Height	49 in.
King Pin Location	*NPO*: 18 in.
Fifth Wheel Plate	5/16 in.
Wear Pad	6 in. Braided rubber on top of frame to act as buffer between box and frame
Ride Axle Configuration	*NPO*: 2 of 25,000 lbs Capacity ; Intraax
Extra Lift Kit	None Required
Lift Axle Control Valve	None Required, for use with Lift Axle only
Steer Axle Configuration	None Required
Axle Spread	*NPO*: 52 in.
Ride Suspension	2 of Hendrickson Intraax - Webb Slacks, TSE Long Stroke Booster, fixed
Ride Suspension Controls	Electric
Steer Suspension	None Required
Steer Suspension Control	None Required
Wheel Monitor	None Required
Bearing	Propar Equal Inner and Outer
Hubs & Drums	Duralight Hubs and Drums
Dust Shields	Included
Ride Rims	8, 8.25 x 24.5 Aluminum Alcoa High Polish
Steer Rims	None Required
Ride Tires	*NPO*: 11R24.5 General Tires
Suspension Hanger	Galvanized
Steer Tires	None Required
Hubmeter	None Required
Spare Tire Carrier	None Required
ABS	Wabco 2S/1M
Weight Gauge	Located on front at 45 degree
Frame Finish	Milled, Non Polished
Paint Color for Steel Compo	Black
Board Color	None Required
Front Flaps	*NPO*: Full Height, Full Width Panels; 36 in. Panels w/Rubber Flaps
Mudflaps	3 Flaps Across the Rear of the Trailer
Fenders on Front	None Required
Fenders Over Axles	None Required
Calcium Tank	None Required
Air Tanks	Aluminum

CHASSIS

Landing Gear	Aluminum Jost 10 year, no lube w/paintee gear and braces: Driver Side
Toolbox	None Required

BOX CONSTRUCTION

Wall Panels	2 in. Hollow Core Double Wall 6061 Aluminum Extrusion. Fully Welded Interior Wall
Wall Thickness	Outside Wall 0.094 (3/32)in. and Inside Wall 0.125 (1/8) in.
Wall Finish	Polished
Last 10 Rear Wall Panels	*NPO*: Heavy Duty .188 in. (3/16) x .125 in. (1/8)
Floor Construction	*NPO*: .250 (1/4 in.) with .375 (3/8 in.) for last 10 ft. 6061 Aluminum Sheets welded together, supported by Reinforced Extruded Aluminum, C-Channel crossmembers on 4 in. centers
Floor Liner	None Required
Bulkhead Construction	3/16 in. 5083 Aluminum Sheets with Corners Formed into a Radius
Bulkhead Height	*NPO*: 60 in.
Bulkhead Steps	*NPO*: None
Tailgate	Heavy Duty 2 in. Hollow Core Double Wall 6061 Aluminum Extrusion. Fully Welded inside extruded frame
Tailgate Slope	Straight
Tailgate Type	*NPO*: Overslung w/2 Way and Ground Control
Tailgate Locks (Stainless)	Air Booster
Tailgate Hinges	Stainless
Compression Locks	Set(s): 1 per Side
Rear Tailgate Seal	Rubber Seal
Grain Chute	*NPO*: Medium 13 in. Chute Opening , comes with Stainless Hardware and Plastic Sliders
Sock Adapter	None Required
Header Type	None Required
Tarp	None Required
Tarp Drive	None Required
Front Tarp Shield	None Required
Rear Tarp Shield	None Required
Tarp Color	None Required
Tarp Supplies	None Required
Cross Pipes	None Required
Man Door	Located on Bulkhead,: Driver Side
Hoist Size	*NPO*: Custom Hoist - 8-5-250
Square Offs	Installed on Top Front Outside Corners of Box
Catwalk	None Required
Shovel Holder	*NPO*: Located on Dog House ; Located on Passenger Side
Broom Holder	Located on Dog House
Asphalt Lip	None Provided (If required It is 8 in. with no compression locks and 6 in. with bottom compression locks)
Steps - Front, Driver Side	None Required
Steps - Rear, Driver Side	None Required
Steps - Front Passenger Side	None Required
Steps - Rear, Passenger Side	None Required

BOX CONSTRUCTION

Jug Holder	None Required
Fork Lift Package	None Required
Hydraulic Hose	9 ft. With Winged Hose Ends
Document Holder	Standard Round

LIGHTING/ELECTRICAL

Electrical System	Grote
Lights	LED CMVSS 108 / FMVSS 108
LED Type	Colored
Rear Lighting	3 of 4 in. per side at rear , 3 of 2 1/2 in. in bolster, center
Rear Center Plate Lights	None Required
Lights Located in Bottom Rail	5 of 2 1/2 in. Amber evenly spaced per side
Lights Located in Top Wall	None Required
Tarp Shield Lights	None Required. They can only be mounted in tarp shield for Slide N Go Tarp Only
Tailgate Lights	None Required
Tailgate Post Lights	None Required
Signal Lights on Sides	Located in the Siderail
Reverse Lights below the rail	None Required
Light Shield	1/4 in. x 2 in.
Wiring	*NPO*: Air Gate Control and Suspension Control, Wired to 7 Way Aux and Control Box

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.