

HALE

TRAILER

BRAKE & WHEEL



A028469
VIN: D46734

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

Base Model #: LB 35-38CS
Serial #: 46734
components description
CAPACITY 35 Ton
OVERALL LENGTH 48'
OVERALL WIDTH 8' 6"
DECK LENGTH 30'
DECK HEIGHT 38" - Loaded
DECK FLOORING Apitong - 1 1/2" - Covering Entire Deck
MAINBEAMS 16" Fabricated I-Beam - Positive Camber
SIDE RAILS 12" Fabricated I-Beams - Positive Camber
GOOSENECK Flat Deck Wood w/ 21 Degree Slope - Steel & Traction Bars
KING PIN SETTING 18"
KING PIN PLATE 5/16 Plate
KING PIN SWING RADIUS 84"
KING PIN HEIGHT 48"
DOVETAIL 4' Steel w/ Traction Bars
WHEEL WELL Covered w/ Steel Plate & Traction Bars
LOADING RAMP Hydraulic - 96" x 36" - Wood Filled
LANDING GEAR Two Speed - 50,000 lbs.
D RING 28
WIDENING BRACKET 11 Pair of 12" Brackets (extends deck width 2')
12" Widening Brackets(Extends Deck Width 2').
TOOL BOX IN GOOSENECK Tool Box in Gooseneck
AXLE (2) 25,000 lb. Capacity w/ 49" Axle Spacings, Auto Slack, ABS
SUSPENSION Hendrickson 25K Air Ride Fixed - Manual Dump Valve
Manual All Axle Dump Vavle.
WHEELS Disc - Hub Piloted - ALUMINUM on all 8 wheels - Outside Polished
TIRES 255/70R22.5
PARKING BRAKES Type 30/30 Spring Brakes - 2 Axle
WIRING D.O.T Sealed Wiring Harness
LIGHTS STD w/ Strokes in Bumper (Change 2 in Center)
PAINT Black
CUSTOM 1 None
CUSTOM 2 Tire Inflation
Hendrickson CP.
CUSTOM 3 3 Pair of Micro Light Evenly Spaced Along Flat Deck
Ref SN # 19971
Q#10803

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.