HALE TRAILER BRAKE & WHEEL

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer

800-232-6535 *FINANCING AVAILABLE

ALPHA HD TRAILERS

A028771
VIN: T7495

A110HDG-SF-18 (Alpha Series Hydraulic Detachable)

Capacity 110,000 lbs.
Concentrated 110,000 lbs. in 16' as 3+1. 110,000 lbs. in 12' as a 4 in a row
OAL 53' **OAW** 102"

Gooseneck

12' 11" Hydraulic Detachable
51" 5th Wheel Height
15" & 41" King Pin
110" & 84" Swing Clearance
5 Position Ride Height
Hydraulics run by Wet Kit
Air Operated Lock pin
LED Work Light on Rear Platform

Main Deck

26' Length
12" Fabricated I-Beams
18" Loaded Deck Height
6" Ground Clearance
12" Cross Member Spacing (6")
HD Swing Out Outriggers
2 Sets of HD Removable Flat Back Outriggers
Chain Drops on 24" Centers
7 Bent d-Rings Per Side
5' Tool Box at Front with 2 Bent D-rings
6' Bucket Well at Rear with 2 Pr. Bent D-rings
Top Flange Reinforcement
Front Flip Load Ramps
1 3/4" Apitong Decking

Lighting

2 Tail Light Package with Stainless Steel Covers
2 Pr. Side Markers on Deck
Grote Ultra Blue-Seal Wire Harness

Sub Frame

14' 1" Long
39" Loaded Deck Height
32 Degree Rear Transition
with 4" rise to transition
Open Wheels with Bolsters
Chain Slots in Each Bolster
2 Flat D-Rings at Rear
Flag Holders
1 pair Stake Pockets in Tail Channel
Frame Reinforcement for Single Axle Stinger

Axles and Suspension

3 - 25,000 lb Axles
54 1/2" Axle Spacing
Ridewell Suspension
16 1/2" x 7" Drum Brakes
Spring Brakes on Two Axles
Raise & Lower Valve
Manual Ride Height Control
Air Lift on 3rd Axle
Airweigh Quickweigh Scale
255/70R22.5 Tires
Suspension Control in Bolster

A110HDG-SF-18 (Alpha Series Hydraulic Detachable)

Gooseneck	Sub Frame
13 hp Honda in base section/Dual Operation	Covered Boom Trough- bolt on
Paint	HD Wheel Covers Bolt on(54-1/2)
Black	Polished Aluminum Outer Wheels
	3rd tail light package with strobe (no battery)
	Battery back for strobe with 4-way plug for FA
	Prepped for Hyd Flip Axle
	Air Lock Pins for Flip Axle connection

Estimated Weight with options: **23500**

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.