A110HDG-E (Alpha Series Hydraulic Detachable Extendable)

Capacity 110,000 lbs. Open in 2 point rigid load base
Concentrated 110,000 lbs. in 16' Closed
OAL 53'   **OAW** 102"

Gooseneck
10' 5" Hydraulic Detachable
51" 5th Wheel Height
15" King Pin
80" Swing Clearance
5 Position Ride Height Adjustment
3' Flip Neck Connection
3' Flip Neck(116" Swing)
LED Work Light

Sub Frame
14' 1" Long
39" Loaded Deck Height
32 Degree Rear Transition
Open Wheels with Bolsters
Chain Slots in Each Bolster
2 Flat D-Rings at Rear
Flag Holders
1 pair Stake Pockets in Tail Channel
Frame Reinforcement for Single Axle
    Stinger

Main Deck
28' 7" Closed- 50' Open
14" Fabricated I-Beams
20" Loaded Deck Height
6" Ground Clearance
Cross Members ALT on 12" Centers
8 Bent D-Rings per Side
Chain Slots on 24" Centers each side
1 3/4" Apitong Raised Decking-Full Width
Upper Flange Reinforment
Front Flip Ramps
Full Depth Removable Swingout Outriggers
Air Operated Lock Pin, Deck opens every 2'
Toolbox W/Lid In Rear of Male Deck Section

Axles and Suspension
3 - 25,000 lb Axles
54 1/2" Axle Spacing
Ridewell Suspension
16 1/2" x 7" Drum Brakes
Spring Brakes on Two Axles
Raise & Lower Valve
Manual Ride Height Control
Air Lift on 3rd Axle
Airweigh Quickweigh Scale
255/70R22.5 Tires
Suspension Controls in Bolster

Lighting
2 Tail Light Package with Stainless Steel Covers
2 Pr. Side Markers/1 Pr. Mid-Turn on Deck
Grote Ultra Blue-Seal Wire Harness

A110HDG-E (Alpha Series Hydraulic Detachable Extendable)

Gooseneck	Sub Frame
13 hp Honda in base section/Dual Operatio	275/70R22.5 tires Polished Aluminum Outer Wheels
Main Deck	
2 Pr Additional Clerance Lights	3rd tail light package with strobe (no battery Battery back for strobe with 4-way plug Nitrogen Stinger Top Lugs
Paint	
Black	

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.