



Resale Inventory

A028818

VIN: 150650



SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894

Baltimore, MD: 888-601-7500

Concord, NC: 800-438-2250

Delmar, DE: 866-486-1400

Des Moines, IA: 888-673-5011

Elkton, MD: 800-544-7127

Jacksonville, FL: 800-828-3055

Little Rock, AR: 833-424-8944

Portland, ME: 800-325-4253

Raleigh, NC: 833-418-9777

Scranton, PA: 800-569-1400

Springfield, MA: 800-854-5306

Voorhees, NJ: 866-315-0235

Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer



800-232-6535 *FINANCING AVAILABLE

ITEM	DESCRIPTION
TYPE	CHIPS TRAILER
DIMENSIONS	
LENGTH	48'-0" (14630 mm)
WIDTH	102 3/8" (2600 mm)
HEIGHT	13'-6" coupler height: 48"
WEDGE HEIGHT	5" front to rear.
SUB-STRUCTURE	
KING PIN LOCATION	36" from front. (900 mm)
KING PIN	Bolted Jost KZ1008.
COUPLER PLATE	5/16" thick, reinforced, 100 000 psi steel, extends 18" behind king pin, 17 500 kgs capacity.
CROSSMEMBERS	1 beams, 4" @ 3.2 lbs/ft, 80 000 psi steel, 12" center to center, galv.
FLOOR	
FLOOR	Walking Keith 7/32" straight, (2190/2191-1212) 53'-0", 3 1/2" cylindre. Aluminum Keith subdeck #2469 bolted to the galv. crossmembers. SPLASH BEARING HOLDDOWN #2468 full length and T-BLOCK included. Hydraulic oil. Operating temperature -10 to 60 degree Celsius. Rubber flap on bottom of front deflector of walking floor, to avoid material to go behind deflector. ³ Minimum pump data required : ³ Operation pressure : 2800 psi ³ Pump : 30 to 35 gpm ³ Tank : 35 gallons
SUB-STRUCTURE	Galvanized, cross members, "C" frame for tridem and landing gear structure included. (sub-structure galvanized all over except coupler)
FRONT WALL	Type: "G" (5" radius corners).
PANELS	Prepainted white aluminum 0.040 thick.
POSTS	Qty: 6, 4 of 45 mm, aluminum, and 1 each end, integrated to aluminum front corners.
FASTENERS	3/16" aluminum rivets, 4" c/c and 2" c/c on joints.
INTERIOR LINER	See insulation section.
FRONT CORNERS	Double sheeting, aluminum extrusions, unpolished on the outside and aluminum plate inside.
LADDERS	
CAT WALK	Aluminum, 24" wide on front wall, ladder, made of aluminum, roadside included.
FRONT DOOR	One, 25" x 47", panel 3/4" plymetal doors, aluminum prepainted white outside and satin coated steel inside. Including one molded aluminum foot step above connector. For access inside van,
SIDE WALLS	Aluminum.
PANELS	Prepainted white aluminum (.049 thick).
POSTS	Aluminum, 45 mm, 16" c/c, full length.
FASTENERS	3/16" aluminum rivets, 4" c/c and 2" c/c on joints.
INTERIOR LINER	See insulation section.



ITEM	DESCRIPTION
INTERIOR LINER SAMPLE DOOR(S) TOP RAILS BOTTOM RAILS POSTS VENTS	Horizontal. One, aluminum, 10" x 14", installed road side. 5 1/2" high, open top aluminum extrusions, unpolished. 8 7/8" high, aluminum extrusions, unpainted. Posts at 12" c/c for last three side panels. 4 openings 11" x 19" on each side wall with perforated aluminum plate.
REAR END DOOR FRAME DOOR(S) HEADER DOOR PANELS DOOR LOCK(S) HINGES DOOR HOLDBACKS DOOR FRAME BUMPER BUMPER DOOR LOCK(S)	Galvanized steel (G164). Double, swing type, Prepainted aluminum at bottom and 2 blower doors 36 1/2" x 41 1/2" aluminum prepainted at top. Steel formed 4" x 4" x 3/16". Prepainted white aluminum 0.049 thick. Single, Eberhard 1969-U. 3 per door, aluminum. Chain and hook type, including stabilizing rubber stoppers. 1 1/2" x 1 1/2" solid steel push bars. CMVSS 223-RIG approved (in accordance with Canada & USA regulation). Formed steel uprights, 4" x 4" cross bar roll formed tubing at a maximum height of 22" from under tubing to ground. Security type, road side.
ROOF BOWS ROOF BOW (GALV.) TARP SUPPORT NET	Open type. Qty: 3, steel, without offset and hignes. Galvanised. 1/4" aluminum plate at each end of the unit for roll tarp type. None, (NO HOOK FOR NET).
INSULATION FRONT WALL FRONT INTERIOR LINER SIDE WALLS INTERIOR LINER	1 1/2" thick Polyform. Front corners, 1" thick Polyform. Kemlite LTR, .120" thick, fastened with steel pop rivets. 1 1/2" thick Polyform. Kemlite LTR, .120" thick, fastened with steel pop rivets.
ELECTRICAL FRONT CONNECTOR FRONT ADD. CONNECTOR ELECTRICAL SYSTEM MAIN SYSTEM FLASHERS BACK UP LIGHTS TAIL LIGHTS	7 ways (SAE J560), Phillips brand, located center. 7 ways (ISO 3731), for auxiliary functions only. Shock proof lights, polycarbonate lenses, in compliance with CMVSS 108. Grote Ultra Blue LED, Grote sealed beams, tail lights with male pins #53252 (10 diodes), markers #47122,233 (2 1/2") at bottom and each side on top of rear door frame (1"), licence light #60280-M. Sealed beams LED, (Grote #54163), one lamp including side marker and flasher each side at middle point, amber. Sealed beam spot light (Grote #40-4411-00 in a closed back rubber grommet), Qty: 2 Sealed beams, red, (Grote LED #53252). Qty: 1 additionnal each side. (10 diodes) From outside, tail light and flasher, flasher with parking, brake with parking.



ITEM	DESCRIPTION
ADDITIONAL MARKERS	Sealed beams (Grote LED #47122,123), Qty: 10 Located at BOTTOM RAIL 5 PER SIDE .
LANDING GEAR SAND SHOES CRANK SPAN	Holland, Mark V (LGS-3C315), 10" x 11 1/2", solid axles. Road side. 3/16" formed steel, reinforced, galvanized.
BASIC MECHANICAL FRAME	Fixed, for wedge sub-structure, 1/4" thick, 80 000 psi steel, C-shaped frame construction, bolted connection, galv. 72" spread tridem air ride suspension.
MECHANICAL SUSPENSION SPRINGS AXLES SPIDERS CAM SHAFTS TRACK DUST SHIELDS BRAKES BEARINGS SLACK ADJUSTERS SEALS BRAKE CHAMBERS HUBS AND DRUMS RIMS SPACERS TIRES	Hendrickson INTRAAX AAT-30K, spacer, tridem, 72" spread. For axles with bearings HM 518445. Air. LDA, 5 3/4" diameter, 30 000 lbs. capacity. Welded. 10" long, 28 splines with enclosures. 77 1/2". Steel, clamped. 16 1/2" standard, H23 Hendrickson lining. HM 518445. Meritor, automatic, 28 splines. Stemco, "Guardian" type, with "Gearlube" mineral oil, SAE 80W90. T.S.E. brake, "Omni brake" (30-30), (push rod 9 3/4"). KIC, 10 studs disc hubs, balanced drums 101.6 lbs, outboard mount, 285.75mm B.C., single flange nuts. For dual aluminium wheels. Accuride, aluminum, ACCU-LITE,ALU.EXTRA POL., 24.5 x 8.25, disc (10 holes), 285.75mm B.C., single flange nuts. Stock inventory # 231 727. Wheel guard 10 holes. Located between the inside wheel and the drum and between two wheels. Continental, 11 R 24.5 HSR-2 16 ply (43.5")
AIR SYSTEM GLAD HANDS AIR VALVES VALVE DIAGNOSTIC CABLE CONTROL BOX LOAD DEVICE	Fixed, bolted. Rockwell Wabco, ABS, 2 sensors 1 modulator. Manual blow down valve in a control box, WITHOUT auto-reset feature, including Glycerin filled pressure gauge, in P.S.I., to indicate load with a conversion table. Not included with ABS valve. Stainless steel. Air gage, 4" diameter, glycerin filled in P.S.I. to indicate load with a conversion table. Located: roadside rear, 3'-0" up from bottom rail.
ACCESSORIES	



ITEM	DESCRIPTION
REGISTRATION HOLDER	One plastic, Betts-PS-1 or equivalent.
MUD FLAPS	One set, rubber with Manac logo and vertical grooves to reduce spray.
HYDR. CONN. (PRESSURE)	Male, 1" diameter, quick coupling.
HYDR. CONN. (RETURN)	Female, 1" diameter, quick coupling.
EXTRA MUD FLAPS	Qty: 2 set, rubber with Manac logo and vertical grooves to reduce spray. Located at rear of each axles. Hydraulic control for mobil floor with lever extension.
FINISHING	
PAINT	Galv.
UNDERCARRIAGE	Galv.
HUBS	Black.
WHEELS OR RIMS	Natural.
RETROREFLECTIVE TAPES	Conspicuity striping in compliance with CMVSS 108. Gray and red, 2' segments at bottom of each side wall. Fully covers bottom of rear doors and horizontal underride protection bar. 2 segments of gray tape at each upper corner.
ADDITIONAL OPTIONS	
SUB-CONTRACT BY AN OUTSIDER	Tarp install from Granite Tarp Canvas Cover. Aut: 50835.
ANNEX(ES) ATTACHED	Ref 145782.

DISCLAIMER

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.