

HALE

TRAILER

BRAKE & WHEEL



A029324
VIN: 941036

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894	Little Rock, AR: 833-424-8944
Baltimore, MD: 888-601-7500	Portland, ME: 800-325-4253
Concord, NC: 800-438-2250	Raleigh, NC: 833-418-9777
Delmar, DE: 866-486-1400	Scranton, PA: 800-569-1400
Des Moines, IA: 888-673-5011	Springfield, MA: 800-854-5306
Elkton, MD: 800-544-7127	Voorhees, NJ: 866-315-0235
Jacksonville, FL: 800-828-3055	Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

Quantity	Product ID	Description
1.00	ART-60-402	<p>EA NEW ACE ROLL OFF TRAILER - ART-60-402</p> <p>Overall Length: 40' 11"</p> <p>Container Frame Length: 40'</p> <p>Kingpin to Last Axle: 34'</p> <p>Rated 60,000 lbs. Lift Capacity</p> <p>Container Size Range- 10'-40' Outside Rail Containers</p> <p>MAIN FRAME:</p> <p>12"X 4"X 1/4" Rectangular Tubing</p> <p>12"X 4" Cross Members for Main Frame</p> <p>Top Wrap: 1/2" X 4" Flat Bar Wear Pad</p> <p>Bottom Wrap: 3/4" x 4" Flat Bar</p> <p>1/4" Hollow Truss Mounted Below Main Frame with 1/2" X4"</p> <p>Bottom Wrap</p> <p>(2) 1 1/4" Fixed Stops at Front of Trailer</p> <p>(14) 3 1/2" Rollers Welded to Outside Frame</p> <p>3/4" King Pin Plate with 3/4" Plate Supports & 2" Round Bar Stiffener</p> <p>STABILIZER FRAME:</p> <p>4"X4"X 1/4" Tube with 4"x4"x3/8" Angle Wrap</p> <p>Hinges: 2" Round Bar</p> <p>28"x16"x5/8" Draft Arm Support Plates</p> <p>HYDRAULICS:</p> <p>(2) 8.5"- 4 Stage Telescopic Main Lift Cylinder 133,000 lbs. @ 2,400 PSI</p> <p>(2) Ace Independent Reeves: 3 1/2 Rod 7" Bore Reeving Cylinder 88,000 lbs. ea.</p> <p>Directional Valve with Pressure Gauges and Adjustable PSI – Set to 2,450 PSI</p> <p>Hoses: 3/4" 3000 PSI Hoses with Nylon Covering</p> <p>Hydraulic Pipes: 3/4" Steel Pipe</p> <p>Standard JIC Fitting on All Hydraulics</p> <p>NO HYDRAULICS IN REAR OF TRAILER</p> <p>CABLE AND AFFILIATED COMPONENTS:</p> <p>Cable-7/8" IWRC Cable, (4) Cable Clamps, Cable Button with Cast Ring</p> <p>Pulleys: 10" Sheave with 2.5" Pin (Qty 3)</p> <p>Pulley Block - Independent (2)</p> <p>Independent Pulley Track</p> <p>RUNNING GEAR:</p> <p>H900 50,000 lbs. Spring Single Point Suspension (Tandem)</p>

Quantity	Product ID	Description
		Suspension Hanger: 21" Fabricated I-Beam (2) 25,000 lbs. 5" Round Axles Brake Control: Spring Loaded 16" x7.5" ABS: 2S1M 10 Hole Uni-Mount Hubs & Drums 10 Hole Uni-Mount Rims w/11R22.5 Tires Fenders- Rubber 2-Ply Ace Logo Rubber Mud Flap with Hook 2-Speed Landing Gear 120K lbs. LIGHTING & SAFETY All L.E.D Lights All Lights Meet DOT #108 Lights & Harness- Truck Lite Body Hoist Up Alarm- LED Strobe ICC REGULATED BUMPER- AIR ACTUATED Meets FMCSA 49 CFR § 393.86 (4) Nylon Tie Down Strap – More can be added* PAINT Cleaned, Primed, Painted Industrial Epoxy (Black) WARRANTY- In Years (5) On Main Frame – Excluded Rollers and Greaseable Items (1) All Hydraulic Components (1) on All Items Manufactured by Ace Axles & Suspension are subject to manufacturer discretion Main Frame Assy, Standard Tandem Finishing Stages, 40FT Tandem EA Removable Stop Set Driver & Passenger 3/4 Thk Stop For proper weight distribution on containers shorter than trailers overall length
1.00	80-3004	EA Tarp System, Roll-Off Complete 40' Hyd
1.00	252-3001-40H	EA Front Work Lights Installed
1.00	115-1003-I	

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.