

HALE TRAILER BRAKE & WHEEL



Resale Inventory

A029574

VIN: 562770

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer



800-232-6535 *FINANCING AVAILABLE

Revolution 52 Alum Flat 53' Rear Axle Slide (Model: HAR522RSA)

Length / Width: 53 feet x 102 inches

Suspension Type: Rear axle slide; This Trailer Design Does NOT Meet Proposed GHG2 Compliance Requirements

Frame Rating: 80,000 lbs distributed - 52,000 lbs concentrated in 4 feet- GAWR and tire ratings determine legal payloads

Flooring: Knurled extruded 3-1/8 aluminum, **StirLITE Friction Stir Welded Floor** with 2 wood nailer strips; Heavy wall extrusions in single coil area; Heavy wall extrusion at rear

Side Rails: Exclusive **Revolutionary RASR Rail Technology** -- one piece routed aluminum designed for strength and impact

Stationary Chain Cargo Tie Downs: 17 pair - recessed in siderails

Stake Pockets: Routed Aluminum on 24 inch centers (2 load securement openings in between stake pockets)

Rubrail: Integrated with side rail

Main Beams: Extruded aluminum - 8.25 inch flange

Kingpin: 30 inches

Loaded Fifth Wheel Height: 49 inches

Landing Gear: Jost AX100G19 **ALUMILIGHT Aluminum Landing Gear** with forward & rear bracing

Bulkheads:None standard

Number of Axles: 2

Axle Spindle:Tapered

Brakes:Spring brakes, auto slacks, Aluminum air tank

Air Line Filters:(2) Meritor In-line type installed

ABS: 4S/2M - no cable or tool

Axle Spread: 122 inches open - 54 inches closed - Meets California, Canadian RTAC and BC dimensional specifications in closed

Hub and Drums:10-hole hub-piloted with outboard cast drums - **STANDARD**

Wheel Ends: Grease in hubs - *** 5-year wheel end warranty ***

Wheels:22.5 x 8.25 aluminum LVL One buffed wheels

Tires:295/75R 22.5 14PR OEM standard tires

Tire Inflation System:None standard

Suspension Detail: Hendrickson air ride

Air Assist Slide Box Pins:Standard mount of controls on slider frame

Auto Glad Hand Dump:Installed

Electric Dump Valve:Wired to 7-way auxiliary socket to dump rear axle

Front Corners: Tapered

Electrical System: LED: 5 Lights/Side; Rear with 3 4-inch Round Lights/Side, 3 Round Lights Center Cluster

Other Electrical Specifications: 4 way socket on rear with one hot/one ground pin for wide load and strobe light connections

Paint:Black urethane on steel parts with Revolution decals - **STANDARD**

Conspicuity Tape: Per NHTSA specs - installed in recess on rubrails

Bumper: Bolt-On; Meets underdrive requirements

Mudflaps:1 set OEM standard behind rear axle only

Spare Tire Carrier:None standard

Winch Track: Dual full-length integrated aluminum -- double L design

Sliding Winches:12 standard; 6 each side; sliding rope hook/ winch strap hook retainers - **STANDARD**

27' Winch Straps:None standard

30' Winch Straps:None standard

Sliding J-Hook for Ring vs. Flat Hook on 4" Strap:None standard

Dock Bumpers: 1 pair rubber on rear

Hubodometer:None standard

Registration Holder:Install registration holder - OEM standard

Tool Box:1 aluminum double door box - 24 inches x 24 inches x 60 inches - installed Curb Side; includes 4 sliding

VIN Plate: Bilingual US/Canadian VIN plate

Please Note: Price includes commodity surcharges

Unit Numbers & Decals: Not available

***Aero Conestoga**

DISCLAIMER

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.