

# HALE

## TRAILER

### BRAKE & WHEEL



**A029706**  
**VIN: 575908**

#### SALES | RENTALS | PARTS | SERVICE

|                                       |                                      |
|---------------------------------------|--------------------------------------|
| <b>Allentown, PA:</b> 800-383-8894    | <b>Little Rock, AR:</b> 833-424-8944 |
| <b>Baltimore, MD:</b> 888-601-7500    | <b>Portland, ME:</b> 800-325-4253    |
| <b>Concord, NC:</b> 800-438-2250      | <b>Raleigh, NC:</b> 833-418-9777     |
| <b>Delmar, DE:</b> 866-486-1400       | <b>Scranton, PA:</b> 800-569-1400    |
| <b>Des Moines, IA:</b> 888-673-5011   | <b>Springfield, MA:</b> 800-854-5306 |
| <b>Elkton, MD:</b> 800-544-7127       | <b>Voorhees, NJ:</b> 866-315-0235    |
| <b>Jacksonville, FL:</b> 800-828-3055 | <b>Walpole, MA:</b> 800-854-5310     |

haletrailer.com | @haletrailer

**800-232-6535** \*FINANCING AVAILABLE

| Magnitude 55HFLD 60 Air Tridem (Flat Level Deck) (Model: MAGNITUDE55H)   |                          |
|--|--------------------------|
|  | Est. Wt.: 22,534# +/- 3% |
| <b>Capacity:</b> 55 tons in 12-foot length with 4 axle close coupled or single axle stinger - GAWR and tire ratings determine legal payloads                           |                          |
| <b>Load Base:</b> 12-foot rigid 2-point load centered in deck area   |                          |
| <b>Framework:</b> All main longitudinal members fabricated with 100,000# minimum yield steel flanges with 50,000# webs   |                          |
| <b>Compatibility:</b> Designed to accept 55/60 rear axle, spreader and/or 23 inch flip box -   |                          |
| <b>Gooseneck Design:</b> Hydraulic removable non-ground bearing design   |                          |
| <b>Loaded Fifth Wheel Height:</b> 50 inches nominal with 5 ride height positions   |                          |
| <b>Swing Radius:</b> 102 inches (11 feet 11 inches overall gooseneck length) - NGB   |                          |
| <b>Alternate Kingpin:</b> Dual kingpin at 81 inch and 102 inch radius  |                          |
| <b>Flip Box:</b> None  |                          |
| <b>Power Source:</b> Set up for wet line operation   |                          |
| <b>Electrical Receptacle:</b> J560 7-pin connector   |                          |
| <b>Deck Width:</b> 8 feet 6 inches overall (unless optional deck width is selected)  |                          |
| <b>Deck Length:</b> Flat Level Deck (FLD) design - 25 feet clear deck length   |                          |
| <b>Loaded Deck Height:</b> 22 inches with 6 inches ground clearance  |                          |
| <b>Flooring:</b> 2 inch nominal wood - side rails only   |                          |
| <b>Front Ramps:</b> None, front of deck sloped top down to assist in loading with traction cleats  |                          |
| <b>Front Bogie Ramp:</b> Included  |                          |
| <b>Extension Brackets:</b> 12 pair - 24 total removable swing type, 1 pair - 2 total heavy duty removable hook-on type (26 swing type, 1 hook-on type on 27 foot deck) |                          |
| <b>Deck to Bogie Connection:</b> Fixed   |                          |
| <b>Tool Box:</b> 2 Fully covered trays in front of deck between mainbeams with lockable covers.  |                          |
| <b>Crossmembers:</b> Recess last 3 crossmembers in deck  |                          |
| <b>Number of Axles:</b> 3 axles  |                          |
| <b>Axle Capacity:</b> 25,000 lb. nominal capacity per axle NOTE: GAWR determined by suspension type, brakes, tires and other components.                               |                          |
| <b>Axle Spread:</b> 60 inches (between axles) **See Deck Length Notes  |                          |
| <b>Dust Shields:</b> None  |                          |
| <b>Brakes:</b> 16.5 inches x 7 inches with 5.5 inches autoslacks - heavy duty brake drums - outboard mount   |                          |
| <b>Suspension:</b> Air ride  |                          |
| <b>First Axle Lift:</b> None   |                          |
| <b>Third Axle Lift:</b> Air lift   |                          |
| <b>Tires:</b> 275/70R 22.5 OEM Standard  |                          |
| <b>Wheels:</b> 8.25 x 22.5 LVL one buffed wheels REV 1 04-25-18  |                          |
| <b>Bolsters:</b> Recessed load bearing between all axles and rear of last axle   |                          |
| <b>Covered Rear Bogie:</b> None  |                          |
| <b>Rear Bogie Height:</b> 40 7/8 inches to top flange - 36 5/8 inches to top of bolsters   |                          |
| <b>Boom Trough:</b> V-style boom trough with bolt-in V pan   |                          |
| <b>Mechanical Ride Height Control:</b> Mechanical ride height control valve (Whittle Style)  |                          |
| <b>Manual Dump Valve:</b> Manual Dump Valve (Push Pull)  |                          |
| <b>Bumper:</b> Heavy duty V-style rear bumper  |                          |
| <b>Width:</b> 8 feet 6 inches  |                          |
| <b>Spreader:</b> None  |                          |
| <b>Flip Axle:</b> None   |                          |

|  |  |
|--|--|
| <b>Dust Shields on Flip Axle: None</b>   |  |
| <b>Electrical System:</b> DOT sealed beam and harness with LED lights and 4 inch flush mounted battery powered amber strobes <b>Additional Pig tail in Rear Ctr for Auxiliary Strobe (Hot wire) REV 2 05-08-18</b> |  |
| <b>Paint: United Blue</b>  |  |
| <b>Lash Rings:</b> 14 pair - 28 total  |  |
| <b>Flag Holders:</b> Flag holders - 1 pair located at front of deck and on rear bumper   |  |
| <b>Accent Package: None</b>  |  |
| <b>Liquid Filled Gauge: None</b>   |  |
| <b>VIN Plate:</b> Bilingual VIN plate  |  |
| <b>Registration/Document Holder:</b> Install registration/document holder  |  |
| <b>Please Note:</b> Price includes commodity surcharges  |  |
| <b>Commercial Terms:</b> Ex Works- Springville, AL, USA  |  |
| <b>Additional Options:</b> <b>Cat's Eye installed on 3 axles REV 1 04-25-18</b>  |  |
| <b>Air Weigh Scale installed Change to 3/4" Hydraulic Fittings on front of trailer REV 1 04-25-18</b>  |  |

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.