



Resale Inventory

A029810

VIN: 215347



SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894

Little Rock, AR: 833-424-8944

Baltimore, MD: 888-601-7500

Portland, ME: 800-325-4253

Concord, NC: 800-438-2250

Raleigh, NC: 833-418-9777

Delmar, DE: 866-486-1400

Scranton, PA: 800-569-1400

Des Moines, IA: 888-673-5011

Springfield, MA: 800-854-5306

Elkton, MD: 800-544-7127

Voorhees, NJ: 866-315-0235

Jacksonville, FL: 800-828-3055

Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer



800-232-6535 *FINANCING AVAILABLE

ITEM	DESCRIPTION
TYPE	SEMI-TRAILER, TELESCOPIC STEEL DROP PLATFORM.
DIMENSIONS	
LENGTH	53'-0" closed.
LENGTH	71'-0 opened.
OPENINGS	5'-0" increments in closed position.
WIDTH	102", 97" between side rails.
HEIGHT	Floor, approximately 61" high at front and 34" at the bumper.
DROP HEIGHT	25", located at 10'-6" from front.
COUPLING	
COUPLER PLATE	3/8", plug welded structure.
KING PIN LOCATION	18" from front.
COUPLER HEIGHT	49".
STRUCTURE	Frame with "CAMBER".
FLANGES	Female section, exterior, 3/8" x 6", 100 000 psi steel, 24" high.
FLANGES	Male section (interior), 3/4" x 6", 60 000 psi steel, 17 5/8" high and 16 1/2" above suspension.
WEB	1/4" plate in king pin area and the remaining in 3/16", 80 000 psi steel.
GOOSENECK	12 1/4" high, 48" straight behind king pin.
CROSSMEMBERS	I beams, 4" @ 3.64 lbs/ft, 80 000 psi steel, galvanized, 12" c/c.
FLOOR	Apitong or equivalent, 1 1/8" thick shiplap finished, no preservative.
FLOOR FASTENING	Two screws per board at each crossmember.
SIDE RAILS	Galvanized 10 gauge shaped 80 000 psi steel, 5" width x 5 11/16" high. Galvanized front and rear bolted sills.
SIDE BOXES	3/16" steel plate, 1 5/8" x 3 5/8" interior, 4" high. (USA Dimensions).
RUB RAILS	3/8" x 2 1/2" shaped steel.
CORNERS	Bevelled.
FENDERS	Over tires at rear, checker plate 1/8".
DIAGONAL BRACES	2" x 2" x 3/16" angles, welded in web and to a crossmember, located each side.
LOCKS	Air operated with a third glad hand at front.
ROLLERS	4, 2 on female sections of frames and 2 on male sections.
ENDS	
FRONT RAIL	9 gauge formed steel. Galvanised
BUMPER	CMVSS 223-RIG approved (in accordance with Canada & USA regulations). Uprights integrated with frames, 4" x 4" cross bar roll formed tubing at a maximum height of 22" from under tubing to ground.
POCKETS	2 bolted galvanised pockets at front for removable headboard.
REAR RAIL	11" high, 9 gauge formed steel, including 3 boxes at rear and 3/8" x 2 1/2" shaped steel.
ELECTRICAL	
FRONT CONNECTOR	7 way (SAE J560), Phillips brand.



ITEM	DESCRIPTION
ELECTRICAL SYSTEM	Shock proof lights, polycarbonate lenses, in compliance with CMVSS 108.
MAIN SYSTEM	Grote Ultra Blue LED, sealed beams Grote, tail lights with male pins #54332, markers #47122, 47233 (2 1/2" dia.), licence light #60280-M, with vapor proof junction box Truck-Lite #50400.
TURN SIGNAL	Sealed beams LED, one lamp including side marker and flasher, each side at middle point, amber.
REAR ADD. CONNECTOR	4 way.
STROBE LIGHTS	(2), installed (1) on each side, (Grote 77353 amber) (rubber grommet)
SWITCH	Sealed, to activate strobe lights, installed *** in the control box ***.
LANDING GEAR	Holland, Mark V (LGS-4F115), with mounting plate, galvanized.
SAND SHOES	10" x 11 1/2".
CRANK	Road side.
BOGIE	
BASIC SUSPENSION	
BOGIE	Fixed.
SUSPENSION	Hendrickson HT-250US (6.5), tandem, 60" spread. *** CAL LEGAL W/REAR AXLE LIFTED ***
LIFT DEVICE	Hendrickson HT-250US (6.5) with Manac center lift. Located at 60" rear of tandem. *** Controlled manually *** *** Only 1 1/2" of clearance from the ground if used at rear. *** *** NO WARRANTY ON THE TIRES NOR GROUND AXLES, (FLAT SPOT) ***
U-BOLTS	With nuts at bottom.
SPRINGS	Air.
AXLE(S)	AXN, TA250T, 20 000 lbs. capacity.
SPIDERS	Welded.
CAM SHAFTS	28 splines.
TRACK	77 1/2".
DUST SHIELDS	None.
BRAKES	12 1/4" standard, AXN R23 lining.
BEARINGS	HM 218248 and HM 212049.
SLACK ADJUSTERS	Haldex S-ABA, automatic, curved, 28 splines, (6").
SEALS	Stemco, "Platinum Performance System". Including "Guardian" seals, Pro-Torq spindle nuts, Integrated sentinel hub caps with Synthetic oil, Mobil Delvac 75W-90. (3 year warranty by Stemco for parts only).
BRAKE CHAMBERS	T.S.E. brake, "Omnibrake" (30-30), long stroke. (4 years warranty by T.S.E. for parts only).
HUBS AND DRUMS	WEBB, 8 studs disc hubs, drums 93 lbs, outboard mount, 275mm B.C., single flange nuts. For dual steel wheels or single wheels.
RIMS	17.5 x 6.75, disc (8 holes), 275mm B.C., single flange nuts, 4 hand holes.
TIRES	Continental, 235/75 R 17.5 HTL-2 ECO-PLUS 18 ply (31.6")
ALIGNMENT	Laser, 3 axles (tridem).
AIR SYSTEM	
GLAD HANDS	Fixed.



ITEM	DESCRIPTION
AIR VALVES VALVE(S) VALVE VALVE	Meritor Wabco, ABS, 2 sensors 1 modulator. Fast-brake kit. Quick and brake release valves on air lift. Manual blow down valve in a control box, with auto-reset feature, including Glycerin filled pressure gauge, in P.S.I., to indicate load with a conversion table.
CONTROL BOX	*** Stainless steel. ***
ACCESSORIES REGISTRATION HOLDER WINCHES	One plastic, Betts-PS-1 or equivalent. Qty: 12, KINEDYNE #1020G, Galvanized slider (5 7/8"). **Stock inventory 363-135**
SLIDING TRACK MUD FLAPS EXTRA MUD FLAPS	Full length, "LL" extruded aluminum, road side. One set, rubber with Manac logo and vertical grooves to reduce spray. Qty: 2, rubber. Located: 1 at front of landing gear in between main frames, to protect roller and 1 at front of suspension in between main frames, to protect air boosters.
FINISHING PAINT	Trailer prepared & shipped to be galvanized. No paint & no primer on the trailer. (extendable drop deck trailer only to be galvanized)
AXLE(S) PAINTED	One coat of epoxy primer and one acrylic urethane top coats, Color: GREY metallic, code: Q37-939514. Axles (wheel end) included.
HUBS WHEELS OR RIMS RETROREFLECTIVE TAPES	GREY metallic, code: Q37-939514. Powder top coat white. Conspicuity striping in compliance with CMVSS 108. Gray and red, each side, fully covers rear sill and horizontal underride protection bar.
PAINT	Vin plate to be made of metal. Pre-drill the web prior to galvanizing
ADDITIONAL OPTIONS R	Ref: 211714 Due to the deep backlogs, material/component availability and price fluctuation, Manac reserves the right to adjust the price based on these instabilities. If needed, Manac will contact the dealer or customer a minimum of 3 months prior to assembly with revised pricing or a change in components.
CONFORMITY	This semi-trailer does not comply with GHG regulations. Should GHG regulations come into force prior to the production of the trailer(s), Manac will have the obligation to ensure the trailer(s) produced meet minimum GHG guidelines. Any modifications required to meet the GHG regulations will be added to the initial purchase price and charged back to the customer.

DISCLAIMER

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.