



A029867
VIN: 180093

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

Product
Hauled: Water

Barrel Description

Model	SRJ3 6250-1 T304, Stainless steel, Round, Jacketed, 3-A sanitary trailer
Code	3A Sanitary Built as Non-code upgradable to 3A.
Capacity	6250 gallons (shell full)
Compartments	One
Shape	Round
Shell Material	T304 Stainless steel, #4 finish, 12 gauge barrel. Two piece barrel with one circumferential weld.
Head Material	T304 Stainless steel, #4 finish, 12 gauge
Operating Pressure	Atmospheric
Design Temperature	212 Degrees F. (TEMPERATURE RATING OF 212 DEGREE F. WITH STANDARD INSULATION. THE USE OF OTHER INSULATIONS MAY DECREASE THE MAXIMUM TEMPERATURE RATING FOR THIS TRAILER. SEE INSULATION FOR MAXIMUM TEMPERATURE RATING CHANGE.)
Overall Length	42' 6"
Product	Various; to be compatible with the materials of construction.

Other Barrel Information

Heat	None
Plumbing	None
Intransit	None
Weld finish	W-5 inside

Construction

Rings	Stainless steel channel
Longerons	12 gauge Stainless steel channel
Frame	Stainless steel, modified angle.
Dam	None
Dam Drains	None
Overturn Protection	None
Cleanout overturns	None
Manhole	Polar 19" stainless steel lid with dust cover, 4 hold-down. Stainless steel sanitary deck around manhole with dust cover vent under hinge.
Gasket	Black gasket in cover..
Insulation	3/4" Polyurethane under 3" Polystyrene, R 18.5, 212 DEG F. max
Thermometer	None
Jacketing	22 gauge stainless steel bright finish
Jacket heads	18 gauge stainless steel #3 finish jacket heads.
* Underlayment	Aluminum .090" underlayment, 24" wide x full length
Static cable	No static cables installed.

Hose Carriers

* Hose Carrier	Aluminum tube 8" diameter x 21' long
* Hose Carrier	8" aluminum door, at rear
* Carrier Location	Mounted curbside rear

Lights and Wiring

Lights	12-volt, Truck-Lite grommet mount LED lamp system complying to FMVSS. Combination center marker / turn signals, one each side.
Wiring	Plug-in style harness system.
Rear Lights	Enclosed in stainless steel light boxes
Nose box	Standard 7 way, J560 receptacle without circuit breakers.
Gladhands	Gladhand, Phillips, Quick Release

Undercarriage

Upper 5th Wheel	5/16" Standard duty upper coupler with Heavy duty double hubbed kingpin.
Paint	Fifth wheel plate painted black.

Landing Gear	Jost A440, 2-speed, load bearing, telescopic, with swivel type sand shoe.
* Landing Gear	Additional stainless steel bracing mounted to the front of the support legs.
Frame	Stainless steel construction
Bracing	Stainless steel, with cross brace.
Crank location	Crank handle located on roadside
Tire carrier	None.
* Suspension	Hendrickson INTRAAX AAT25K tandem axle suspension set with 5.75" diameter Hendrickson integrated axles. Axle spacing to be determined by scale. Axle plate stamped for 23,000 gawr
* Suspension	3/16" Stainless steel subframe extended to the rear 12"
Dump valve	Hendrickson AK-54 automatic dump valve. System exhausts the air from the air bags when the glad-hands are disconnected or when the parking brake is activated and automatically refills when glad-hands are reconnected.
Lift Axle Control	None - no auto lift controls included
Hangers	Stainless Steel weld on hangers with soft coat applied to axle and trailing arm.
Subframe	3/16" Stainless steel subframe, 38" wide with stainless fender supports.
* Bumper	Stainless underride protection. Compliant with both FMVSS and CMVSS, including certification label as required.
Beam	Straight axle beam
Track	Axle track, 71.5"
Hub & drums	Hendrickson 5 year warranty, Ready to roll with Duralite hubs, cast drums and semi-fluid grease. OEM slack adjusters, seals, brake chambers and brake lining.
Anti-lock / Roll stability	Wabco 4S/2M with "RSS-Plus" roll stability support system for tandem (2) axle airride suspension set.
Air system	One (1) aluminum tank system. 2850 cu. in. meeting FMVSS 121 D.O.T. specifications.
Emission Compliance	NA
Wheels	Original Equipment Manufacturer, 22.5 X 8.25 Aluminum polished wheels
Tires	Original Equipment Manufacturer, 11R-22.5, Load Range G 14 Ply.
* Tire pressure system	Axle prep for Hendrickson TIREMAAX Pro or TANK Ai tire inflation systems.
Front	Aluminum, single contour, ribbed, front fender, each side.

Rear		Aluminum, double contour, ribbed, rear fender, each side.
Mud flaps		White, anti-sail and anti-spray with Polar logo, mounted front and rear.
Valving and Piping		
* Seal provisions		Seal provisions on all openings
* Sump		6" flanged sump out rear head
Discharge location		Rear of trailer.
* Outlet valve		Betts 6" T316 stainless steel sliding gate valve, SV916SSM-006, flange x thread, with handle directed to rear.
* Adaptor		6" stainless steel male adaptor, female npt.
* Adaptor		6" stainless steel dust cap
Venting and cleanouts		
* Vacuum	3	Run-O-Vent in manhole cover Installed in the manhole cover.
Cleanouts		None
* Cleanouts		3" stainless steel ACME threaded ferrule with cap, nut and dust cover Installed forward of the manhole.
Walkway and Ladder		
Top center		None
Ladder		Two Stainless steel tubular with grip steps and dual large step, bolt on.
Ladder Location		One mounted curbside and roadside, near center of trailer.
Cabinet		
Cabinet		None. No Cabinet installed.
Pump System		
Hydraulic Lines		None
Meter		None
Meter Installation		None
TANK Ai™		
IntelliSECURE		TANK Ai™ - None installed
Miscellaneous		
Decals		Standard warning and safety package. Decals in English.
Conspicuity Tape		Discontinuous tape

Customer Logo	None
Document holder	Truck Lite 97960 Certificate Holder. Install in standard location unless otherwise specified.
Calibration	Computer generated theoretical calibration chart, 1/4" increments. Based on innage.
Paint	None. No paint or primer installed on trailer.
Passivate	None
Warranty	Polar standard two year.
Tests	Standard testing.
Drawings	None.

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.