



A030184
VIN: 053233

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894

Little Rock, AR: 833-424-8944

Baltimore, MD: 888-601-7500

Portland, ME: 800-325-4253

Concord, NC: 800-438-2250

Raleigh, NC: 833-418-9777

Delmar, DE: 866-486-1400

Scranton, PA: 800-569-1400

Des Moines, IA: 888-673-5011

Springfield, MA: 800-854-5306

Elkton, MD: 800-544-7127

Voorhees, NJ: 866-315-0235

Jacksonville, FL: 800-828-3055

Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer



800-232-6535 *FINANCING AVAILABLE

BODY SPECIFICATIONS

Design Type:	Genesis Design - INBOARD
Length:	30'-0"
Width:	96"
Overall Side Height:	66" (64"+2")
Aluminum Height:	64"
Top Rail Type:	9" DUMP
Top Options:	3/8" X 3" X 3" ANGLE - ABOVE BH AND GATE
Side Material:	.100 Wall: 4' -Front .140 Wall: 20' -Middle .180 Wall: 6' -Rear
Rear Post:	STANDARD - INBOARD
Floor Design:	SHEET AND CROSSMEMBER
Body Package Options:	NONE
Body Latch:	NONE
Body Vibrator:	NONE
Doghouse Width:	14" WIDE - HOIST ACCESS INSIDE BODY (DO NOT CUT FRONT OF BULKHEAD)
Floor Thickness:	1/4" FULL LENGTH
Floor Overlay:	NONE
Floor Options:	NONE
Floor Cleanout:	1/4" x 5" STANDARD BOTTOM RAIL
Cleanout Overlay:	NONE
Crossmember Spacing:	10" (13 1/2" CENTER TO CENTER)
Crossmember Type:	STANDARD
Body Wear Pads:	QUIET RIDE PADS
Floor Stringers:	NONE
Longitudinals:	STUBBED
Rear Hinge Shoes:	SINGLE - EACH SIDE
Hinge Shoe Lubrication:	GREASE ZERK IN SHOES
Body Guides:	THREE PAIR
Spray Skirts:	STANDARD TRANSITION SKIRT
Body Fenders at Base of Bulkhead:	SQUARED OFF
Apron:	NONE
Flaps:	10" FLAP FRONT, 40" SOLID ALUM FLAP W/ 3" LIPS AHEAD AXLE #1, 42" FLAP BEHIND REAR AXLE
Chassis Flaps:	ACROSS REAR OF CHASSIS
Option	NONE
Bulkhead Design:	STANDARD
Bulkhead Material:	3/16"
Doghouse Width:	14" WIDE - HOIST ACCESS INSIDE BODY (DO NOT CUT FRONT OF BULKHEAD)
Doghouse Side Thickness:	1/4"
Slope Plates at Inside Bottom Front:	17" PLATES
BH Inside Joint Reinforcement:	NONE
Tarp Hooks:	NONE
Ladders Out - Front:	NONE
Ladders In - Front	NONE
Shovel Hanger:	(2) SHOVEL HANGERS - ONE EACH SIDE OF DOGHOUSE - INSIDE OF BODY
Bulkhead Equipment:	NONE



TAILGATE SPECIFICATIONS

Tailgate Height:	FULL
Tailgate Slope:	NONE
Rear Post:	STANDARD - INBOARD
Tailgate Material:	.140 GENESIS PANEL
Top Hinges:	OVERSLUNG
Tailgate Powerlift:	NOT APPLICABLE
Sideswing:	SIDE SWING W/ GROUND CONTROL
Bottom Latch Trip:	AIR CYLINDER
Mid-Gate Hook Latch:	NONE
Tailgate Seal:	RUBBER
Winder Latches:	ONE EACH SIDE
Coal Door:	NO COAL DOOR
Coal Chute:	NONE
Spreader Chains:	NONE
Gate Latch Bar Grease:	STANDARD BEARING BLOCK GREASE ZERKS
Tarp Hooks:	NONE
Marker Lights:	6 BOTTOM - FORWARD-MOST PAIR TO BE LOCATED IN SIDE FENDER. ADD'L PAIR TO BE INSTALLED ON OUTSIDE FOWARD FACE OF BODY FENDER
Side Lamp Type:	ALL CLEAR LENS - TRUCKLITE LED GROMMET MOUNT
Mid-Turn Signal:	BELOW RAIL - 2" IN FROM EDGE - PART # TBD - PER ENGINEERING - CUSTOMER SUPPLIED LIGHTS
Rear Body Light Panel	ALL CLEAR LENS - FULL WIDTH - 000 000 000 - Center ID Size: 4" - TRUCKLITE LED GROMMET MOUNT
Backup Lights:	NONE - NOT APPLICABLE
Apron:	NONE
Rear Post Lights:	NONE
Tarp Bars:	NONE
Tarp Hooks:	NONE
# of Bow Holders:	NONE
Tarp Bow Design/Location:	NONE
Tarp Bow Qty:	NONE
Tarp Bow Rise:	NONE
Tarp Wiring:	NONE
Splash Shields:	NONE
Ladders Out - Front:	NONE
Ladders Out - Rear	DRIVER SIDE
Ladders In - Front	NONE
Ladders In - Rear:	ONE DRIVER SIDE (3" X 3" ANGLE)
Shovel Hanger:	(2) SHOVEL HANGERS - ONE EACH SIDE OF DOGHOUSE - INSIDE OF BODY
Registration Holder:	NONE
Body Fenders at Base of Bulkhead:	SQUARED OFF
Body Latch:	NONE
Body Vibrator:	NONE
Wood Color:	N/A
Tarp Bar Tape:	NONE
Top Rail Tape:	NONE
Body Overhang:	6" OVERHANG



CHASSIS SPECIFICATIONS

Chassis Length	29' 6"
Chassis Width:	96" (71 1/2" TRACK AXLES)
Number of Axles:	2
Chassis Beam Material:	17" ALUMINUM - BODY WEAR PADS: QUIET RIDE PADS
King Pin Setting:	18"
Rear Axle Setting:	21 1/2"
Body Overhang:	6" OVERHANG
K/P To Rear Axle:	314.5"
Kingpin to Axle 1:	262.5"
5th Wheel Height:	51
Rear Suspension Ride Height:	17"
Draft from Front to Rear:	
Neck Bracing:	NONE
5th Wheel Plate:	3/8" WITH 3/8" X 3" X 7" HOIST MOUNT
Special Frame Bracing at Suspension:	NONE
Chassis Rear Crossmember:	TAPERED
Chassis Lights:	NONE
Rear Hinge Shoes:	SINGLE - EACH SIDE
Rear Hinge Pin:	HOLLOW
Hinge Shoe Grease:	GREASE ZERK IN SHOES
Gate Latch Bar Grease:	STANDARD BEARING BLOCK GREASE ZERKS
Hoist:	8-5-250 CUSTOM
Hoist Pin Grease:	REMOTE GREASE ZERK FROM TOP PIN TO BOTTOM DRIVER SIDE FACING FORWARD

AXLE - 1

Axle 1 Suspension:	AAL30K - UBL LIFT HENDRICKSON (APPROX. 5" GROUND CLEARANCE)	Brake Lining:	EXTENDED LIFE
Dist. to Prev. Axle:	52 Inches	Axle 1 Brake Drums:	CAST
Axle 1 Spindle type:	TP SPINDLES (UP TO 23,000# GAWR)	Axle 1 Wheel type:	8.25 x 24.5 BUFF IN - POLISHED OUT
Axle 1 Hubs:	10 STUD - STEEL	Axle 1 Tire Selection:	11R 24.5 -16 PLY GENERAL S371 LRH
Axle 1 Brake Type:	DRUM - CAM ACTUATED	Qty of Tires/Wheels:	FOUR TIRES
Brake Shoe Size:	16-1/2" x 7"	Suspension Hangers:	GALVANIZED HANGERS (LIFTABLE INTRAAX SUSPENSION)

REAR AXLE - 2

Suspension:	AAT30K HENDRICKSON	Brake Lining:	EXTENDED LIFE
Rear Axle Ride Height:	17"	Brake Drums:	CAST
Rear Axle Type:	AIR - NON-LIFTABLE	Wheel Selection:	8.25 x 24.5 BUFF IN - POLISHED OUT
Spindle Type:	TP SPINDLES (UP TO 23,000# GAWR)	Tire Selection:	11R 24.5 -16 PLY GENERAL S371 LRH
Hubs:	10 STUD - STEEL	Qty Wheels/Tires:	FOUR TIRES
Brake Type:	DRUM - CAM ACTUATED	Rear Axle Susp. Hanger:	GALVANIZED HANGERS (NON-LIFTABLE INTRAAX SUSPENSION)
Brake Size:	16-1/2" x 7"		

Dust Shields:	OEM
Brake Chambers:	OEM
Cam Covers:	NONE
Slack Adjusters:	OEM
Chain - Strap Stops:	NONE
Suspension Scale:	NONE
Tire Inflation System:	NONE
Hubometer:	NONE
Tire Carrier:	NONE



Landing Gear:	2-SPEED JOST A450 MAGNUM - DRIVER SIDE CRANK - REAR AND CROSS BRACING
Tow Hook:	NONE
Chassis Flaps:	ACROSS REAR OF CHASSIS
Underride Guard:	NONE
ABS and RSS:	2S-1M - WABCO
Auxiliary ABS:	NONE
Air Tank Quantity	STANDARD (DEFINED BY ENGINEERING)
Air Tank Material:	STEEL TANKS
Air Dryer:	NONE
CONTROLS	
Gate Open-Close:	FRAME SWITCH - DRIVER SIDE (NEAR LANDING GEAR)
Gate Cab Control:	ELECTRIC SOLENOID - WIRE TO AUXILIARY (RED PIN)
Suspension - Primary Fill-Exhaust:	FRAME SWITCH - DRIVER SIDE (NEAR LANDING GEAR)
Suspension - Cab Control:	ELECTRIC SOLENOID - WIRE TO AUXILIARY (BLUE PIN)
Plumbing Note:	NONE
Liftable Suspension Up-Down:	FRAME SWITCH - DRIVER SIDE (NEAR LANDING GEAR)
Liftable Up-Down Cab Control:	ELECTRIC SOLENOID - WIRE TO STD 7-WAY (BLUE PIN)
SPIF:	NONE
Down Bag Pressure:	EQUALIZING WITH PRIMARY SUSPENSION
Brake Release:	YES - BRAKES DO NOT APPLY WHEN AXLE IS RAISED
Control Box:	TWO POLYCARBONATE; ONE FOR SUSP. & GATE SWITCHES; ONE FOR LIFT AXLES/CONTROLS
Electric Coupler:	7-WAY + 6-WAY (MARKED AUXILIARY)
Hydraulic Oil Tank:	NONE
Hydraulic Hose Fitting:	WINGNUT FITTING
Hydraulic Hose:	STANDARD 108" LONG (4,000 LBS. PSI)
Back-Up Alarm:	NONE
Frame Color:	BLACK
Wheel Color:	N/A
Wheel Guard Insulators:	NONE

Weight: 11,893 lbs.

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.

