

PARTS |

Little Rock, AR:

Portland, ME:

Scranton, PA:

Springfield, MA:

Voorhees, NJ:

Walpole, MA:

Raleigh, NC

SERVICE

833-424-8944

800-325-4253

833-418-9777

800-569-1400

800-854-5306

866-315-0235

800-854-5310

	800-232-6535 *FINANCING AVAILABLE
Item HYDRAULIC DETACHABLE GOOSENECK Description Model: RTN55ETD3-PS TRAILER	
CONSTRUCTION	(4) I-BEAM, CAMBERED, T-1 STEEL
CUSTOM/PAVER SPECIAL	TAPERED FRONT BEAMS (8-3/8" DEEP)
PLATFORM WIDTH	8'-6"
PLATFORM LENGTH	24'
PLATFORM HEIGHT/ROAD CLEARANCE	22"/6"
CROSSMEMBER SPACING	ON 20" CENTERS
FRONT FOLDING RAMPS	41" LONG-WOOD FILLED-ADJUSTABLE
HYDRAULIC SYSTEM	FROM TRACTOR WET LINE
GOOSENECK	NON-GROUND ENGAGING REMOVABLE-HI LIFT
GOOSENECK SUPPORT CYLINDER	HYDRAULIC
GOOSENECK CONNECTION	PIN & STIRRUP TYPE W/VERTICAL AIR LOCK PIN
SWING CLEARANCE	108" & 84"
FIFTH WHEEL HEIGHT	48"-50"-52"-54"-56" LOADED (ADJUSTABLE)
1/8" ALUMINUM TOP COVER	OVER GOOSENECK AREA
AIR BRAKES	16.5" X 7" W/AUTO SLACKS & OUTBOARD DRUMS
ANTI-LOCK BRAKES	NONE (TRAILER GVWR EXCEEDS 120,000#)
SPRING BRAKES	ON ONE AXLE
AXLES	(3) 22,500#, 5/8" WALL
TIRES	(12) 255/70R22.5 (H)
WHEELS	STEEL DISC, 10-HOLE, HUB PILOTED, 8.25" X 22.5"
SUSPENSION	AIR RIDE W/55" AXLE SPACING
SUSPENSION	AIR LIFT 3RD AXLE ONLY
SUSPENSION	+3/-3 HEIGHT CONTROL, AUTO/MANUAL
MANUAL EXHAUST VALVE	ON ALL AXLES
LIGHTS	L.E.D. TRUCK-LITE RUBBER SEALED SYSTEM
BATTERY BACK-UP	AMBER STROBE LIGHTS ON BATTERY-BACK UP
3RD TAILLIGHT PACKAGE	AMBER L.E.D. STROBE WARNING LAMPS
LASH RINGS	(18) TOTAL- 6-PER SIDE (BENT STYLE), 1-EACH SIDE FRONT OF DECK FLAT STYLE ON 45 DEGREE ANGLE, 1-EACH BOLSTER END (FLAT STYLE)
EXTENSION BRACKETS (OUTRIGGERS)	NONE (WELDMENTS ONLY)
DECKING	1-1/2" APITONG-FULL WIDTH
PAINT	GLOSS BLACK (2-PART URETHANE) STEEL PARTS TO MATCH PAINT COLOR
CHAIN HOOK & FLAG HOLDER SLOTS	ON BOLSTERS
PIPE TYPE FLAG HOLDERS	W/THUMB SCREWS 1-PAIR FRONT DECK CORNERS & 1-PAIR ENDS OF REAR LIGHT PANEL
STORAGE BASKETS	(1) AT FRONT OF DECK
REAR DECK	FULL WIDTH-WOOD COVERD, 1-1/2" APITONG
REAR SLOPE (MAIN TO REAR DECK)	3 TO 1 (18 DEGREE) W/FULL WIDTH DECKING
ROLLER STOP@REAR	4" HIGH, WIDTH OF MAIN BEAMS