

HALE

TRAILER

BRAKE & WHEEL



Resale Inventory

A030384

VIN: 125537

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894

Baltimore, MD: 888-601-7500

Concord, NC: 800-438-2250

Delmar, DE: 866-486-1400

Des Moines, IA: 888-673-5011

Elkton, MD: 800-544-7127

Jacksonville, FL: 800-828-3055

Little Rock, AR: 833-424-8944

Portland, ME: 800-325-4253

Raleigh, NC: 833-418-9777

Scranton, PA: 800-569-1400

Springfield, MA: 800-854-5306

Voorhees, NJ: 866-315-0235

Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer



800-232-6535 *FINANCING AVAILABLE

| | | |
|-------|---------------------------------|--|
| 78330 | Custom Options | <p>78330 TK85EFX-5L</p> <ul style="list-style-type: none"> • 85,000-lb. capacity • Overall length – 52'-11" closed • Max open 191'-1" plus 19' non load bearing pullout at rear. • 102" wide • 12'-7" detachable gooseneck , 112" swing clearance • 19" kingpin setting • 49" 5th wheel height • 58" front platform height (102" wide, 24" long) • Heavy duty front pullout/rotate down stabilizing legs • 2-speed landing gear @ rear of gooseneck • Narrow Mono-beam design with 5 stages • Kingpin steering • 19 ft. non-loadbearing pull-out rear extension • Hydraulic lifting leg • Lodar wireless remote system • Wired Pendant control • Approximately 42 deg max steer angle (3rd axle) • Self-contained hydraulics • 13 HP Honda SCU unit in aluminum box with removable cover • 3 axle-72" axle spacing • 4S2M Anti-lock brakes • Steel hub-piloted - cast drums • Red & white conspicuity markings • Epoxy primer • Blasted prior to paint • Color: (BLACK with WHITE DECALS) Trail King 2-part polyurethane |
| 76632 | Hydraulics & Controls - Special | 76632 EFX - Isolate the accelerator for use when manual steering |
| 74028 | Custom Options | 74028 TK85EFX - Add "plastic fenders ILO standard |
| 78702 | Custom Options | 78702 TK85EFX - sliding load bunk to be 48" wide ILO std 36" |
| 74027 | Custom Options | 74027 TK85EFX - Move axles to the rear (SCU in front of the axles) |
| 15004 | Custom Options | 15004 6.75 x 17.5 8-hole polished (XP) aluminum wheel outside (per heel) ILO Std |

DISCLAIMER

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.