

HALE TRAILER BRAKE & WHEEL



Resale Inventory
A030386
VIN: 125872

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894	Little Rock, AR: 833-424-8944
Baltimore, MD: 888-601-7500	Portland, ME: 800-325-4253
Concord, NC: 800-438-2250	Raleigh, NC: 833-418-9777
Delmar, DE: 866-486-1400	Scranton, PA: 800-569-1400
Des Moines, IA: 888-673-5011	Springfield, MA: 800-854-5306
Elkton, MD: 800-544-7127	Voorhees, NJ: 866-315-0235
Jacksonville, FL: 800-828-3055	Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer

800-232-6535 *FINANCING AVAILABLE

78330 TK85EFX-5L

O9999-01-Add

Custom Option 1

Custom Option 1

0110140-ADB-14-...

Item #	Category	Description	Weight (lbs)	Qty
78330	Custom Options	78330 TK85EFX-5L • 85,000-lb. capacity • Overall length – 52'-11" closed • Max open 191'-1" plus 19' non load bearing pullout at rear. • 102" wide • 12'-7" detachable gooseneck , 112" swing clearance • 19" kingpin setting • 49" 5th wheel height • 58" front platform height (102" wide, 24" long) • Heavy duty front pullout/rotate down stabilizing legs • 2-speed landing gear @ rear of gooseneck • Narrow Mono-beam design with 5 stages • Kingpin steering • 19 ft. non-loadbearing pull-out rear extension • Hydraulic lifting leg • Tritronic remote control with auto align function • Remote can be used wireless or cord type • Approximately 42 deg max steer angle (3rd axle)	39,259	

78330	Custom Options	• Self-contained hydraulics • 13 HP Honda SCU unit in aluminum box with removable cover • 3 axle-72" axle spacing • 4S2M Anti-lock brakes • Steel hub-piloted - cast drums • Red & white conspicuity markings • Epoxy-primer • Blasted prior to paint • Color: Trail King 2-part polyurethane • Air ride suspension 72" axle spacing • 25,000 lbs axles (5/8" wall) • Machined aluminum wheels inside/outside • 235/75R x 17.5 Tires • Aluminum Air Tanks • 3 tail light package, Super Nova LED STT lights • One pair 4" round amber LED strobes at rear (4 lights per side) • Micro Nova LED Clearance Lights • 1 Pair Mid-Turn LED lights on 5th stage beam.
76632	Hydraulics & Controls - Special	76632 EFX - Isolate the accelerator for use when manual steering
08009	Paint	Epoxy primer
08024	Paint	S7203 Black with white decals
74028	Custom Options	74028 TK85EFX - Add plastic fenders ILO standard
78702	Custom Options	78702 TK85EFX - sliding load bunk to be 48" wide ILO std 36"
74027	Custom Options	74027 TK85EFX - Move axles to the rear (SCU in front of the axles)
15004	Custom Options	15004 6.75 x 17.5 8-hole polished (XP) aluminum wheel outside (per heel) ILO Std

DISCLAIMER

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.