

HALE

TRAILER

BRAKE & WHEEL



Resale Inventory
A030593
VIN: 514625

SALES | RENTALS | PARTS | SERVICE

| | | | |
|-------------------|--------------|------------------|--------------|
| Allentown, PA: | 800-383-8894 | Little Rock, AR: | 833-424-8944 |
| Baltimore, MD: | 888-601-7500 | Portland, ME: | 800-325-4253 |
| Concord, NC: | 800-438-2250 | Raleigh, NC: | 833-418-9777 |
| Delmar, DE: | 866-486-1400 | Scranton, PA: | 800-569-1400 |
| Des Moines, IA: | 888-673-5011 | Springfield, MA: | 800-854-5306 |
| Elkton, MD: | 800-544-7127 | Voorhees, NJ: | 866-315-0235 |
| Jacksonville, FL: | 800-828-3055 | Walpole, MA: | 800-854-5310 |

haletrailer.com | @haletrailer



800-232-6535 *FINANCING AVAILABLE

| Infinity Flat 48' Wide Spread Air (Model: HCICF12WSA) | |
|---|--------------------------|
| | Est. Wt.: 10,407# +/- 3% |
| Length / Width: 48 feet x 102 inches | |
| Suspension Type: Wide spread air | |
| Frame Rating: 80,000 lbs distributed - 55,000 lbs concentrated in 4 feet | |
| Flooring: 1 1/8 inch aluminum with 4 wood nailer strips | |
| Crossmembers: 12 inch centers - 4 inch jr. I-steel | |
| Single Coil Hauling Package: Included | |
| Side Rails: Exclusive Routed Aluminum (RASR) designed for strength and impact | |
| Chain Cargo Tie Downs: 15 pair recessed in siderails | |
| Stake Pockets: Routed aluminum on 24 inch centers (2 load securement openings between stake pockets) | |
| Rubrail: Integrated with siderail | |
| Main Beams: 130K load bearing flanges | |
| Kingpin: 30 inches | |
| Loaded Fifth Wheel Height: 49 inches | |
| Landing Gear: OEM Standard | |
| Knee Braces: Fabricated on approx. 60 inch C/C | |
| Bulkheads: None standard | |
| Bulkhead Pockets: None standard | |
| Number of Axles: 2 | |
| Axle Spindle: Tapered | |
| Brakes: Spring brakes, auto slacks | |
| ABS: 4S/2M - no cable or tool | |
| Axle Spread: 122 inches - set at rear | |
| Hub and Drums: 10-hole hub-piloted with outboard cast drums | |
| Wheel Ends: Grease in hubs - *** 5-year wheel end warranty ***; Axles vented for tire inflation option | |
| Wheels: 22.5 x 8.25 steel disc wheels - pre-painted white - STANDARD | |
| Tires: 295/75R 22.5 14PR OEM standard tires- STANDARD | |
| Tire Inflation System: None standard | |
| Spare Tire Carrier: None standard | |
| Suspension Detail: Hendrickson AANT23K Intraax air ride | |
| Auto Glad Hand Dump: Installed | |
| Electric Dump Valve: Wired to 7-way auxiliary socket to dump rear axle | |
| Front Corners: Tapered steel | |
| Electrical System: LED: 3 lights/side, 2 lights/side on rear - STANDARD | |
| Paint: Black urethane on steel parts with Infinity decals - STANDARD | |
| Conspicuity Tape: Per NHTSA specs - installed in recess on rubrails | |
| Bumper: Weld-on type - meets underride requirements - painted steel | |
| Mudflaps: 2 sets OEM standard; Spring loaded brackets behind front axle | |
| Winch Track: Full length integrated double L type aluminum on both sides - STANDARD | |
| Sliding Winches: 12: 6 each side; sliding Rope Hook/ Winch Strap Hook Retainers - STANDARD | |
| Winch Straps: None standard | |
| Dock Bumpers: 1 pair rubber on rear | |
| Hubodometer: None standard | |
| Registration Holder: None standard | |
| Tool Box: 1 aluminum double door box - 24 inches x 24 inches x 60 inches - installed Road Side | |
| VIN Plate: Bilingual US/Canadian VIN plate | |

DISCLAIMER

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.